

G-SW-10A-BH-OF-ILS

10A On-Off Ball Handle Toggle General Usage Inline Switch for LED and HID Lights

Product ID: 49853

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

Down: Off, Up: On. Ball handle. Nickel-plated brass handle, facenut and mounting stem. Silver contacts. Mounting stem has 15/32" -32 thread, 15/32" (11.9mm) long, and fits panels up to 9/32" (7.2mm) thick. Wire leads, 6" long. Phenolic housing with plated steel frame. Keyway is in the down position. 10A at 12V DC. Ball handle: 3/8" (9.52mm) long.

Durable silicone rubber bonded to a standard 15/32" -32 thread nickel plated brass hexnut. When the nut is tightened to the stem of a toggle switch, the rubber forms an O-ring seal with the panel. Full boots completely cover a standard 11/16" (17.5mm) handle. Boot seals protect switches from moisture and dirt; colored boots provide color-coding for ready identification of switches.

Switch type - Toggle, Inline
Description - Medium Duty Toggle Switch
Circuitry - SPST
Electrical Rating - 10A at 12V DC
Contacts - Silver
Housing - Black Bakelite with plated steel cap
Up position - On
Down position - Off
Terminals - 2/ 6" wire leads
Handle material - Nickel-plated brass

Handle type - Ball / short
Handle size - 3/8" (9.52mm) Long
Mounting hardware - Nickel plated brass face and hex nut
Mounting stem material - Nickel plated brass
Mounting stem dimensions - 15/32" -32 thread, 15/32" (11.90mm) Long
Mounting hole dimension - 15/32" (11.90mm) Panel Hole
Panel thickness - Up to 1/4" (6.35mm) thick



Frequently Asked Questions (FAQ)



G-SW-10A-BH-OF-ILS

Product ID: 49853

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)