Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDLB-280X2E-VIR

840 Watt LED Light Emitter - 280, 3-Watt LEDs - Visible/Infrared Combo. - 50,400 Lumen - IP68

Product ID: 50436

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDLB-280X2E-VIR LED Light Bar

LEDs: 280 Edixeon® 3 Watt LED Emitters
Dimensions: 72.25"-L 5.25"-H 3.56"-D
Watts: 840
Voltage: 9-42 VDC
Weight:58.5 Lbs
Lighting Configuration: 10° Spot or 35° Flood
Mounting: Inverted U Bracket
Wiring: Deutsch IPD / LADD DT04-2P connector
Amps: 70 (on 12 volts) 35 (on 24 volts)
Lumens: 50,400
Wavelength: 6000K Visible Mode - 750nm, 850nm or 940nm Infrared Mode
LED Life Expectancy: 50,000 hours
Optics Efficiency: 90%
Materials: Aluminum Housing, Polycarbonate Lens
Housing Colors: Black
Spot Beam: 3900`L x625`W
Flood Beam: 1000`L x 950`W

CE Certified
3 year warranty replacement on this LED light. After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a

LEDLB LED Features

Edixeon® 3 Watt LED Emitters
LEDs Driven At 80%
-40 C~ +80C Operating Temp Range
RoHS Compliant
70% Lumen Retention @65,000 hours
LED Chip Op Temp -40C to +125C
IP68 Rated Waterproof to 3 meters

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, Larson Electronics will ship a new replacement.

Buy American Compliant

The Larson Electronics LEDLB-280X2E-VIR LED Light Bar offers high light output and extreme durability combined with the ability to produce either visible or infrared light with only one LED light bar. This IP68 rated LED light bar is waterproof to three meters and produces 50,400 total lumens while drawing only 840 watts of power @70 amps from a 12 volt electrical system. This light can run on any voltage from 9 to 42 volts and provides an extremely rugged lighting solution that is ideal for use in commercial security environments as well as law enforecement and military operations.

The LEDLB-280X2E-VIR LED light bar from Larson Electronics produces a 3900` long by 625` wide light beam with 50,400 lumens of light while drawing only 840 watts @70 amps from a 12 volt electrical system. Two separate power connections are provided, including one that powers the infrared LEDs and one that powers the visible LEDs. Thus, the visible LEDs can be connected to a MRAP or MATV blackout system, enabling the visible light to be turned off when the operator goes into covert mode. 2 rows of 70 LEDs are dedicated to visible lighting, while the other two rows of 70 LEDs are dedicated to infrared lighting. The infrared portion of this LED light can be configured with 750Nm, 850nm or 940nm wavelength IR LEDs. The infrared light produced by this light bar can only be viewed with night vision devices.

Click here to view an article on the Generations of Night Vision and Infrared.

Click Photo to Enlarge

We also offer optional floodlight versions with 35 degree optics to produce a wider beam spread and more light over a larger area nearer the fixture. These LED light bars are IP68 rated and waterproof to 3 meters, sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications. The entire Larson Electronics LEDLB-E series are constructed of extruded aluminum and feature heavier housings, rubber isolated mounts and unbreakable polycarbonate lenses to provide increased durability against vibrations, impacts, waves, hard rains, sand and high winds.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Edison Edixeon® Emitters. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours

Voltage Control: These units are able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These LEDLB series light bars can operate on current ranging from 9 to 42VDC without any modifications necessary as a result. This multi-voltage

capability makes these units ideal for mobile and standalone applications such as those found on commercial boats, heavy equipment and vehicles where power systems don't always operate with 12 volts and external generators, transformers or inverters are impractical.

LEDLB-280X2E-VIR 35° Flood Beam (Opt)



LEDLB-280X2E-VIR 10° Spot Beam (Stnd)



Durability: The LEDLB-E series of LED light bars from Larson Electronics offer IP68 rated construction that is designed to withstand extremes of environmental and operating conditions. The LED lights with the 'E' part number designation are designed for extreme durability and are larger and nearly twice as heavy as their standard counterparts. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three meters and resist ingress of dust, dirt and humidity. The housings are formed from thick extruded aluminum and the lenses are unbreakable polycarbonate. The Edixeon® LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance. We recommend these LED lights for high stress - high vibratory conditions, high humidity climates, very cold areas and rough saltwater conditions. They are also well suited to environments where equipment is used in one temperature extreme and stored in another temperature extreme.
Mounting: Larson Electronics LEDLB series light bars are equipped standard with aluminum mounting blocks which slide within the aluminum housing to allow users to adjust their positioning to match existing or user drilled mounting holes. Each aluminum mounting block has an integrated rubber bushing to absorb vibrations and shocks. To secure the lights in place users simply slide the mounting bolts through the aluminum mounting block and rubber isolator, through the mounting surface, then secure the bolt with a locking nut on the opposite side of the mounting surface. This mounting system enables mounting to flat or round surfaces and allows for minimal 7 degrees of flexibility of angle placement of the light. In this LED emitter light bar model, an additional mounting option is provided. The adjustable, shock insulated mounts are attached to a simple, inverted u-bracket type mount.

Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDLB-280X2E-VIR
Product ID: 50436

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:
LEDLB-280X2E-VIR-Finish-Beam Pattern-Wavelength
Example: LEDLB-280X2E-VIR-Black-S-750nm

Finish	
BLACK	-Black
WHITE	-White

Beam Pattern	
SPOT	-S
FLOOD	-F

Wavelength	
750NM	-750nm
850NM	-850nm
940NM	-940nm

Links (Click on the below items to view):

- CE Certificate
- Eye Safety Information/Certificate
- Military Specification Certificate 1
- MSDS (Material Safety Data Sheet
- Operations Manual
- RoHS Certificate (Restriction of Hazardous Substances)
- SpecSheetArabic
- SpecSheetFrench
- Spectrum Curve (Wavelength Graph)
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map