Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDP10W-240ET

High Intensity LED Light Bar - Trunnion U-Bracket - 24, 10-Watt LEDs - 20,640 Lumen - 9-46VDC

Product ID: 50881

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDP10W-240ET LED Light Bar

Lamp Type: CREE XLamp MC-E® LED
Dimensions: 39.10"-L 2.5"-H 3.5"-D
Watts: 240
Led Drive %: 90%
Voltage: 9-46 VDC
Lighting Configuration: 20° Spot or 40° Flood
Mounting: Trunnion U-Bracket Mount - 270° Adjustable Angle
Wiring: Deutsch IPD / LADD DT04-2P connector
Amps: 20 (on 12 volts) 10 amps (on 24 volts)
Lumens: 20,640
LED Light Color: 6000K
LED Life Expectancy: 50,000 hours
Optics Efficiency: 90%
Materials: Aluminum Housing, Polycarbonate Lens
Housing Colors: Black or White
Flood Beam: Lux @1 meter= 35,000 @3 meters= 7,500
Spot Beam: Lux @1 meter= 72,000 @3 meters= 13,750
Spot Beam: 1450`L x 200`W
Flood Beam: 475`L x 350`W
Weight:16lbs
CE Certified

Internal LED Driver Features

Fast average current control
Programmable off-time switching
Linear dimming input
PWM dimming input
Short protection w/Skip mode
Ambient Op Temp -40C to +125C
Pin-compatible with the HV9910B

View Avg-Mode Driver Control PDF

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

3 year warranty replacement on this LED light. After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, Larson Electronics will ship a new replacement.

Buy American Compliant

The LEDP10W-240ET LED Light Bar with trunnion u-bracket offers high light output and extreme durability combined with a versatile trunnion mounting system that provides 270 degrees of adjustability. This LED unit is ideal for a wide variety of uses including equipment, vehicle, military, law enforcement and is particularly well suited to boating installations. 20,640 lumen output with low voltage and low amp draw, a 50,000 hour rated service life, and 9 to 46 volt compatibility provides operators with an extremely versatile and powerful LED lighting solution.

The LEDP10W-240ET LED light bar from Larson Electronics produces 20,640 lumens of bright light while drawing only 240 watts @20 amps from a 12 volt electrical system. Twenty four CREE XLamp MC-E®10 watt LEDs producing 860 lumens each are paired with high purity optics to produce a 20 degree spread spot beam approximately 1450’ long by 200’ in width. We also offer floodlight versions with a 40 degree beam spread to provide more light over a larger area nearer the fixture, making flood versions ideal for use as work lights. These LED light bars are waterproof to 3 meters, sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications.
An integral Pulse Width Modulation controller, small profile, low power requirements, high durability and versatile mounting system makes these LED light emitters a superior lighting solution for a wide array of applications including but not limited to: military, industrial manufacturing, machine visioning, security and law enforcement, boating, offroading and commercial structure illumination.



This photo shows an open field illuminated only by ambient light at approximately 9:00 pm`.

Click Photo to Enlarge

This shows the LEDP10W-240ET illuminating the field in flood configuration. This unit is ideal for work area illumination where more light is needed closer to the fixture..

Click Photo to Enlarge



This is a close up of the `Larson Electronics` sign. The output gets soft past the sign due to it`s flood configuration, yet the flood beam is still powerful up to 800`.

Click Photo to Enlarge

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units contain advanced drivers which use pulse width modulation to control heat buildup rather than simple voltage regulators which are typically harsh on sensitive electronics and can contribute to early LED failure. These units automatically sense the temperature of each LED and adjust the energy frequency or “duty cycle” accordingly to maintain heat levels within acceptable ranges. This system in essence flashes current at an extremely fast on and off rate to each LED based upon the LED’s core temperature. This flash rate is too fast to detect with the human eye, but provides precise control of the current flowing to each LED and thus the heat it generates. This allows the LEDs to be driven at up to 100% capacity without overheating or visible loss of light output. The LEDs are always driven at the same voltage but the duty cycle, however, is changed to alter how long the LEDs are actually on or off. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance

after 50,000 hours.
PWM Control: The pulse width modulation drivers in this unit also provide secondary benefits through the ability to tap into a provided input wire with an external pulse generator and adjust the duty cycle of the current being applied to the LEDs. Thus you can connect an external dimmer, switch or pulse control and adjust the perceived output of the light, effectively causing the light to flash, dim or brighten to the desired levels. Additionally, this method of controlling light output results in a corresponding drop in amperage draw, so if the duty cycle is cut back to 50% there will be a matching 50% reduction in amperage draw. These units are also able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These LEDP10W series light bars can operate on current ranging from 9 to 46VDC without any modifications necessary as a result. This ability to sense and adjust input current also provides protection against voltage spikes and drops that can occur in vehicle electrical systems which would otherwise result in burning up or premature LED failure without it.

Durability: As well as unparalleled heat control, the LEDP10W series of LED light bars from Larson Electronics also offer IP68 rated construction that is designed to withstand extremes of environmental and operating conditions. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three meters and resist ingress of dust, dirt and humidity. The housings are formed from extruded aluminum and the lenses are unbreakable polycarbonate. The CREE XLamp MC-E® LEDs offer resistance to shocks and vibrations and are rated at 70% lumen maintenance after 50,0000 hours of use.
Adjustable Mounting: The trunnion mounting design on the LEDLB-20ET allows for post-installation angle positioning. This means that by loosening 2 thumb bolts located on either side of the light, the operator can adjust the positioning angle of this light 270 degrees. Then he/she would simply have to tighten thumb bolts to lock the angle in place. No tools are required for adjusting angle.

Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB, LEDP10W and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors.

LEDP10W-240ET 40° Flood Beam (Opt)



LEDP10W-240ET 20° Spot Beam (Stnd)



CONDITIONS

Vin min (V) = 9	toff (us) = 2.9
Vin nom (V) = 12	R1 (kohm) = 50.2
Vin max (V) = 50	L1 (uH) = 3.0
Vo min (V) = 6.5	L-Pk (A) = 2.9
Vo nom (V) = 6.8	L-rms (A) = 2.9

Vo max (V) = 7	**Ipk (A) = 2.5**
I-LED (A) = 2.2	**R2 (ohm) = 0.10**
Efficiency = .85	**I-FET (A) = 2.2**
fsw nom (kHz) = 150	**fs min (kHz) = 77**
Ts nom (us) = 6.666667	**fs max (kHz) = 301**
Base frequency-	= 36~37Khz @ 12V
Amplitude of pulse width-	= 27Ms
Outside: External dimmer-	= 500Hz
Inside : Current sensing from-	77KHz at 12V to 300KHz at 50V

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDP10W-240ET

Product ID: 50881

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

LEDP10W-240ET-Beam Pattern-Housing Color-Color Temp

Example: LEDP10W-240ET-SP-BLK-60K

Beam Pattern	
SPOT	-SP
FLOOD	-FL

Housing Color	
BLACK	-BLK
WHITE	-WHT

Color Temp	
6000K	-60K
4300K	-43K
3000K	-30K

Links (Click on the below items to view):

- **CE Certificate**
- **MSDS (Material Safety Data Sheet**
- **Operations Manual**
- **RoHS Certificate (Restriction of Hazardous Substances)**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**