

WAL-18LED-BP

LED Light Tower - Battery Powered - Portable work light - 18 Watt LED Lights on Telescoping Pole

Product ID: 50948

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

WAL-18LED-BP Portable LED Light Tower

Power: 12VDC

Battery: AGM Lead Acid Deep Cycle, 12VDC, 22 amp hr, 600 Cycles

Lamps: 2- 9 watt LED Light Bars, IP68 Rated

Total Lamp Watts: 18 watts

Tower: Adjustable Aluminum 3-8 Feet Total Height

Case: Pelican Style Watertight with Wheels and Handle

Dimensions: 22"-H x 9"-L x 14" W - Weight-48lbs

Total Lumens: 1368

Charging: 5 Hour charge time, 115VAC Built in AC Charger

Ratings: FAA, DOT, CAB, IA, TA Approved Air Transport

Mounting: Portable Tower with 2- 3 Foot Outriggers

Run Time: Up To 8 Hours on Single Charge at Full Power

Operating Temp: -40 F/C and + 185F / 85C

Certification

CE Certified

EN55015 EMI

EN61547 EMS

EN62471 Photo-biological Safety

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Made in the USA

The WAL-18LED-BP LED light tower is a fully portable and rechargeable unit and produces a wide flood of light ideal for use on construction sites and emergency scenes. This light tower offers a long list of features including versatile power and recharging options and provides an extremely rugged lighting solution that is ideal for use in commercial and industrial applications as well as emergency services and law

enforcement environments.

The WAL-18LED-BP LED light tower is a self contained and portable light tower package that offers high power and extreme portability in a compact and durable design. This unit produces 1368 lumens that covers over 40 square feet and can run for up to 14 hours at full power on a single full charge of its on-board batteries. This LED light tower includes two 9 watt LED lights mounted to a telescoping aluminum mast that can be adjusted from 3 to 8 feet in total height. The entire package weighs 48 pounds and measures 22 inches tall by 9 inches in length by 14 inches wide, making it very easy to stow and deploy.

This portable LED light tower is designed to be easily deployed and can be set up in less than thirty seconds after a single practice run to familiarize yourself with its operation. Approximately the size of a carry on suitcase, this unit weighs only 48 lbs and includes a collapsible handle and wheels for easy transport around the deployment area. The heavy duty waterproof Pelican style case contains all of the operational equipment and provides secure protection against damage from impacts and contaminants when closed. When fully deployed, this unit will withstand 65 mph winds and can be extended to a total of 8 feet in tower height for optimal illumination of the target area.



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



without illumination.

[Click Photo to Enlarge](#)

Backyard



Illuminated by the WAL-18LED-BP .

[Click Photo to Enlarge](#)

The WAL-18LED-BP portable light tower incorporates a long list of impressive features including:

Power: AGM sealed lead acid battery, 22 amp hour, 12 VDC deep cycle with built-in charging system and a 600 charge life cycle or 3-5 year life cycle. This unit offers 4 power options, including an internal battery pack, the ability to allow AC recharging while in use, and use as a jump and carry external battery pack with an included special plug. A built in AC charger (wall charger) allows operators to easily recharge the battery, even while in use. This portable tower also accepts low voltage input from vehicles and other battery packs to power the light or charge the battery. A DC port (cigarette plug socket) allows users to power other DC devices, in effect allowing this unit to double as a portable 12VDC power supply. Included LED indicators provide operators with the current battery charge conditions.

LED Light Bars: This tower includes two 9 watt LED light heads that are IP68 rated waterproof to three meters and constructed of extruded aluminum with polycarbonate lenses for the ultimate in durability. Each LED unit is controlled by a separate switch, allowing operators to use the lights together or independently

based on lighting requirements and desired battery run time. Two LED light bars will run 14+ hours, while a single LED emitter will run 29 hours. The LED light bar emitters are attached to the telescoping pole via an adjustable "T" style bracket. The LED light bars can be positioned at various ideal angles and the assembly will hold that position until changed by the operator. A single coil cord provides power from the battery to the LED light heads.

Telescoping Tower: The aluminum telescoping tower on this unit is comprised of four sections and extends and locks into place much the same as a camera tripod. The user simply opens the case, folds out the telescoping tower and then locks it into position with a simple latching mechanism. The user can then extend the tower anywhere from 3 to 8 feet in total height and simply tightens the locking clamps to lock the tower in position. The mast from ground level to top of light is 8'. The actual pole is 6.5 feet long and the 18" case makes the total length 8 feet. Stability is provided by two stainless steel spring loaded aluminum support legs that unfold from the case as well and are extended to 30 inches length and then locked into place. This tower and support system provides a stable light platform even in windy conditions up to 65 mph.

Watertight Case: All the components of this portable light tower stow away within the watertight Pelican style case. This case includes a carrying handle and wheels to provide easier transport around the deployment area and measures only 22 inches tall by 9 inches in length by 14 inches wide. There are no loose parts and all components fit within the case for easy transport. All parts and controls are easily accessible simply by opening the front of the case, with controls located at the top and the battery assembly at the bottom. The entire unit weighs only 48 pounds and can be easily stowed in back seats or behind the seat of a pickup truck. This easy opening case and collapsible tripod and support system results in a portable high power infrared light tower that can be deployed in less than thirty seconds after a single practice run.

Additional Features:

Battery and lights will function at -40 F/C and + 185F / 85C.

Battery charger has charge indicator to show level of charge.

One year replacement warranty on battery pack and charger.

Approved for continuous charging.

Rocker switch for internal and external power operation.

220V 50/60hz charger available.

Option to order unit with infrared LED light heads in the 850 or 940NM ranges.

FAA, DOT, CAB, IA, and TA approved for air transport.

Applications: Applications include emergency response work, first responders for utility repairs and non-hazardous location lighting. Basically, applications where operators need to deploy lighting without the benefit of traditional high voltage power sources. Depending on the position of the light heads, operators can cover 25-40 square feet with foot candle output which is about 3 times as bright as a well lit mall parking lot.

NOTE: This unit ships in either orange or black case colors depending upon stock. Contacts sales@larsonelectronics.com if you require a specific color.

Made in USA Quality

1. Watertight Pelican Style Case
2. IP68 Rated LED Light Heads are Waterproof and Dustproof
3. Aluminum Tower Mast and Spring Loaded Aluminum Outrigger Legs.
4. Nothing To Wire or Connect. All Parts Contained Within Case.
5. 5 Hour Runtime on a Single Charge.
6. Integral Handle and Wheels for Easy Transport.
7. High Power LEDs Produce Equivalent of 2880 Lumens.
8. One Year Replacement Warranty on Battery Pack and Charger
9. Adjustable From 3 to 8 Feet in Height.

Superior LED Benefits

1. 50,000+ hour lifespan.
2. Cool operation.
3. 100% recyclable.
4. No toxins-lead, mercury.
5. No UV light, infrared radiation or CO2 emissions.
6. Bright, even light maintains consistent color over time.
7. Instant on/off – No flickering, delays or buzzing.
8. No lenses or filters to reduce output.
9. Vibration/impact resistant.
10. Compact size..
11. Less frequent outages, higher output.

Frequently Asked Questions (FAQ)

WAL-18LED-BP

Product ID: 50948

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Dimensional Drawing 2D](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [Operations Manual](#)
- [SpecSheetFrench](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)