

EPPK-20A

Explosion Proof Fixture/Extension Cord Plug - 20 Amp Rated

Product ID: 50968

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPPK-20A

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPPK-20A Explosion Proof PLug

Amp Rating:20

Dimensions: 2.78"-L 1.75"-W

Configuration: 3 Pole 2 Wire

Suitable Cable Diameter: .538" to .639"

Voltage Rating: 125V 1HP or 250V 2HP

Compatibility: [EPO-20A Receptacle](#)- Crouse Hind™ ENR Receptacles

Cross Interchangeability: Crouse Hind™ ENP5201 and Hubble Killark UGP-20231-UGP-20232 ACCEPTOR® plugs

Certifications - Compliance

Class 1, Div 1 & 2 Groups B,C,D

Class 2 Div 1 & 2 Group G

Class III

CSA Type 7BCD, 9G

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664


E-mail: sales@larsonelectronics.com

The Larson Electronics EPPK-20A Explosion Proof Plug is a watertight plug and is rated for Class 1, Division 1 and 2 and Class 2, Division 1 and 2 and is suitable for use in areas where coal dust and petrochemical vapors may be present.

The EPPK-20A explosion proof plug is rated at 20 amps and along with our with our EPP-15A series plug is compatible with our EPO-20A explosion proof 20 amp outlet. This plug can only

be used in T style outlets and in order to retain explosion proof safety it must be mated to an explosion proof outlet. This plug is designed to lock into compatible receptacles by twisting the plug body until an audible click is heard, which indicates the plug is securely connected. Once locked into place this plug will not accidentally pull out. This plug is ideal for applications where moisture and corrosion is a problem and well suited for use in marine and manufacturing environments.

This explosion proof plug features non sparking aluminum construction, longer housing for easy handling, specially designed brass pins for secure full length pin contact and 20 amp current rating.



[Click Photo to Enlarge](#)

Inter-Compatibility: These plugs will fit non-explosion proof standard receptacles (NEMA 5-20R for 125V version, NEMA 6-20R for 250V version). These plugs will work with Course Hind ENR Dead Front Interlocked receptacles. These plugs are cross-interchangeable with Crouse Hind™ ENP5201 and Hubble Killark UGP-20231-UGP-20232 ACCEPTOR® plugs.

Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Motor-Generator Sets, Compressors, Wet areas or Locations Where Petrochemical Vapors are Present.



Frequently Asked Questions (FAQ)

There are no Fags



Image: EPPK-20A



Image: EPPK-20A



Image: EPPK-20A



Image: EPPK-20A

EPPK-20A

Product ID: 50968

Export Control Classification Number (ECCN): EAR99

Options:

EPPK-20A-Voltage HP

Example: EPPK-20A-125V-1HP

Voltage HP	
125V 1HP	-125V-1HP
250V 2PH	-250V-2HP



Links (Click on the below items to view):

- **Operations Manual** (<https://www.larsonelectronics.com/images/product/Manual/50968.PDF>)
- **HigResPic1** (<https://www.larsonelectronics.com/images/product/HigResPic1/50968.JPG>)
- **HigResPic2** (<https://www.larsonelectronics.com/images/product/HigResPic2/50968.JPG>)
- **HigResPic3** (<https://www.larsonelectronics.com/images/product/HigResPic3/50968.JPG>)
- **HigResPic4** (<https://www.larsonelectronics.com/images/product/HigResPic4/50968.JPG>)
- **HigResPic5** (<https://www.larsonelectronics.com/images/product/HigResPic5/50968.JPG>)
- **HigResPic6** (<https://www.larsonelectronics.com/images/product/HigResPic6/50968.JPG>)
- **HigResPic7** (<https://www.larsonelectronics.com/images/product/HigResPic7/50968.JPG>)
- **HigResPic8** (<https://www.larsonelectronics.com/images/product/HigResPic8/50968.JPG>)
- **ISO 9001 Certification** (<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate** (<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map** (<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)