Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPP-20A-1P

Explosion Proof Industrial Line Cord & Plug - 20 Amp Rated - 1' Pigtail - Line Cord- Hot Work Permit

Product ID: 64170

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPP-20A-1P

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPP-20A-1P Explosion Proof Plug
Amp Rating: 20
Dimensions: 2.78"L x 1.75"W
Configuration: 3 Pole 2 Wire
Suitable Cable Diameter: .538" to .639"
Wiring: 1` Pigtail - 12/3 SOOW Cord
Plug: 5-20P or 6-20P Male Plug - Explosion Proof
Connector: 5-20C or 6-20C Female Plug - Industrial
Comparability: EPO-20A Receptacle- Crouse Hind™ ENR Receptacles
Cross Interchangeability: Crouse Hind™ENP5201 and Hubble Killark UGP-20231-UGP-20232 ACCEPTOR® plugs

Approvals/Ratings
Class I Divisions 1 & 2 Groups B, C and D
Class II Divisions 1 & 2 Group G
Class III
CSA Type 7BCD, 9G
Hot Work Permit

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671


Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The EPP-20A-1P from Larson Electronics is an Explosion Proof Plug that is rated at 20 amps and along with our with our EPP-20A series plug is compatible with our EPO-20A explosion proof 20 amp outlet. This plug can only be used in T style outlets and in order to retain explosion proof safety it must be mated to an explosion proof outlet. This plug

is designed to lock into compatible receptacles by twisting the plug body until an audible click is heard, which indicates the plug is securely connected. Once locked into place this plug will not accidentally pull out. This plug is ideal for applications where moisture and corrosion is a problem and well suited for use in marine and manufacturing environments.

This watertight plug is rated for Class I Divisions 1 and 2 and Class II Divisions 1 and 2 and is suitable for use in areas where coal dust and petrochemical vapors may be present. This explosion proof plug features non sparking aluminum construction, longer housing for easy handling, specially designed brass pins for secure full length pin contact and 20 amp current rating.

Hot Work Permit: This line cord is approved for hot work permit applications and allows operators to use their non-explosion proof equipment within an explosion proof environment. The alternative to this line cord is to convert non-explosion proof equipment to explosion proof plugs which can quickly become prohibitively expensive. Having the ability to use non-explosion proof equipment within hazardous areas when a job requires it makes this line cord able to greatly increase the versatility of non-explosion proof equipment. These industrial line cords are popularly used in hazardous locations when hot work permits have been acquired. We also offer class rated extension cords for use within explosion proof and hazardous location environments without hot work permits.



Click Photo to Enlarge

Inter-Compatibility: These plugs will fit non-explosion proof standard receptacles. These plugs will work with Course Hind ENR Dead Front Interlocked receptacles. These plugs are are cross-interchangeable with Crouse Hind™ENP5201 (125V) or ENP6202 (250V) and Hubble Killark UGP-20231 (125V) or UGP-20232 (250V) ACCEPTOR® plugs.

Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Motor-Generator Sets, Compressors, Wet areas or Locations Where Petrochemical Vapors are Present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at

800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPP-20A-1P

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPP-20A-1P

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPP-20A-1P

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPP-20A-1P

Product ID: 64170

Export Control Classification Number (ECCN): EAR99

Options:

EPP-20A-1P-Voltage
Example: EPP-20A-1P-2023-125V

Voltage	
120V	-2023-125V
250V	-2023-250V

Links (Click on the below items to view):

- **Operations Manual**(https://www.larsonelectronics.com/images/product/Manual/64170.PDF)
- **Wiring Diagram**(https://www.larsonelectronics.com/images/product/WiringDiagram/64170.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/64170.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/64170.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/64170.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/64170.JPG)
- **Video1**(https://www.youtube.com/watch?v=UR1M3j1ICnY)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)