Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

**RFM-LED-15.5CL**

**30 Watt Roof Mount Light RFM-LED-15.5CL with 15.5 inches of shaft from lamp center to handle center**

**Product ID: 64204**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

LED Roof Mount Spotlight. This particular LED spotlight projects a beam approx. 600` in length by 70` in width. Rotation and up/down directional control with handle at the end of the post inside the vehicle. 15.5 inches of post, measuring from the center of the lamp to the center of the handle. 10 inches of post are exposed (2.75 inches are inside the lamp head and 2.75 inches are inside the handle attachment). 2 3/4" roof clearance (measured from top of roof surface to bottom of headliner).
30 watt, PAR46 LED bulb.
Roof mount light comes complete with `O` ring for a leak-proof design, universal mounting bracket, installation template, and installation instructions.
Chrome or black, UV resistant polycarbonate lamp housing. Chrome version has chrome plating.
12 volt spotlight, 30 Watt PAR46 LED bulb with aluminum reflector and impact resistant polycarbonate lens
Twisting the handle moves lamp head up and down, while turning rotates the light
On/off switch located just above the rubberized handle for easy access with the thumb
Available in 12 volts. (Most American consumer vehicles require 12 volts. Most military

vehicles and some heavy equipment require 24 volts.)

**Roof Mount Light in Action**

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

# Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364







**RFM-LED-15.5CL**

**Product ID: 64204**

**Harmonized System (HS) Code:** 9405.41.84.10
**Export Control Classification Number (ECCN):** EAR99

**Options:**

**RFM-LED-15.5CL-Finish**

**Example: RFM-LED-15.5CL-B**

| Finish | |
|---|---|
| BLACK | -B |
| CHROME | -C |

Links (Click on the below items to view):

- **Operations Manual**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**