

HALPRM-1000WMH-EB

1000 Watt Metal Halide Light with External Ballast - Class 1 Division 2 Groups A-D - T3b

Temperature

Product ID: 64209

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HALPRM-1000WMH-EB Metal Halide

Lamp Type: Metal Halide

Dimensions: 22" W X 11" D X 26 1/4" H w/Yoke Mount

Watts: 1000

Lumens Per Watt: 100-115 Approx.

Voltage: 120V, 208V, 240V, or 277V / 220-480 OPT

Lighting Configuration: Flood Pattern

Mounting: Slip Fit Pole Mount or Zinc Trunnion

Weight: 45 lbs

U.L. Listing: Outdoor Marine Approved

Total Lumens: 110,000

Wiring: 3/4 inch Threaded NPT Conduit Entrance

U.L Ratings

Class I, Division 2 Groups A, B, C, D

UL Standard 1598 (supersedes UL Standard 57)

UL Standard 844

Class I Div. 2 UL Standard 1598A

Max OP Temp 325°C (T1 NEC ID Number)

Operating temperature 325 degrees C (T3b)

Not Approved For Confined Spaces

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The extremely durable Larson Electronics HALPRM-1000WMH-EB metal halide hazardous area light produces exceptional illumination from a 1000 watt metal halide lamp. Constructed of die cast aluminum and U.L. listed for marine use, this metal halide fixture includes a remote ballast within a NEMA enclosure and ideal hazardous area

lighting solution for areas where wet or corrosive environments are encountered.

The rugged HALPRM-1000WMH-EB metal halide light fixture with remote ballast is weatherproof and suitable for use in wet, outdoor and marine environments, making it an ideal lighting solution for industrial applications, boat docks, building exteriors and outdoor work areas. The lamp housing is weatherproof and constructed of pressure cast copper free aluminum with an architectural bronze Polyester finish. The lens door is pressure-cast copper-free aluminum, and secured with 1/4" diameter captive stainless steel slotted hex-head bolts. By removing the ballast from the fixture and mounting it in the external NEMA enclosure, the weight of the fixture is reduced, making it easier to mount at height. This unit features an integral multi- tap ballast with a choice of 120V, 208V, 240V, or 277V connections. Also available are optional and separate 220V and 480V configurations. Choose voltage options when ordering.

The optical assembly includes thermal shock and impact resistant door glass with a pressure-cast copper-free aluminum door frame and heavy duty, high temperature silicone rubber seal. The lamp socket is a specification grade mogul base porcelain unit with heavy gauge brass, a nickel-plated, double lamp-grip screw shell and spring-loaded center contact. The reflectors are a double segment compound parabolic design with Alzak® finish for maximum efficiency.

Mounting choices include:

1. Yoke mount: zinc plated steel yoke with architectural bronze Polyester finish.
2. Poletop mount: built-in slip-fitter for internal wiring. Adjustable laterally and vertically. Slip fits 2" or 2 1/2" pipe. Architectural bronze Polyester finish.

This hazardous area light is rated IP65, U.L. standard 844 and 1598 compliant, approved Class 1 Division 2, Groups A,B,C,D, and U.L. listed 1598A for outdoor salt water marine environments. The integral multi-tap ballast is protected within the weatherproof housing and has primary electrical taps for 120V, 208V, 240V, and 277V. This lamp is suitable for use in areas where flammable petrochemical vapors are sometimes present in a non-confined, open air work space and IS NOT suitable for use in confined spaces.

This 1,000 watt metal halide light is highly durable, produces 110,000 lumens in a wide flood pattern, and has a maximum operating temperature of 325°C (T1 NEC Identification Number). All hardware on this unit is resistant to rain, snow, salt water and corrosive chemicals. The heavy duty design and attractive finish of this fixture makes it a popular choice for outdoor applications regardless of whether the locations are designated hazardous or not.

LAMPS: Use only lamps specified on nameplate. Bulb not included with fixture. Observe lamp manufacturer's recommendations and restrictions on lamp operation, particularly ballast type, burning position, etc.

Made in the USA Quality

1. High Efficiency Metal Halide lamp.
2. Approximately 100-115 Lumens per Watt
3. Rugged Pressure Cast Aluminum Housing.
4. Thermal Shock and Impact Resistant Glass Lens Door.
5. Heavy Duty Door Gasket.
6. Socket: Mogul Base heavy gauge brass, nickel-plated double lamp-grip screw shell .
7. Low Maintenance.
8. Slip Fit Pole Mount or Zinc Plated Yoke Mount.
9. Heavy Duty High Heat Silicone Door Glass Seal.
10. Architectural Bronze Polyester Finish.

Metal Halide Benefits

1. Long lamp life.
2. High efficiency and low amp draw after initial startup.
3. High durability and reliability.
4. High output and very good color rendering.
5. Vibration and shock resistant.
6. Low maintenance.

Frequently Asked Questions (FAQ)







HALPRM-1000WMH-EB

Product ID: 64209

Export Control Classification Number (ECCN): EAR99

Options:

HALPRM-1000WMH-EB-Voltage

Example: HALPRM-1000WMH-EB-120V60

Voltage	
120V/60HZ	-120V60
220V/50HZ	-220V50
240V/60HZ	-240V60
277V/60HZ	-277V60
480V	-480V

Links (Click on the below items to view):

- [Dimensional Drawing 2D](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [Video1](#)
- [Video4](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)