

HAL-RSLED-240W

185W Hazardous Location Wall Pack LED Light - C1D2 - 18,500 lms - Surface/Pendant Mount - IP68

Product ID: 69105

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-RSLED-240W LED Light

Lamp Type: LED

Dimensions: 15.75"L x 15.75"W x 7.28"H

Weight: 24 lbs

Voltage: Universal- 90-305V AC, 50/60Hz

Total Watts: 185W

Total Lumens: 18,500

Luminous Efficacy: 100 Lm/W

LED Lamp Life Expectancy: 100,000+ Hours

Color Temp: 5700K, Cool White (Also available in 4000K and 2700K)

Beam Angle: 120°

Power Factor: ~0.98

Ambient Operating Temperature Range: -30°C to +65°C

Temperature Rating: T4

Ingress Protection: IP68

Housing Material: Die Cast Aluminum

Lens Material: Tempered Glass

Mounting: Surface or Pendant

Wiring: 10" 16/3 SOOW Cable with Flying Leads

Wiring Hub: 3/4" NPT

Housing Color: Grey

Ratings

Listed for United States, Canada, Europe, International
Class I, Division 2, Groups A,B,C,D

IEC Ex / ATEX - Ex ec IIC T4 Gc

Approved for Zone 1, Zone 21

NRTL Certified to UL 844

NRTL Certified to UL 1598

NRTL Certified to C22.2 No. 137

NRTL Certified to C22.2 No. 250.0

NRTL Certified to IEC 60079

NRTL Certified to EN 60079

T4 Temperature Rating

PSE Certified, SAA Certified

IP68 Waterproof

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









HAL-RSLED-240W

Product ID: 69105

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

HAL-RSLED-240W-Color Temp-Mount

Example: HAL-RSLED-240W-57K-SUR

Color Temp	
5700K	-57K
4000K	-40K
2700K	-27K

Mount	
SURFACE	-SUR
PENDANT	-PEN

Links (Click on the below items to view):

- [Dimensional Drawing 2D](#)
- [IES \(Photometric File\)](#)
- [Operations Manual](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)