Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

XLE-PA-IP20-CS.50-50A-3PH-250V-3P4W-P

California Standard CS8365C, Twist-Lock 50-Amp Male Plug, 250V Delta 3PH 3P4W, IP20

Product ID: 70006

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

XLE-PA-IP20-CS.50-50A-3PH-250V-3P4W-P Industrial Plug

Type: California Standard 50A Twist Lock Plug
Dimensions:

Weight: 1.2 lbs

Voltage: 250V Delta AC

Amps: 50A

Max Wattage: 12500W

Configuration: 3-pole, 4-wire
Gender: Male
Dielectric Voltage Withstand: 2,000V Minimum
Operating Temperature: -40°C to +75°C
Color: Black/White
Housing Material: Black Supertough Nylon
Hardware Material: Stainless Steel, Polyester, Brass
Terminal Gauge Accepted: 10-6 AWG
Cord Diameter Accepted: 0.830"-1.25"

Ratings/Features:
Listed for United States and Canada

Mating Plug: XLE-PA-IP20-CS.50-50A-3PH-250V-3P4W-P
Mating Receptacle: %Recpt%
Mating Connector: XLE-PA-IP20-CS.50-50A-3PH-250V-3P4W-C
Mating Inlet: XLE-PA-IP20-CS.50-50A-3PH-250V-3P4W-B

Cross Compatible: CS8365C

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The XLE-PA-IP20-CS.50-50A-3PH-250V-3P4W-P from Larson Electronics is a California Standard CS8 Plug for completing electrical connections and power distribution systems. This 3-pole, 4-wire acces accepts 10-6 AWG terminal gauges and 0.830"-1.25" cord diameters. Listed for the US and Canada, amp unit operates on 250V Delta 3-Phase AC 50/60 Hz.

The Larson Electronics XLE-PA-IP20-CS.50-50A-3PH-250V-3P4W-P is a California Standard 50-amp rated twist
Male Plug for industrial applications. Capabile of supporting up to 12500W, this 50-amp XLE-PA-IP20-CS.50-50A
250V-3P4W-P is cross compatible with CS8365C, operates on 250V Delta 3-Phase AC and operates on a 3-pole,
configuration. Capable of withstanding a dielectric voltage of 2,000V (minimum), the accessory accepts a termi
gauge size of 10-6 AWG and a cord diameter range of 0.830"-1.25". The device is constructed from durable ma
with stainless steel, polyester and brass hardware, for a long-lasting wiring device solution.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and up
parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or
accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability h
made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-3
6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet
specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

XLE-PA-IP20-CS.50-50A-3PH-250V-3P4W-P

Product ID: 70006

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**