

IL-LED-27R

27 Watt Round LED Flood Light - 2160 Lumens - Nine 3-Watt LEDs - 10-32 Volt DC - IP67

Waterproof

Product ID: 70025

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

IL-LED-27R LED Light Bar

Lamp Type: CREE XLamp XR-E® LED

Dimensions: 4.5" Diameter, 1 1/2" Thick

Watts: 27

Lumens: 2160

Amps: 2.2 (on 12 volts)

Mounting: Flat Surface - Stainless Steel Bracket

LED Light Color: 6000K

Lighting Configuration: 30° Flood

LED Life Expectancy: 30,000 hours

Materials: Aluminum Housing, Polycarbonate Lens

Ratings/Approval

IP 67 Waterproof Rated

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The IL-LED-27R LED Flood Light offers high light output from a compact form factor and is ideal for a wide range of uses including heavy equipment, boating, vehicle, military, law enforcement and industrial manufacturing applications. This unit produces a 2160 lumen light output with very low amp draw, 30,000 hour service life and 10 to 30 volt compatibility which provides operators with a compact and powerful LED lighting solution.

The IL-LED-27R LED light bar from Larson Electronics produces 2160 lumens of bright light while drawing only 27 watts @2.2 amps from a 12 volt electrical system. Nine high output three watt LEDs producing 240 lumens each are

arranged in a circle and paired with high purity optics to produce a wide 30 degree flood beam. These LED light bars are IP67 waterproof, sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units contain advanced drivers which use pulse width modulation to control heat buildup rather than simple voltage regulators which are typically harsh on sensitive electronics and can contribute to early LED failure. These units automatically sense the temperature of each LED and adjust the energy frequency or "duty cycle" accordingly to maintain heat levels within acceptable ranges. This system in essence flashes current at an extremely fast on and off rate to each LED based upon the LED's core temperature. This flash rate is too fast to detect with the human eye, but provides precise control of the current flowing to each LED and thus the heat it generates. This allows the LEDs to be driven at up to 100% capacity without overheating or visible loss of light output. The LEDs are always driven at the same voltage but the duty cycle, however, is changed to alter how long the LEDs are actually on or off.

Durability: As well as unparalleled heat control, the IL-LED-27R LED light bar from Larson Electronics also offer IP67 rated construction that is designed to withstand extremes of environmental and operating conditions. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three meters and resist ingress of dust, dirt and humidity. The housings are formed from extruded diecast aluminum and the lenses are unbreakable polycarbonate. We recommend these LED lights for high humidity climates, very cold areas and rough saltwater conditions. They are also applicable to environments where equipment is used in one temperature extreme and stored in another temperature extreme.

Mounting: Each unit is equipped with a stainless steel mounting bracket. Each aluminum mounting block has an integrated rubber bushing to absorb vibrations and shocks.

Frequently Asked Questions (FAQ)









IL-LED-27R

Product ID: 70025

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)