

EPL-EMG-24-4L-T8

Explosion Proof T8 Fluorescent Light with Emergency Battery Backup -2ft 4 Lamp - Paint Booth Approve

Product ID: 70373

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-EMG-24-4L-T8 Explosion Proof

NRTL Listed for United States & Canada

Lamp Type: Fluorescent

Dimensions: W-22.50" L-27" H-8.5 "

Weight: 57 lbs.

Voltage: Multi- 120V-60hz 220V-50hz 240V-60hz 277V-60hz

Total Watts: 68 Watts

Total Lumens: 5,300

Luminous Efficacy: 78 Lm/W

Lamp Life Expectancy: 24,000+ Hours

Color Temp: 4100K

Beam Angle: N/A

Ambient Operating Temp Range: -30 C to 70 C

Operating Temp Rating: T6 Rated

Maximum Case Temp: 90 C

Minimum Operating Temp: -30 C

Mounting: Bracket Standard - Pendant Optional

Wiring Hub: 1/2 inch threaded

***Wattage totals are lamps only and may vary with different lamps.**

Ratings

Class 1 Division 1, Groups C and D

Class 1 Division 2, Group A,B,C,D

Class II Division 1- 2, Groups E,F,G

NRTL Certified to UL 844, 924

NRTL Certified to UL 1598 Marine Type

NRTL Certified to UL 595 Outdoor Marine Type (Saltwater)

Listed for Paint Spray Booths*

California Title 24 Compliant

Switch Leg for Powering Light On/Off

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPL-EMG-24-4L-T8 Explosion Proof Fluorescent Light Fixture is NRTL Listed For United States and Canada Class 1 Division

1, Class 2 Division 1 and ideal for hazardous locations where flammable chemical/ petrochemical vapors exist or have the potential to exist.

*****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS HAZARDOUS LOCATION LIGHT FIXTURE*****

The EPL-EMG-24-4L-T8 fixture is a 2 foot long, 4 lamp, Class 1 Division 1 and Class II Division 1&2 explosion proof fluorescent light and an ideal choice for use in applications where space is at a premium. This T6 temperature rated fixture comes standard with F17-T8 lamps and is available with a variety of lamp options which are listed below. The lamps are protected by heat and impact resistant Pyrex tubes and the fixture is constructed of copper free aluminum alloy. The lamp reflectors are corrosion resistant heavy gauge aluminum and coated with a high gloss reflective finish. This fixture is multi-voltage capable and for use in paint spray booths.

The EPL-EMG-24-4L-T8 provides operators in hazardous locations with a compact, reliable and affordable lighting solution that provides the best explosion proof protection available without sacrificing light quality or fixture durability.



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)

This fluorescent light works, mounts and is wired like our EPL-24-4L-T8 explosion proof fluorescent light fixtures. The main difference is that we attach an extra Bodine ballast box to the unit that adds the emergency light functionality to the fixture. This explosion proof emergency light will run the standard 90 minutes after power is lost. The light recharges the battery once standard electrical power is restored. Standard configuration includes a single emergency ballast that will run a single lamp at 1325 lumens for 90 minutes. For an additional charge, a second ballast can be added to run a second lamp for 2650 total lumens output for 90 minutes. The battery backup unit includes a switched leg for turning the light fixture on/off without kicking the unit into emergency mode.

NOTE ON LAMPS: This unit comes equipped with an electronic ballast and F17-T8/841 bulbs which produce 1325 lumens per bulb and have a rated lifespan of 24,000 hours.

Additional mounting options: Unless otherwise specified, our standard, most popular configuration is the bracket end mounting shown in the photos above. We also offer a pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit).

Standard Bracket Mounts: Each bracket is cinched to the bracket mounting peg on each side of the light. The angle of the bracket is set by tightening two cap screws on either side of the bracket. The cap screws act as a set screw. The bracket itself is mounted via a single bolt hole at the top the bracket. There are two brackets, one on each end of the light. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be removed from the brackets by loosening the cap screws that hold the bracket to the mounting peg. The first picture shown above illustrates the ballast side bracket and also shows the access caps for changing the bulbs. The second picture shows the bracket at the opposite end of the fluorescent light.

Made in USA Quality

1. Each unit dialectically tested.

Lamp Options

F17-T8 – 1325 lumens per bulb (2650 lumens total),

2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture, where other models may only offer one or three choices.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy.
4. Over-sized, finned ballast housing for 800 mA fixtures provides more heat dissipation and extends ballast life. Ballast housing easily accessible and externally mounted. **24,000 hours life, 4100 Kelvin color**
Top and bottom covers secured with nuts and bolts, instead of threaded through holes, which can be damaged with dirt.
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. A wrench is used to unscrew the end caps for relamping the fixture, while other models require the "tap and knock off" method to loosen the end cap.
7. Explosion proof, impact and heat resistant Pyrex tubes provide lamp protection.



Frequently Asked Questions (FAQ)

EPL-EMG-24-4L-T8

Product ID: 70373

Warranty: 60 Months

Export Control Classification Number (ECCN): EAR99

Options:

EPL-EMG-24-4L-T8-Mount

Example: EPL-EMG-24-4L-T8-SFC

Mount	
SURFACE	-SFC
PENDANT	-PND

Links (Click on the below items to view):

- [Dimensional Drawing 2D](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [Operations Manual](#)
- [STEP File \(3D CAD Model\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [Video1](#)
- [Video2](#)
- [Video3](#)
- [Video4](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)