Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-24-2L-LED-BMSW-PND

Class 1 Div 2 LED Pendant Mount w/ Punch Out - 2 foot 2 lamp - LED T series Style (fluorescent)

Product ID: 70895

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-24-2L-LED-BMSW-PND Hazardous Area

Dimensions: W-7" L-25 1/2" H-6 1/8"

Weight: 14 Lbs
Total Watts: 30 watts

Voltage: Multi- 120V-60hz 220V-50hz 240V-60hz 277V-60hz

Low Voltage (Optional): 12-24V DC

LED Lamp Life Expectancy: 50,000 Hours

Efficiency: 90 Lumens per Watt
Operating Temp Range: T4A rated -30 C to 85 C

Beam Angle: 150 degrees

Color Temp: 5300K- Color Rendering Index-75

Mounting: Pendant Mount Hubs
Wiring Hub: 1/2" or 3/4" threaded

Minimum Operating Temp: -30 C

Maximum Case Temp: 90 C

U.L. Ratings

NRTL Certified to UL 595 Outdoor Marine Type (Saltwater)

NRTL Certified to UL 1598A Marine Type

California Title 24 Compliant

Class 1 Division 2, Groups A, B, C and D

NRTL Listed for United States & Canada

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics HAL-24-2L-LED-BMSW-PND Hazardous Area LED Light Fixture is NRTL Listed for United States & Canada Class 1 Division 2 Groups A, B, C and D - NRTL Certified to UL 1598A, has a T4A temperature rating and ideal for hazardous

locations where flammable chemical/petrochemical vapors may be occasionally encountered.

The HAL-24-2L-LED-BMSW-PND fixture is a 2 foot long, 2 lamp, Class 1 Division 2 Groups A, B, C and D hazardous area LED light that takes the reliability and efficiency of a fluorescent fixture and adds even longer lamp life and efficiency with high output LEDs. This fixture is T4A temperature rated and comes standard with our high power 15 watt LED lamps. The lamps are protected by a powder coated aluminum frame and shatter and heat resistant clear acrylic lens secured with four zinc coated steel draw latches.

The fixture is constructed of copper free aluminum alloy and powder coated. The lamp reflector is corrosion resistant heavy gauge aluminum and coated with a high gloss reflective finish. This fixture can be configured to run on 120 to 277VAC as well as 12-24VDC and is NRTL Certified to UL 595 and UL 1598A Marine Type approved for use marine environments. The HAL-24-2L-LED-BMSW is weatherproof and provides operators in hazardous locations with a highly efficient, reliable and affordable lighting solution for open areas where flammable chemicals and vapors may occasionally be present.

We have eliminated the ballast normally associated with fluorescent fixtures which reduces overall weight, increases lamp life to an extreme 50,000 hours and helps this LED fixture maintain a T4A temperature rating. The solid state design of the included LED lamps give this fixture superior resistance to damage from vibrations and extremes in temperature as well as a lamp service life over twice that of standard T8 bulbs. The 15 watt LED lamps produce more illumination than standard T8 bulbs, but draw only 3/4 of the current. The current generation of Larson Electronics LED T-series style bulbs produce 15% more light than standard T8 bulbs. This fixture is multi-voltage capable (not multi-tap) and works on the following voltages: 120 Volt 60 HZ, 220 Volt 50 HZ, 240 Volt 60 HZ, 277 Volts 60 HZ. We also make a 12-24V DC version for low voltage applications (-LV suffix). Our HAL-24-2L-LED LED light fixture is NRTL Listed for United States & Canada.

Pendant Mount Hubs: This fixture is equipped with two threaded hubs on the back of the fixture. This allows operators to mount the fixture via ridgid pipe for suspended hanging.

Suggested Applications: Aircraft maintenance, Oil drilling rigs, Refineries, Solvent and cleaning areas, Chemical manufacturing, Waste treatment plants, Gas processing plants.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture, where other models may only offer one or three choices.
3. Fixture constructed streamlined ribbed corrosion-resistant, copper free extruded aluminum body for better hear dissipation and extended ballast life.
4. Aluminum extruded lens frame for greater strength
5. Relamping done via 10 draw latches, which enable the operator to unlatch the lens and access the lamps.
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. 1/2" or 3/4", threaded access hole for wiring conduit.
7. Units can be wired end to end in series.

Superior LED Benefits


1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off – No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)







Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-24-2L-LED-BMSW-PND

Product ID: 70895

Warranty: 60 Months

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

HAL-24-2L-LED-BMSW-PND-Voltage-Color Temp-Hub Config

Example: HAL-24-2L-LED-BMSW-PND-120277-5600K-0.5IN

Voltage	
120V-277V	-120277
12VDC	-12VDC
24VDC	-24VDC

Color Temp	
5600K	-5600K
4100K	-4100K

Hub Config	
1/2IN	-0.5IN
3/4IN	-0.75IN

Links (Click on the below items to view):

- **Operations Manual**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **HigResPic9**
- **HigResPic10**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**