Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

## XCANLED-DC

# 31 Watt Low Voltage LED Fixture for Hazardous Location Lighting - Class 1 Division 2 Approved

**Product ID: 71137**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**XCANLED-DC Hazardous Location LED Light**

**Lamp Type: LED**
**Lamp Dimensions (w/o Bracket):** 6.9" Diam"- 2.9"-Depth
**Lamp Dimensions (w/ Bracket):** 4.63"-H 7.25" W"

**Weight:** 4.5lb | 2.05 k g
**Watts:** 31.6 W @ 12 VDC | 33.6 W @ 24 VDC
**Voltage:** 12-28V DC
**Lumens:**Spot: 2334 - Flood: 1996

**Lamp Life Expectancy:** 100,000 Hours
**CRI:** CW: 75, NW: 75, WW: 80
**Amps:** 2.64 A @12 VDC - 1.4 A @ 24 VDC
**Light Color:** CW: 6500K, NW: 4300K, WW: 3500K
**Beam Type:** 30° Spot or 100° Flood

**Mounting:** 1/4" - 20 Screws /Aluminum 1" Yoke

**Materials:** Machined aluminum housing - acrylic lens
**Housing Finish:** Clear anodized finish
**Temp Range:** -40°C – +85°C
**Typical Case Temperature:** ~20°C above ambient temperature
**Wiring:** 5Ft Lead | White: + Black: -

**ETL Listed**

Class 1 Division 2 Groups A,B,C,D
CSA 22.2 No. 250.0
UL 1598

IP66 Ingress Protection

T3 Temperature Rating
LM-80 > 60,500 hrs (based on Cree long term tests)

**Special Orders - Special Requirements**

Contact us for special requirements
**Toll Free:** 1-800-369-6671
**Intl:** 1-903-270-1187
**E-mail:** sales@larsonelectronics.com

**Buy American Compliant**

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364


**The XCANLED-DC is a low voltage hazardous location lighting solution approved for Class 1 Division 2 environments and UL 1598 compliant for use in wet locations. This powerful LED light produces 2334 lumens, operates from 12 or 24 VDC, and is available in a variety of configurations to allow tailoring to the specific requirements of various applications.**

The XCANLED-DC is designed to provide a high output and ruggedly durable lighting solution for applications where Class 1 Division 2 compliance is required. This low voltage explosion proof light can be operated with either 12 or 24 volt DC current and includes 5 feet of connecting lead with standard two wire configuration. This light is constructed of precision machined aluminum for excellent strength and durability, clear anodized for corrosion resistance, and is IP66 rated for ingress protection against direct exposure to high pressure water spray.

The XCANLED-DC is also available in a 30 degree narrow beam configuration for distance and a 100 degree configuration for wide area illumination. The light output is offered in 6500K cool white, 4300K neutral white, and 3500K warm white color temperatures for maximum illumination. The high output, cool running operation, and good color rendering properties of this light make it an ideal replacement for older, bulkier, and less reliable metal halide and high pressure sodium lamps.



Click Photo to Enlarge




Click Photo to Enlarge




Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge

**Durability:** The XCANLED-DC hazardous location LED light is constructed of machined aluminum for high strength and durability with a clear anodized finish for increased corrosion resistance. The housing is IP66 rated, providing protection against intrusion into the housing from oils and water directly sprayed on the housing at high pressure. This LED light is equipped with an impact resistant acrlyic lens for increased safety compared to glass lenses. This design is weather resistant, suitable for indoor or outdoor applications, and ideal for areas where wet conditions are commonly encountered.

**High Output LEDs:** The LEDs in this unit are Cree X-Lamp XR-E units that have been chosen for their high lumen per watt ratio and extreme long life. These Cree LEDs provide over 90 lumens per watt output and have a 70% lumen retention at 100,000 hours, giving them better efficiency and operational life than comparable LEDs. These lights are available in a 30 degree spotlight configuration for long beam length or 100 degree flood configuration for wide area coverage. The HAL-31L-LV has multiple color temperature options and is offered in 6500K cool white with a color rendering of 75, 4300K neutral white with a color rendering of 75, and 3500K warm white with a color rendering of 80.

**Mounting:** Mounting for this unit is provided by an included aluminum yoke that

allows vertical adjustment of the light once installed. The mounting yoke is 1 inch wide and predrilled with two ¼ inch holes spaced 2 inches apart for easy and secure mounting to flat surfaces. The entire assembly weighs 4.5 lbs and measures only 6.9 inches in diameter and 3 inches deep, making it ideal for mounting in areas where space is limited and a heavy fixture cannot be installed due to lack of support.

**Wiring/Power:** These hazardous location LED lights are equipped with 5 feet of cord containing a standard two wire (White+ Black-) connecting configuration. These lights operate from 12 to 24 volt DC current and draw 31 watts 2.64 amps on 12 VDC and 33 Watts 1.4 amps on 24 VDC.

**Versatility:** The XCANLED-DC is ETL listed for Class 1 Division 2 groups A,B,C and D locations, certified to CSA 22.2 No. 250.0, and conforms to UL 1598. This unit carries an IP66 waterproof rating ensuring protection against ingress from oils and water sprayed at high pressure directly on the fixture. This light is ideal for indoor or outdoor applications, food processing, and industrial operations with hazardous location classification where wet conditions are commonly encountered.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

# Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

**XCANLED-DC**

**Product ID: 71137**

**Harmonized System (HS) Code:** 9405.41.84.10

**Export Control Classification Number (ECCN):** EAR99

**Options:**

**XCANLED-DC-Color Temp-Beam Angle-Housing Color**

**Example: XCANLED-DC-CW-W-ALU**

| Color Temp | |
|---|---|
| CW 6500K | -CW |
| NW 4300K | -NW |
| WW 3500K | -WW |

| Beam Angle | |
|---|---|
| WIDE | -W |
| NARROW | -N |

| Housing Color | |
|---|---|
| ALUMINUM | -ALU |
| CUSTOM | -CUS |

Links (Click on the below items to view):

- **Operations Manual**
- **Wiring Diagram**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**