

GSLEDIP36-GEN-WHT

25 Watt LED Cabinet Light Fixture - 36" Light Bar - White Housing - Low Voltage Strip Light

Product ID: 71661

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

GSLEDIP36-GEN-WHT LED Bar

Lamp Type: LED

Dimensions: Lamp 35.88"-L 2.68" -W 1.69"- D

Weight: 2.1lb | 0.9 k g

Watts: 25.2 W

Voltage: 12-24 VDC

Lumens: 1812

Lamp Life Expectancy: 100,000 Hours

CRI: CW: 75, NW: 75, WW: 80

Amps: 1.3 A @12 VDC | 0.66 A @ 24 VDC

Light Color: CW: 6500K, NW: 4300K, WW: 3500K

Beam Type: 100° Flood or 30° Spot

Lens: Clear or Frosted

Mounting: Standard Triangle End Brackets

Temp Range: -40°C – +85°C

Wiring: 5Ft Lead | White: + Black: -

GSLEDIP36-GEN-WHT Ratings

IP54 Ingress Protection

T3 Temperature Rating

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Buy American Compliant

The Larson Electronics GSLEDIP36-GEN-WHT is a low voltage lighting solution approved for use in wet locations. This powerful 36" long LED strip light produces 1812 lumens, operates from 12 or 24 VDC, and is suitable for a variety of applications.

The GSLEDIP36-GEN-WHT is designed to provide a high output and ruggedly

durable lighting solution. This low voltage light can be operated with either 12 or 24 volt DC current and includes 5 feet of connecting lead with standard two wire configuration. This light is constructed of powder coated extruded aluminum for excellent strength and durability and is rated IP54 for protection against exposure to splashing water and limited dust ingress. These units are configured in a 36" long strip or "bar" profile for installation in locations where wide dispersal and a low profile is preferred. The high output, cool running operation, and good color rendering properties of this light make it an ideal replacement for older, bulkier, and less reliable HID and halogen light fixtures.

Durability/Mounting: The GSLEDIP36-GEN-WHT LED light is constructed of extruded aluminum with a tough powder coat finish for high strength and durability. The housing is IP54 rated, providing limited ingress protection against dusts, and basic protection against splashing water such as rain. This design is weather resistant, suitable for indoor or outdoor applications, and ideal for areas where wetness or dusty conditions are commonly encountered.

The LEDs in this unit are Cree X-Lamp XR-E units that have been chosen for their high lumen per watt ratio and extreme long life. These Cree LEDs provide over 90 lumens per watt output and have a 70% lumen retention at 50,000 hours, giving them better efficiency and operational life than comparable LEDs.

Mounting for this unit is provided by two standard adjustable end brackets that allow operators to mount the light to flat surfaces and then adjust the light 170° vertically for the best placement. The entire assembly weighs 2.1 lbs and measures 35.88 inches in length and 2.68 inches wide and 1.69" deep, making it ideal for mounting in areas where space is limited and a low profile fixture is more readily installed.

Wiring/Power: These LED lights are equipped with 5 feet of cord containing a standard two wire (White+ Black-) connecting configuration. These lights operate from 12 or 24 volt DC current at 25.2 watts 1.3 amps on 12 VDC and .66 amps on 24 VDC.

Versatility: This unit carries an IP54 water resistant rating ensuring protection against limited ingress from dusts, dirt, and basic protection against light water spray landing directly on the fixture. This light is ideal for indoor or outdoor applications and industrial operations with hazardous location classification where dusty or wet conditions are commonly encountered.

Frequently Asked Questions (FAQ)









GSLEDIP36-GEN-WHT

Product ID: 71661

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

GSLEDIP36-GEN-WHT-Kelvin & Beam-Housing Color-Voltage

Example: GSLEDIP36-GEN-WHT-CW-N-BLK-12VDC

Kelvin & Beam	
COOL W-SPOT	-CW-N
COOL W-FLOOD	-CW-W
COOL W-SPOT FROST	-CW-NF
COOL W-FLOOD FROST	-CW-WF
NEUTRAL W-SPOT	-NW-N
NEUTRAL W-FLOOD	-NW-W
NEUTRAL W-SPOT FROST	-NW-NF
NEUTRAL W-FLOOD FROST	-NW-WF
WARM W-SPOT	-WW-N
WARM W-FLOOD	-WW-W
WARM W-SPOT FROST	-WW-NF
WARM W-FLOOD FROST	-WW-WF
CUSTOM-SPOT	-CUS-N
CUSTOM-FLOOD	-CUS-W
CUSTOM-SPOT FROST	-CUS-NF
CUSTOM-FLOOD FROST	-CUS-WF

Housing Color	
BLACK	-BLK
WHITE	-WHT
ALUMINUM	-ALU
CUSTOM	-CUS

Voltage	
12 VOLTS DC	-12VDC
24 VOLTS DC	-24VDC

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)