
Explosion Proof Ultraviolet LED Light - Base Stand Mount - 100 Watt LED - Class I Div 1 C&D
EPL-16BS-1X150LED-UV365-100



EPL-16BS-1X150LED-UV365-100 Explosion Proof LED Light

Listing: United States & Canada

Lamp Type: LED

Dimensions: 14" x 22" Light head

Weight: 30 Lbs.

Voltage: Universal Voltage 120-277V AC 50/60Hz

Total Watts: 100 watts

LED Lamp Intensity: 38,400 mW

Wavelength: 365NM

LED Lamp Life Expectancy: 60,000 Hours

Beam Lux: 8500@ 1 Meter 1250@ 3 Meters

Lighting Configuration: Flood Pattern

Ambient Operating Temp Range: -40°C to 65°C

Operating Temp Range: T5 Rated

Mounting: Aluminum Base Stand

Wiring: 100' SOOW Cord Explosion Proof Straight Blade Plug

Cord Cap: 5-15 Straight Blade Plug, 5-20 Straight Blade Plug,
6-20 Straight Blade Plug

Quick Summary

Class I Division 1, Groups C and D

Class I Division 2, Group A,B,C,D

Class II, Divisions 1 & 2, Groups E,F,G

Class III, Divisions 1 & 2

T5 Temperature Rating

Certified to UL844 and C22.2 Standards

IP67 Rated Waterproof

Paint Spray Booth Approved

LEL Approved

Multiple Driver Banks

80% Lumen Retention after 60,000 Hours

Made in the USA

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com



Warranty: 60 Months

Options:

EPL-16BS-1X150LED-UV365-100-Voltage-Cord Cap

Example: EPL-16BS-1X150LED-UV365-100-1227-1227

Voltage	
120-277V AC	-1227
11-25V AC/DC	-1224

Cord Cap	
5-15	-1227
5-20	-1224

Links (Click on the below items to view):

- [Addpic1large](#)
- [Addpic2large](#)
- [Addpic3large](#)
- [Addpic4large](#)
- [DimensionalDrawing](#)
- [large](#)
- [medium](#)
- [SpecSheet](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)