Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

PML-70

Permanent Mount 70 Watt HID Spotlight w/ Adjustable Handle - Pivots and Rotates - 12-24VDC

Product ID: 73056

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

PML-70 HID Spotlight
Lamp Type: Xenon D2 lamp
Watts: 70
Voltage: 12V DC or 24V DC
Lighting Configuration: Spot or Flood
Mounting: Flat Surface - Adjustable Tensioners
Wiring: Deutsch Connector on Light, 20` SOOW cable
Amps: 5.9 (on 12 volts) Lamp Only
Light Color: 6500K
Lumens: 6300 +/- 400 lumens
Ballast : 70 Watt, Instant on, 3 Seconds to Full Power
Vibration tolerance: 12G RMS
HID Lamp Life Expectancy: 3,500 hours
Materials: High Impact Nylon, Steel, Polycarbonate, Borosilicate lens

Ratings/Features
IP67 Waterproof
12G RMS Vibration Tolerance
4800` - 6500K Light Beam
AC or DC Power Options

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Buy American Compliant


The Larson Electronics PML-70 70 Watt HID Spotlight produces 6,300 lumens of intense bright light and offers the versatility of both 12V and 24V DC operation from a compact spotlight profile. This permanent mount HID spotlight is equipped with a rugged polycarbonate control handle and tension hinges that allow the unit to be easily adjusted and set into position and produces a powerful light beam reaching over 4800 feet in length.

This 70 watt HID spotlight contains a single Xenon D2 lamp powered by an internally contained 70 watt HID ballast with instant on capability and reaches full power light output within 3 seconds. Producing 6,300 lumens of bright white light while drawing only 5.9 amps, the light beam from this unit in spot configuration exceeds 4,800 feet in length while an optional flood configuration covers an area approximately 400 feet wide by 350 feet long. The housing on this spotlight is constructed of high impact nylon for light weight and durability while the handle assembly is constructed of powder coated steel and solid polycarbonate.
The 4 inch square mounting base has 4 corner bolt holes to keep the spotlight secured to the mounting surface under extreme vibration and off-road conditions. Tension hinges incorporated into the mounting assembly allow the light to hold its position once adjusted without the need to set or lock any hardware before releasing the adjusting handle. The operator simply adjusts the unit to the desired position and releases it to set the unit into position.



This image shows a dark street with no illumination but the distant street lights

Click Photo to Enlarge



PML-70 being used to fill the entire street in length and width. Street terminates at 4200` however, the HID reaches that distance easily.

Click Photo to Enlarge

Durability: The housing on the PML-70 is constructed of high impact nylon to provide resistance to impacts, shocks and vibration. Rubber isolators connect the housing to the adjustable steel tensioner hinges to further provide protection from vibration and give this unit a 12G RMS vibration resistance rating. The mounting assembly is constructed of steel and the adjusting handle is constructed of powder coated steel with a solid polycarbonate handle. The High Intensity Discharge Lamp has no filament and is highly resistant to damage from vibrations and shocks. The lamp is protected by a Borosilicate hardened glass lens. This spotlight is gasketed and sealed and IP67 rated, making it weatherproof and waterproof and resistant to the ingress of water, dust and other contaminants.
Mounting: This light has a 4 inch square steel mounting plate that is secured to the mounting surface via 4 screws. The mounting assembly on this unit allows the unit to be rotated and adjusted vertically. The adjusting hinges on this light are tensioned, allowing the user to simply position the light as desired without any need for locking the unit into place. Once positioned, the light will hold its position until the user again repositions it.
Power: This light can be operated on either 12 volt or 24 volt DC current and includes a 20` SOOW Cord to allow the operator to mount the light itself at a different location than the power source.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

PML-70

Product ID: 73056

Harmonized System (HS) Code: 8512.20.2080
Export Control Classification Number (ECCN): EAR99

Options:

PML-70-Beam Config-Voltage

Example: PML-70-S-12V

Beam Config	
SPOT	-S
FLOOD	-F

Voltage	
12V DC	-12V
24V DC	-24V

Links (Click on the below items to view):

- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**