

EPP-30A-30FT-BCE

Explosion Proof Plug - Class I, Div. 1 & 2 - Class II, Div. 1 & 2 - 30 Amp Rated - 30FT - Blunt Cut
Product ID: 104900



Image: EPP-30A-30FT-BCE

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPP-30A-30FT-BCE Explosion Proof PLug

Amp Rating: 30

Dimensions: 8.44"-L 3.06"-W

Configuration: 4 Pole 3 Wire

Suitable Cable Diameter: .390" to 1.375"

Compatibility: [EPO-30A](#), Appleton Powertite®, Crouse Hind™-CES2214, Hubbell-Killark-KR Series 30 amp

Cable Locking: Mechanical Cable Clamps

Plug Type: Pin and Sleeve

Voltage: 125-240VAC / 480 VAC

Cable: 30 feet 10/4 SOOW w/ blunt cut end

Certifications - Compliance

Class 1 Division 1 & 2 Groups C & D

Class 2, Div. 1 & 2

NRTL Certified to UL Standard: UL 1010 (UL 1203), UL 894, UL 1682, UL 1686

NRTL Certified to CSA Standard: C22. No 30, C22.2 No. 159, C22.2 No 182.1

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

Larson Electronics EPP-30A-30FT-BCE Explosion Proof Plug

This explosion proof pin and sleeve plug is compatible with our [EPO-30A](#) power receptacles. This plug is rated for 30 amps and is approved Class I, Division 1 and 2, Groups C, D. This explosion proof plug features non sparking aluminum construction, recessed brass contacts to prevent accidental contact, and a 120-240 VAC/ 480 VAC @30 amps current rating. This plug is designed to lock into our EPO-30A receptacles by pushing the plug into the receptacle, moving the sliding lock to the side, then pushing the plug in the rest of the way to fully seat and

lock it into place. This C1D1 plug comes factory installed with 30` of 10/4 SOOW cable and a blunt cut end.

[Click Photo to Enlarge](#)

Inter-Compatibility: These plugs are cross-interchangeable with Appleton CPH plugs and will work with Powertite® Series receptacles, Crouse Hind™ receptacles under catalogue number "CES2214", and receptacles. Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Motor-Generator Sets, Compressors, Wet areas or Locations Where Combustible Dust is Present.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Frequently Asked Questions (FAQ)

There are no Faqs