

EPL-EMG-RBALL-C1D1

Explosion Proof Remote Emergency Ballast for EPL-48-2L-LED Explosion Proof Fixtures - C1D1

Product ID: 104912



Image: EPL-EMG-RBALL-C1D1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-EMG-RBALL-C1D1 Explosion Proof Emergency Backup Ballast

UL Listing: United States - Canada

Dimensions: 17.75" L x 6" W x 5" H

Weight: 30 Lbs

Total Watts: N/A

AC Input Voltage: 120/277 VAC (Auto Select), 60hz

AC Input Current: 90 mA

AC Input Power Rating: 9.5 W

Maximum Load Power: 20 W (Including AC Ballast/Driver)

Output Current: 120 V, 165 mA - 277 V, 72 mA

Illumination Time: 90 Minutes

Test Switch: Single Pole (Momentary)

Battery: High-Temperature, Maintenance Free Nickel-Cadmium

Battery Life: 7 to 10 Year Life Expectancy

Battery Charging Current: 250 mA

Recharge Time: 24 Hours

Charging Indicator Light: LED

Wiring Hubs: (2) 3/4" EYS w/ Cord Grips

Wiring: Customer Provided

U.L. Ratings

Class 1 Division 1 Explosion Proof

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com


The Larson Electronics EPL-EMG-RBALL-C1D1 Explosion Proof Emergency Backup Ballast works in conjunction with a LED fixture to create an emergency lighting system. This explosion proof Ballast operates a maximum load of 20 W at unity power factor. It allows the connected fixture(s) to be on, off, switched or dimmed without

affecting emergency operation. Each unit consists of a high-temperature nickel-cadmium battery, charger and electronic circuitry in one steel case. The EPL-EMG-RBALL-C1D1 provides power to the input side of the fixture, including the ballast, can be used with indoor or outdoor emergency fixture applications and offers remote mounting.

The EPL-EMG-RBALL-C1D1 supports emergency illumination for a minimum of 90 minutes. At a maximum of 20 W at unity power factor, the EPL-EMG-RBALL-C1D1 will provide input power to ballasted lamp supporting it at 100% of the AC rated output throughout the 90-minute emergency illumination period. Upon failure of normal power, the ballast instantly begins providing emergency power to the connected lighting load for a minimum of 90 minutes. A solid-state low voltage disconnect circuit protects the inverter battery from severe damage by deep discharge during prolonged power failures. When normal power is restored, the EPL-EMG-RBALL-C1D1 automatically returns to charge mode. The battery capacity is fully restored in 24 hours. The explosion proof ballast does not affect normal fixture operation and may be used with a switched or unswitched fixture. It can be installed in close proximity to the fixture or remotely, away from the fixture (up to 250 feet).

Emergency lighting shall be provided by using a standard fixture equipped with the Larson Electronics EPL-EMG-RBALL-C1D1. Each unit consists of a high-temperature, maintenance free nickel-cadmium battery, charger and electronic circuitry contained in one 16.6" x 2.8" x 2.85" metal case. Solid-state indicator lights signal operational status. The EPL-EMG-RBALL-C1D1 unit shall be capable of powering any fluorescent or LED lighting fixture rated at a maximum of 20 W (at unity power factor) for a minimum 90 minutes regardless of local switch position. The EPL-EMG-RBALL-C1D1 shall allow the connected fixture(s) to be on, off, switched or dimmed without affecting emergency operation. The EPL-EMG-RBALL-C1D1 unit shall exceed emergency standards set forth by the current NEC. It shall be UL Listed, suitable for damp location.

EPL-EMG-RBALL-C1D1 Wiring Diagram



SAFETY DATA SHEET

HCS-2012 APPENDIX D TO §1910.1200

Version 1

Product Name Nickel Cadmium Battery

Issue Date 21-Jan-2015

Revision date 21-Jan-2015

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Nickel Cadmium Battery
Chemical Name Nickel Cadmium Battery

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended Use Used in electric tools
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Jiangsu Highstar Battery Manufacturing Co.,Ltd.
Address No.306 Heping Road(s), Qidong City, Jiangsu, China
Postal Code 226200
Phone 0086-513-80795666
FAX 0086-513-83312306
E-mail chenj@highstar.net.cn

Emergency telephone number

0086-513-80795666

2. HAZARDS IDENTIFICATION

GHS Classification

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Label elements

Symbols/Pictograms None
Signal word None
Hazard Statements None
Precautionary Statements
Prevention None
Response None
Storage None
Disposal None

Hazards not otherwise classified (HNOC)

No information available

Unknown acute toxicity

.?% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Mixture

Chemical Name	CAS No	Weight-%
Nickel	7440-02-0	10 - 25
Cadmium and compounds (as Cd)	7440-43-9	10 - 25
Cadmium hydroxide (Cd(OH) ₂)	21041-95-2	12 - 23
Nickel hydroxide	12054-48-7	6 - 14

Iron	7439-89-6	10 - 13
------	-----------	---------

4. FIRST AID MEASURES

Description of first aid measures

General advice	Remove contaminated clothing and shoes. If symptoms persist, call a physician.
Inhalation	Not an expected route of exposure. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin Contact	Wash hands thoroughly after handling. .
Eye contact	Not an expected route of exposure. .
Ingestion	Rinse mouth Get medical attention Never give anything by mouth to an unconscious person

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	No information available.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas
Ensure adequate ventilation, especially in confined areas
Remove all sources of ignition
Use personal protection recommended in Section 8

Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so
Pick up and transfer to properly labeled containers

Avoid release to the environment

7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice
Ensure adequate ventilation, especially in confined areas
Avoid creating dust
Avoid contact with eyes
Wash thoroughly after handling
Use personal protection recommended in Section 8



Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place

Keep away from heat

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	Denmark	European Union
Nickel (CAS #: 7440-02-0)	TWA: 1.5 mg/m ³ inhalable fraction	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 10 mg/m ³ IDLH: 10 mg/m ³ Ni TWA: 0.015 mg/m ³ TWA: 0.015 mg/m ³ except Nickel carbonyl Ni	TWA: 0.05 mg/m ³	-
Cadmium and compounds (as Cd) (CAS #: 7440-43-9)	TWA: 0.01 mg/m ³ TWA: 0.002 mg/m ³ respirable fraction TWA: 0.01 mg/m ³ Cd TWA: 0.002 mg/m ³ Cd respirable fraction	TWA: 0.1 mg/m ³ fume applies to any operations or sectors for which the Cadmium standard is stayed or otherwise not in effect TWA: 0.2 mg/m ³ dust applies to any operations or sectors for which the Cadmium standard is stayed or otherwise not in effect TWA: 5 µg/m ³ (vacated) STEL: 0.3 ppm fume Ceiling: 0.3 mg/m ³ fume applies to any operations or sectors for which the Cadmium standard is stayed or otherwise not in effect Ceiling: 0.6 mg/m ³ dust applies to any operations or sectors for which the Cadmium standard is stayed or otherwise not in effect	IDLH: 9 mg/m ³ dust IDLH: 9 mg/m ³ Cd dust and fume	TWA: 0.005 mg/m ³	-
Cadmium hydroxide (Cd(OH) ₂) (CAS #: 21041-95-2)	TWA: 0.01 mg/m ³ Cd TWA: 0.002 mg/m ³ Cd respirable fraction	-	-	TWA: 0.005 mg/m ³	-
Nickel hydroxide (CAS #: 12054-48-7)	TWA: 0.2 mg/m ³ Ni inhalable fraction	TWA: 1 mg/m ³ Ni (vacated) TWA: 1 mg/m ³ Ni	IDLH: 10 mg/m ³ Ni TWA: 0.015 mg/m ³ except Nickel carbonyl Ni	TWA: 0.05 mg/m ³	-

Chemical Name	Latvia	France	Finland	Germany	Italy
Nickel (CAS #: 7440-02-0)	TWA: 0.05 mg/m ³	TWA: 1 mg/m ³	TWA: 1 mg/m ³ TWA: 0.1 mg/m ³	Skin	-
Cadmium and compounds (as Cd) (CAS #: 7440-43-9)	TWA: 0.01 mg/m ³ STEL: 0.05 mg/m ³	TWA: 0.05 mg/m ³	TWA: 0.02 mg/m ³ Skin	Skin	-
Nickel hydroxide (CAS #: 12054-48-7)	TWA: 0.05 mg/m ³	TWA: 1 mg/m ³	TWA: 0.1 mg/m ³	Skin	-

Chemical Name	Poland	Portugal	Spain	Switzerland	Netherlands
Nickel (CAS #: 7440-02-0)	TWA: 0.25 mg/m ³	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³	TWA: 0.5 mg/m ³	-
Cadmium and compounds (as Cd) (CAS #: 7440-43-9)	TWA: 0.01 mg/m ³ TWA: 0.002 mg/m ³	TWA: 0.01 mg/m ³ TWA: 0.002 mg/m ³	TWA: 0.01 mg/m ³ TWA: 0.002 mg/m ³	Skin TWA: 0.015 mg/m ³	-
Nickel hydroxide (CAS #: 12054-48-7)	TWA: 0.25 mg/m ³	TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³	TWA: 0.05 mg/m ³	-

Chemical Name	Norway	United Kingdom	Australia	Austria	Belgium
Nickel (CAS #: 7440-02-0)	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³	STEL: 1.5 mg/m ³ TWA: 0.5 mg/m ³	1 mg/m ³	-	-

Cadmium and compounds (as Cd) (CAS #: 7440-43-9)	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³	STEL: 0.075 mg/m ³ TWA: 0.025 mg/m ³	0.01 mg/m ³	-	-
Cadmium hydroxide (Cd(OH) ₂) (CAS #: 21041-95-2)	-	-	0.01 mg/m ³	-	-
Nickel hydroxide (CAS #: 12054-48-7)	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³	TWA: 0.5 mg/m ³	-	-	-

Appropriate engineering controls

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hand Protection Wear protective gloves.

Eye/face protection No special technical protective measures are necessary.

Skin and body protection Wear suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Appearance	Solid
Color	No information available
Odor	Odorless
Odor Threshold	Not determined
pH	Not determined
Melting point/freezing point	Not determined
Boiling point / boiling range	Not determined
Flash point	Not applicable
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Flammability Limit in Air	Not determined
Vapor Pressure	Not applicable
Vapor density	Not determined
Density	Not determined
Relative density	Not determined
Bulk density	Not determined
Specific gravity	Not determined
Water solubility	Not determined
Partition coefficient (LogPow)	Not determined
Autoignition temperature	Not determined
Decomposition temperature	Not determined
Kinematic viscosity	Not determined
Dynamic viscosity	Not determined
Explosive properties	Not an explosive
Oxidizing properties	Not determined

Other information

No information available

10. STABILITY AND REACTIVITY**Reactivity**

Stable under recommended storage and handling conditions (see SECTION 7, handling and storage).

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing

Conditions to avoid

Strong heating. Incompatible materials

Incompatible materials

Strong acids Strong bases Strong oxidizing agents

Hazardous Decomposition Products

None known based on information supplied

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system
 Eye contact Contact with eyes may cause irritation
 Skin Contact Substance may cause slight skin irritation
 Ingestion may cause irritation to mucous membranes

Information on toxicological effects**Acute toxicity**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel (CAS #: 7440-02-0)	> 9000 mg/kg (Rat)	-	-
Cadmium and compounds (as Cd) (CAS #: 7440-43-9)	= 2330 mg/kg (Rat)	-	= 25 mg/m ³ (Rat) 30 min
Nickel hydroxide (CAS #: 12054-48-7)	-	-	= 1200 mg/m ³ (Rat) 4 h
Iron (CAS #: 7439-89-6)	98.6 g/kg bw (rat)	-	-

Skin corrosion/irritation

Non-irritating to the skin

Serious eye damage/eye irritation

No eye irritation

Sensitization

No information available

Germ cell mutagenicity

No information available

Carcinogenicity

This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP

Chemical Name	ACGIH	IARC	NTP	OSHA
Nickel (CAS #: 7440-02-0)	-	Group 2B	Known Reasonably Anticipated	X
Cadmium and compounds (as Cd) (CAS #: 7440-43-9)	A2	Group 1	Known	X
Cadmium hydroxide (Cd(OH) ₂) (CAS #: 21041-95-2)	A2	-	-	-
Nickel hydroxide (CAS #: 12054-48-7)	A1	Group 1	Known	X

Reproductive toxicity

No information available

STOT - single exposure

No information available

STOT - repeated exposure

No information available

Aspiration hazard

No information available

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Algae/aquatic plants EC50	Fish LC50	Crustacea EC50
Nickel (CAS #: 7440-02-0)	0.18 mg/L/72h Pseudokirchneriella subcapitata 0.174 - 0.311 mg/L/96h Pseudokirchneriella subcapitata static	100 mg/L/96h Brachydanio rerio 1.3 mg/L/96h Cyprinus carpio semi-static 10.4 mg/L/96h Cyprinus carpio static	100 mg/L/48h Daphnia magna 1 mg/L/48h Daphnia magna Static
Cadmium and compounds (as Cd) (CAS #: 7440-43-9)	-	0.003: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.006: 96 h Oncorhynchus mykiss mg/L LC50 static 0.002: 96 h Cyprinus carpio mg/L LC50 4.26: 96 h Cyprinus carpio mg/L LC50 semi-static 0.24: 96 h Cyprinus carpio mg/L LC50 static 21.1: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.016: 96 h Oryzias latipes mg/L LC50 0.0004 - 0.003: 96 h Pimephales promelas mg/L LC50	0.0244: 48 h Daphnia magna mg/L EC50 Static
Iron (CAS #: 7439-89-6)	-	-	> 100 mg/L/48h (Daphnia magna)

Persistence and degradability

No information available

Bioaccumulative potential

No information available

Mobility in soil

No information available

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods**

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations

Contaminated packaging

Dispose of in accordance with federal, state and local regulations

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
---------------	------	--------------------------	------------------------	------------------------

Nickel 7440-02-0	-	Included in waste streams: F006, F039	-	-
Cadmium and compounds (as Cd) 7440-43-9	-	Included in waste streams: F006, F039, K061, K069, K100	1.0 mg/L regulatory level	-
Chemical Name		California Hazardous Waste Status		
Nickel 7440-02-0		Toxic powder Ignitable powder		

14. TRANSPORT INFORMATION

It is considered as non-dangerous good by the ICAO, IATA, IMDG and TDG.

According to IATA DGR 56th Edition for transportation and International Maritime Dangerous Goods (IMDG Code 36th) and the Recommendation on the Transportation of Dangerous Goods-Model Regulation (18th)

The products are not subjects/subject to dangerous.

DOT / IMDG / IATA

UN/ID No.	Not regulated
Proper shipping name	Not regulated
Hazard Class	Not regulated
Packing Group	Not regulated
Special precautions	No information available
Marine pollutant	Not applicable

15. REGULATORY INFORMATION

International Inventories

Component	AICS	DSL/NDL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	TSCA
Nickel 7440-02-0 (10 - 30)	X	X	X	-	X	X	X	X
Cadmium and compounds (as Cd) 7440-43-9 (10 - 30)	X	X	X	-	X	X	X	X
Cadmium hydroxide (Cd(OH) ₂) 21041-95-2 (10 - 30)	X	X	-	-	X	-	-	-
Nickel hydroxide 12054-48-7 (10 - 30)	X	X	X	X	X	X	X	X
Iron 7439-89-6 (10 - 30)	X	X	X	-	X	X	X	X

"-" Not Listed

"X" Listed

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Nickel - 7440-02-0	0.1
Cadmium and compounds (as Cd) - 7440-43-9	0.1
Nickel hydroxide - 12054-48-7	0.1

SARA 311/312 Hazard Categories

Does not apply

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Nickel 7440-02-0	-	X	X	-
Cadmium and compounds (as Cd) 7440-43-9	-	X	X	-
Cadmium hydroxide (Cd(OH) ₂) 21041-95-2	-	X	-	-
Nickel hydroxide 12054-48-7	-	X	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Nickel 7440-02-0	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Cadmium and compounds (as Cd) 7440-43-9	10 lb	-	RQ 10 lb final RQ RQ 4.54 kg final RQ
Nickel hydroxide 12054-48-7	10 lb	-	RQ 10 lb final RQ RQ 4.54 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Nickel - 7440-02-0	Carcinogen
Cadmium and compounds (as Cd) - 7440-43-9	Carcinogen Developmental Male Reproductive
Cadmium hydroxide (Cd(OH) ₂) - 21041-95-2	Carcinogen
Nickel hydroxide - 12054-48-7	Carcinogen

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Nickel 7440-02-0	X	X	X
Cadmium and compounds (as Cd) 7440-43-9	X	X	X
Nickel hydroxide 12054-48-7	X	X	X

16. OTHER INFORMATION**Revision Note**

Issue Date 21-Jan-2015
Revision date 21-Jan-2015
Revision Note Not applicable

Key or legend to abbreviations and acronyms used in the safety data sheet

TWA - TWA (time-weighted average)
STEL - STEL (Short Term Exposure Limit)
Ceiling - Maximum limit value
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

----- End of Safety Data Sheet -----



Frequently Asked Questions (FAQ)

There are no Faqs