Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

RL-85-LED-CPR

6 Million Candlepower Rechargable LED Light Hunting Spotlight- 25 Watts - Pistol Style - Li-Ion

Product ID: 106171



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

RL-85-LED-CPR Handheld Spotlight

Lamp Type: Cree LED
Dimensions: 7.95"L x 8.37"H x 2.75"D
Weight: 3 lbs.
Voltage: 120-240V AC or 12-24V DC
Total Watts: 25W
Total Lumens: 2,000
Candlepower: 6 Million CP
Battery: (2) 3.7V 2600maH lithium ion batteries
Luminous Efficacy: 80 Lm/W
LED Lamp Life Expectancy: 50,000+
Beam Type: 30° Spot
Housing Material: Aluminum Alloy & Nylon
Housing Color: Black
Lens Material: Polycarbonate
Mounting: Handheld
Cord Cap: 5-15P or Schuko, Cigarette Plug

Quick Summary

IP65 Waterproof
Dustproof
Shockproof
Impact/Vibration Resistant Construction
Lightweight
Portable
Red and Green Lenses Available

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The RL-85-LED-CPR 6 Million candlepower handheld spotlight from Larson Electronics is lightweight, ruggedly built, and features a rechargeable lithium ion battery and AC/DC charging adaptor for convenient recharging at home, on the worksite, or on the go. Designed for both functionality and convenience, the RL-85-LED-CPR allows operators to roam freely without the hassle of being plugged into a power source. This unit uses a premium Cree LED and a parabolic reflector to generate an impressive

2,000 lumens while drawing a modest 25 watts of power. This powerful IP65 rated spotlight is ideal for hunting, camping, marine and boating use as well as for first responders and emergency services.

Light Features: The RL-85-LED-CPR 6 million candlepower handheld spotlight delivers an impressive 2,000 lumens while drawing only 25 watts of energy. In combination with a single high output Cree LED and a parabolic reflector, this light cuts through the darkness with an ultra-focused 30° spot beam that clearly and sharply illuminates objects all the way to the end of the beam reach. The Cree LED units in this light have been chosen for their high lumen per watt ratio and extreme longevity. These Cree LEDs generate 80 lumens per watt and have a 70% lumen retention at 50,000 hours, giving them better efficiency and operational life than traditional light sources.

This IP65 rated spotlight features an ultra-durable ABS shockproof polymer body, an aluminum alloy light head housing, and an impact resistant polycarbonate lens. While the RL-85-LED-CPR is built to withstand rugged use and harsh outdoor conditions, comfort and ease of operation haven`t been sacrificed. This unit is ergonomically designed for balanced and comfortable handling. The nylon handle has a no-slip textured surface that ensures a firm grip even in wet conditions. The booted push button is conveniently placed to allow operators easy forefinger access to the switch for quick on/off action.

Larson Electronics offers additional options for the RL-85-LED-CPR spotlight, including red and green lenses. For more information, contact sales@larsonelectronics.com.



Click Photo to Enlarge

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Cree Specific: This lamp uses Cree LED units that have been chosen for their high lumen per watt ratio and extreme longevity. These Cree LEDs generate a robust 80 lumens per watt effective lumen output and have a 70% lumen retention at 50,000 hours, giving them better efficiency and operational life than traditional light sources.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Click Photo to Enlarge



Click Photo to Enlarge

Power: The rechargeable RL-85-LED-CPR spotlight comes equipped with two 3.7V 2600MA lithium batteries and is recharged using an included AC and DC charger. A 120V or 240V wall charger comes standard, as well as a vehicle charger that operates on 12-24V DC. This light has a work time of 2.5-3 hours on a single charge. Recharging from a fully discharged state takes 3 hours.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

High Quality Features

1. Low power consumption.
2. Instant on/off operation.
3. Nylon and aluminum alloy body.
4. Durable polycarbonate lens.
5. Retains 70% lumen output after 50,000 operating hours.
6. Ergonomic nylon handle.
7. Built for Toughness and Durability
8. Low profile - Lightweight
9. 2,000 Lumen output from only 25 watts.

Superior LED Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off - No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.









MATERIAL SAFETY DATA SHEET

Model ICR18650S3 Lithium Ion Rechargeable Battery

LG CHEMICAL LTD

1. Chemical Product and Company Identification

Product Identification

LG CHEM ICR18650S3 Lithium-Ion Battery

Manufacturer

LG Chemical Ltd.
Twin Tower
Youido-Dong 120, Youngdeungpo-Ku
Seoul, Korea

Emergency Telephone Number

82-2-3773-7256

2. Composition Information

Hazardous Ingredients	%	CAS Number
Aluminum Foil	2-10	7429-90-5
Metal Oxide (proprietary)	20-50	
Polyvinylidene Fluoride (PVDF)	<5	24937-79-9
Copper Foil	2-10	7440-50-8
Carbon (proprietary)	10-30	7440-44-0
Electrolyte (proprietary)	10-20	
Stainless steel, Nickel and inert materials	Remainder	N/A

* Equivalent Lithium Content: 0.66g, Electric Power Capacity: 7.92Wh

3. Hazards Identification

Emergency Overview

May explode in a fire, which could release hydrogen fluoride gas.
Use extinguishing media suitable for materials burning in fire.

Primary routes of entry

Skin contact	:	NO
Skin absorption	:	NO
Eye contact	:	NO
Inhalation	:	NO
Ingestion	:	NO

Symptoms of exposure

Skin contact
No effect under routine handling and use.

Skin absorption
No effect under routine handling and use.

Eye contact
No effect under routine handling and use.

Inhalation
No effect under routine handling and use.

Reported as carcinogen
Not applicable

4. First Aid Measures

Inhalation
Not a health hazard.

Eye contact
Not a health hazard.

Skin contact
Not a health hazard.

Ingestion
If swallowed, obtain medical attention immediately.

IF EXPOSURE TO INTERNAL MATERIALS WITHIN CELL DUE TO DAMAGED OUTER CASING, THE FOLLOWING ACTIONS ARE RECOMMENDED ;

Inhalation
Leave area immediately and seek medical attention.

Eye contact
Rinse eyes with water for 15 minutes and seek medical attention.

Skin contact
Wash area thoroughly with soap and water and seek medical attention.

Ingestion
Drink milk/water and induce vomiting; seek medical attention.

5. Fire Fighting Measures

General Hazard
Cell is not flammable. Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

Extinguishing Media
Use extinguishing media suitable for the materials that are burning.

Special Firefighting Instructions
If possible, remove cell(s) from fire fighting area. If heated above 160°C, cell(s) may explode/vent.

Firefighting Equipment
Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

6. Accidental Release Measures

On Land
Place material into suitable containers and call local fire/police department.

In Water
If possible, remove from water and call local fire/police department.

7. Handling and Storage

Handling
No special protective clothing required for handling individual cells.

Storage
Store in a cool, dry place.

8. Exposure Controls / Personal Protection

Engineering controls

Keep away from heat and open flame. Store in a cool dry place.

Personal Protection

Respirator

Not required during normal operations. SCBA required in the event of a fire.

Eye/face protection

Not required beyond safety practices of employer.

Gloves

Not required for handling of cells.

Foot protection

Steel toed shoes recommended for large container handling.

9. Physical and Chemical Properties

State	Solid
Odor	N/A
PH	N/A
Vapor pressure	N/A
Vapor density	N/A
Boiling point	N/A
Solubility in water	Insoluble
Specific gravity	N/A
Density	N/A

10. Stability and Reactivity

Reactivity
None

Incompatibilities
None during normal operation. Avoid exposure to heat, open flame, and corrosives.

Hazardous Decomposition Products
None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

Conditions To Avoid
Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

11. Toxicological Information

This product does not elicit toxicological properties during routine handling and use.

Sensitization	Teratogenicity	Reproductive toxicity	Acute toxicity
NO	NO	NO	NO

If the cells are opened through misuse or damage, discard immediately. Internal components of cell are irritants and sensitizers.

12. Ecological Information

Some materials within the cell are bioaccumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

13. Disposal Considerations

California regulated debris

RCRA Waste Code : Nonregulated

Dispose of according to all federal, state, and local regulations.

14. Transport Information

Lithium Ion batteries are considered to be "Rechargeable batteries" and meet the requirements of transportation by the U.S. Department of Transportation(DOT), International Civil Aviation Administration(ICAO), The 50th edition of International Air Transportation Association(IATA, 2009) special provision A45/A154 and belong to non-dangerous goods.

15. Regulatory Information

OSHA hazard communication standard (29 CFR 1910.1200)

_____Hazardous ____✔___Non-hazardous

Frequently Asked Questions (FAQ)