Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EXC-1.5-GFCI-15A-1523Y

18" 12/3 SOOW Linecord w/ GFCI Protected Outlet - 15 Amp - Explosion Proof Plug - Hot Work Permit

Product ID: 144137



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXC-1.5-GFCI-15A-1523Y - 5' GFCI Protected Linecord w/ EXP Plug
Male Cord Cap: (1) 5-15P - Explosion Proof
Female Receptacle: (1) 5-15R Standard Receptacle
Voltage Rating: 120 V
Max Amp Rating: 15 A
Cable Type: 12/3 SOOW
Cable Length: 18"
Weight: 1.5 lb

Approvals/Ratings
C1D1 15A Male Cord Cap
Hot Work Permit


Special Orders - Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in the USA

The EXC-1.5-GFCI-15A-1523Y from Larson Electronics is a 18" SOOW Linecord with GFCI Outlet that is designed for heavy duty and outdoor applications. This rugged extension cord is constructed of 18" 12-gauge 3-conductor wire, equipped with a single 15-amp rated explosion proof 5-15 male cord cap, an inline GFCI, a single 5-15R standard receptacle and allows operators to provide ground fault protection within hazardous locations.

The EXC-1.5-GFCI-15A-1523Y linecord provides a safe and effective way for operators to power a variety of general use devices within a hazardous location with a hot permit. The 18" of chemical and abrasion resistant flexible 12/3 SOOW cord is terminated in (1) male NEMA 5-15, 15 amp rated, explosion proof cord cap. An inline GFCI and (1) female 5-15R standard receptacle provides ground fault protection from explosion proof receptacles that do not provide GFCI

protection.
Hot Work Permit: This line cord is approved for hot work permit applications and allows operators to use their non-explosion proof equipment within an explosion proof environment. The alternative to this line cord is to convert non-explosion proof equipment to explosion proof plugs which can quickly become prohibitively expensive. Having the ability to use non-explosion proof equipment within hazardous areas when a job requires it makes this line cord able to greatly increase the versatility of non-explosion proof equipment. These industrial line cords are popularly used in hazardous locations when hot work permits have been acquired. We also offer class rated extension cords for use within explosion proof and hazardous location environments without hot work permits.
Applications: This GFCI protected linecord system is ideal for indoor or outdoor use and applications including but not limited to aircraft maintenance, alcohol processing, aerospace, chemical manufacturing, coke processing, cold storage, compressed natural gas (CNG) facilities, cranes, cryogenics, distilleries, food processing, fuel storage, gas processing plants, grain processing, laboratories, liquefied natural gas (LNG) facilities, liquid propane gas (LPG), manufacturing, marine vessels, methane production, mining, offshore, oil drilling rigs, oil refineries, paint spray booths, paper processing, petrochemical, pharmaceuticals, power plants, production refineries, sand blast cabinets, sewage and septic tanks, shipyards, solvent and cleaning areas, storage facilities, tank farms, tankers, textile, washdown areas, waste treatment plants, and woodworking. These industrial extensor cords are popularly used in hazardous locations when hot work permits have been acquired. We also offer class rated extension cords for use within explosion proof and hazardous location environments without hot work permits.
Larson Electronics is a manufacturer and as such can build extension cords and portable transformer systems to your specifications. Although we carry several models of power distribution transformers, we can deliver custom ordered units almost as quickly as our prebuilt units If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



TAGS	QTY	CATALOG	DESCRIPTION
J1-101.08	1	UNV00005389	5-15P EXPLOSION PROOF PLUG 125V 15A
J1-101.13	1	UNV00006732	5-15C 125V 15A CONNECTOR
1-101.14	1	UNV00001096	12/3 Cord Set Tri-Source End NEMA

LARSON ELECTRONICS
9419 E US HWY 175,
KEMP, TX 75143

TITLE: EXC-1.5-GFCI-15A-1523Y

DRAWN BY	DATE	REV
S. MAZZOCCHI	7/01/2022	A
CHECKED BY	SHEET #	DRAWING #
S. DESAI	1 OF 1	101

REV	DESCRIPTION	DATE
A	PRODUCTION RELEASE	7/01/2022

EXC-1.5-GFCI-15A-1523Y

LARSON ELECTRONICS®


AVOID SHOCK HAZARD:
THIS UNIT IS NOT INTENDED FOR USE AS AN ON-OFF SWITCH.
A14
INPUT/LINE
LARSON ELECTRONICS
EXC-1.5-GFCI-15A-1503Y
LARSONELECTRONICS.COM
1-800-369-6871
sales@larsonelectronics.com
OUTPUT/LOAD
1819


LARSON
ELECTRONICS


AVOID SHOCK HAZARD:
THIS UNIT IS NOT INTENDED FOR USE AS AN ON-OFF SWITCH.



Frequently Asked Questions (FAQ)