

EPL-24-2L-LV-SOL-80C-C1D2-20C

C1D1 Solar Powered Explosion Proof LED Lighting - 2' 2L Fixture - 80' Cord - C1D2 Panel

Product ID: 146985



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-24-2L-LV-SOL-80C-C1D2-20C Explosion Proof Solar Powered LED Light Fixture

Lamp Type: Solar LED

Lamp Dimensions: 8.5"H x 27.5"L x 11.25"W

Solar Panel Dimensions: 11-3/8"L x 15-3/4"D

Weight: 32 lbs

Voltage: 12V DC

Battery: (4) 18aH Sealed Lead Acid Batteries

Runtime: 10 Hours

Charging Time 5 Hours

Total Watts: 28W

Lumens: 3,500

Luminous Efficacy: 125 Lm/W

LED Lamp Life Expectancy: 50,000+ Hours

Color Temp: 5300K

Color Rendering Index: >80

Beam Angle: 150°

Lighting Configuration: Wide Flood Beam

Power Efficiency: >90%

Power Factor: >0.85

Amperage: 2.3A@12V DC

Operating Temp Range: -40°C to +65°C

Operating Temp Rating: T6

Housing Material: Cast Aluminum

Lens Material: Tempered Glass

Mounting: Bracket Standard - Pendant Optional

Wiring: 80' 10/2 SOOW Cord

Ratings/Approvals

Class I Division 2 Groups A, B, C, D

Class II Division 1 & 2 Groups E, F, G

Class I, Division 1 Groups C & D

NRTL Certified to UL 1598 Marine Type

NRTL Certified to UL 595 Outdoor Marine Type (Saltwater)

NRTL Certified to UL 844

NRTL Listed for United States & Canada

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in Texas

The EPL-24-2L-LV-SOL-80C-C1D2-20C Explosion Proof Solar Power LED light fixture from Larson Electronics is the ideal lighting solution for remote areas and standalone applications where connection to external power is either impractical or unavailable. This powerful yet compact hazardous location light delivers crisp, clean light while reducing operating costs. Charged by the 120 watt Class I, Division 2 solar panel, four 12V AC 18aH sealed lead acid batteries provide constant, reliable power to the 2 tube, 28 watt fixture. The EPL-24-2L-LV-SOL-80C-C1D2-20C ships with a convenient 80' of 10/2 SOOW cord connecting the solar panel to the light fixture which allows operators to position the panel where the most ambient light is available.

This 2 foot long, 2 LED tube, explosion proof solar light fixture is ideal for use in remote locations requiring powerful yet compact hazardous location lighting. The EPL-24-2L-LV-SOL-80C-C1D2-20C features our second generation LED T-series 14 watt T17 style lamps which produce 15% more illumination at 8 feet as compared to standard T8 lamps when measured with an Extech light meter. Our LED-T series bulbs are visibly brighter than standard T8s and have consistently surprised many of our customers with their unexpectedly high light output levels.

We have eliminated the ballast box normally associated with fluorescent fixtures which reduces overall weight, creates a slimmer unit profile, and helps this LED fixture maintain a T-6 temperature rating. The solid state design of the LED lamps gives this fixture superior resistance to damage from vibrations and extremes in temperature as well as a lamp service life over twice that of standard T8 bulbs.



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



Charged by the 120 watt Class I, Division 2 rated solar panel, four 12V AC 18aH sealed lead acid batteries provide constant, reliable power to the 2 tube, 28 watt fixture. The batteries, 24V Class I, Division 2 charge controller, and battery disconnect are contained within a NEAM 4X remote enclosure to be installed within a Class I, Division 2 environment. 20' of photovoltaic cable between the enclosure and light fixture allows for easy mounting of the panel and control box. The EPL-24-2L-LV-SOL-80C-C1D2-20C ships with a convenient 80' of 10/2 SOOW cord connecting the control box to the light fixture which allows operators to position the panel and control box where the most ambient light is available.

The control box is equipped with either a day/night sensor and motion sensor or with an on/off switch. The day/night and motion sensor is programmed to activate the solar panel in the evening and to shut it off during the day while the motion sensor will activate the panel upon detecting motion. The on/off switch will activate and shut off the solar panel according to the operator's preference. Operators can switch between modes with a toggle switch.

The EPL-24-2L-LV-SOL-80C-C1D2-20C provides 10 hours of continuous runtime when the battery is fully charged. Charging time for the battery bank is 5 hours when exposed to direct sunlight. As with all solar powered equipment, charging time is affected by the amount of available ambient light. Indirect sunlight and low ambient light levels, such as on cloudy days, will extend the charge time.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation.

Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. Solid state LED lighting is also safer for the environment as LEDs are 100% recyclable. And recycling simultaneously reduces operating costs by eliminating the need for the expensive special disposal services required with traditional gas burning and arc type lamps.

NOTE: Larson Electronics has further upgraded the options available with this light. We expect the light to be mounted separately from the panel. This means the solar panel can be mounted in direct sunlight (not in the hazardous area) while the light is mounted in a hazardous area workspace. Standard installation for explosion proof lighting, including threaded rigid pipe to the LED light fixture and appropriate seal-offs, etc. are required.

Additional Mounting Options: Unless otherwise specified, our standard, most popular configuration is the bracket end mounting shown above. We also offer a pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit).

Standard Bracket Mounts: Each bracket is cinched to the bracket mounting peg on each side of the light. The angle of the bracket is set by tightening two cap screws on either side of the bracket. The cap screws act as a set screw. The bracket itself is mounted via a single bolt hole at the top of the bracket. There are two brackets, one on each end of the light. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be removed from the brackets by loosening the cap screws that hold the bracket to the mounting peg. The pictures shown above illustrate the side brackets. The third picture enlarged below also shows the brackets at the both ends of the light.

Power/Wiring: This EPL-24-2L-LV-SOL-80C-C1D2-20C is powered by two 12V AC 18Ah sealed lead acid batteries that are recharged by a 30 watt solar panel. These rechargeable batteries provide a continuous supply of steady, reliable power. The lead acid battery pack is contained within the solar panel, not the light. This fixture ships with 80 feet of 10/2 SOOW cord that connects the light fixture to the solar panel. Custom lengths are available upon request. Please contact us for special requirements.

Suggested Applications: Paint spray booths, Aircraft maintenance, Oil drilling rigs, Refineries, Solvent and cleaning areas, Gas processing plants, Chemical manufacturing, Waste treatment plants, Gas processing plants

High Quality Features

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy
4. No ballast box. No ballast to replace. We simply run the black wire to one end of the bulb and white wire to the other.
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. A wrench is used to unscrew the end caps for relamping the

Superior LED Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LEED and other sustainable business certifications.

fixture, while some competitive models require the end tap and knock off method to loosen the end cap.

7. Explosion proof, impact and heat resistant Pyrex tubes provide lamp protection.

9. Bright, even light maintains consistent color over time.

10. Instant on/off - No flickering, delays or buzzing.

11. Very good color rendering.

12. Vibration/impact resistant.

13. Significantly cooler operation.

14. Less frequent outages, higher output improves workplace safety.









SECTION 1: PRODUCT NAME

Valve regulated lead-acid batteries.

SECTION 2: HAZARDOUS COMPONENTS

COMPONENTS	%WEIGHT	TLV	LD50 ORAL	LC50 INHALATION	LC50 CONTACT
Lead (Pb, PbO, PbSO) 24	About 70%	N/A	(500) mg/Kg	N/A	N/A
Sulfuric Acid	About 20%	1 mg/m ³	(2.140) mg/Kg	N/A	N/A
Fiberglass Separator	About 5%	N/A	N/A	N/A	N/A
ABS or PP	About 5%	N/A	N/A	N/A	N/A

SECTION 3: PHYSICAL DATA

COMPONENTS	DENSITY	MELTING POINT	SOLLUBILITY (H2O)	ODOR	APPEARANCE
Lead	11.34	327.4°C (Boiling)	None	None	Silver-Grey Metal
Lead Sulfate	6.2	1070°C (Boiling)	40 mg/L(15°C)	None	White Powder
Lead Dioxide	9.4	290°C (Boiling)	None	None	Brown Powder
Sulfuric Acid	About 1.3	About 114°C (Boiling)	100%	Acidic	Clear Colorless Liquid
Fiberglass Sep.	N/A	N/A	Slight	Toxic	White Fibrous Glass
ABS or PP	N/A	N/A	None	No Odor	Solid

SECTION 4: PROTECTION

EXPOSURE	PROTECTION	COMMENTS
SKIN	Rubber gloves, Apron, Safety shoes	Protective equipment must be worn if battery is cracked or otherwise damaged.
RESPIRATORY	Respirator (for lead)	A respirator should be worn during reclamation operations if the TLV is exceeded.
EYES	Safety goggles, Face Shield	

SECTION 5: FLAMMABILITY DATA

COMPONENTS	FLASHPOINT	EXPLOSIVE LIMITS	COMMENTS
Lead	None	None	
Sulfuric Acid	None	None	
Hydrogen	259?	4% - 74.2%	Batteries can emit hydrogen only if over charged (float voltage > 2.4 VPC). The gas enters the air through the vent caps. To avoid the chance of a fire or explosion, keep sparks and other sources of ignition away from the battery. Extinguishing Media: Dry chemical, foam, CO ₂ .
Fiberglass Sep.	N/A	N/A	Toxic vapors may be released. In case of fire: wear self-contained breathing apparatus.
478 Polystyrene	None	N/A	Temperatures over 300 °C (572°F) may release combustible gases. In case of fire: wear positive pressure self-contained breathing apparatus.

SECTION 6: REACTIVITY DATA

COMPONENT	Lead/lead compounds
STABILITY	Stable
INCOMPATIBILITY	Potassium, carbides, sulfides, peroxides, phosphorus, sulfurs.
DECOMPOSITION PRODUCTS	Oxides of lead and sulfur.
CONDITIONS TO AVOID	High temperature, Sparks and other sources of ignition
COMPONENT	Sulfuric Acid
STABILITY	Stable at all temperatures
POLYMERIZATION	Will not polymerize
INCOMPATIBILITY	Reactive metals, strong bases, most organic compounds
DECOMPOSITION PRODUCTS	Sulfuric dioxide, trioxide, hydrogen sulfide, hydrogen
CONDITIONS TO AVOID	Prohibit smoking, sparks, etc. from battery charging area. Avoid mixing acid with other chemicals.

SECTION 7: CONTROL MEASURES

1. Store lead-acid batteries with adequate ventilation. Room ventilation is required for batteries utilized for standby power generation. Never recharge batteries in an unventilated, enclosed space.

2. Do not remove vent caps. Follow shipping and handling instructions that are applicable to the battery type. To avoid damage to terminals and seals, do not double-stack industrial batteries.

STEPS TO TAKE IN CASE OF LEAKS OR SPILLS

If sulfuric acid is spilled from a battery, neutralize the acid with sodium bicarbonate (baking soda), sodium carbon (soda ash), or calcium oxide (lime).

Flush the area with water. Do not allow unneutralized acid into the sewage system.

WASTE DISPOSAL METHOD:

Neutralized acid may be flushed down the sewer. Spent batteries must be treated as hazardous waste and disposed of according to local state, and federal regulations. A copy of this material safety data must be supplied to any scrap dealer or secondary smelter with battery.

ELECTRICAL SAFETY

Due to the battery's low internal resistance and high power density; high levels of current can be developed across the battery terminals. Do not rest tools or cables on the battery. Use insulated tools only.

Follow all installation instruction and diagrams when installing or maintaining battery systems.

SECTION 8: HEALTH HAZARD DATA

LEAD: The toxic effects of lead are cumulative and slow to appear. It affects the kidneys, reproductive, and central nervous system. The symptoms of lead overexposure are anemia, vomiting, headache, stomach pain (lead colic), dizziness, loss of appetite, and muscle and joint pain. Exposure to lead from a battery most often occurs during lead reclaim operations through the breathing or ingestion of lead dusts and fumes.

THIS DATA MUST BE PASSED TO ANY SCRAP OR SMELTER WHEN A BATTERY IS RESOLD.

SULFURIC ACID: Sulfuric acid is a strong corrosive. Contact with acid can cause severe burns on the skin and in the eyes. Ingestion of sulfuric acid will cause GI tract burns. Acid can be released if the battery case is damaged or if the vents are tampered with.

FIBERGLASS SEPARATOR: Fibrous glass is an irritant of the upper respiratory tract, skin and eyes. For exposure up to 10F/CC use MSA Comfort with type H filter. Above 10F/CC up to 50F/CC use Ultra-Twin with type H filter. NTP or OSHA does not consider this product carcinogenic.

SECTION 9: SULFURIC ACID PRECAUTIONS

INHALATION: Acid mist may cause respiratory irritation. Remove any individual from exposure, and apply oxygen if breathing is difficult.

SKIN CONTACT: Acid may cause irritation, burns or ulceration. Flush with plenty of soap and water, remove contaminated clothing, and see physician if contact area is large or if blisters form.

EYE CONTACT: Acid may cause severe irritation, burns, cornea damage and blindness. Call physician immediately and flush with water until physician arrives.

INGESTION: Acid may cause irritation of mouth, throat, esophagus and stomach. Call physician. If patient is conscious, flush mouth with water, have the patient drink milk or sodium bicarbonate solution.

DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON.

SECTION 10: TRANSPORTATION REGULATIONS

We hereby certify that all Larson Electronics Valve Regulated Lead-acid Rechargeable batteries conform to the UN2800 classification as "Batteries, wet, Non-Spillable, and electric storage" as a result of passing the Vibration and Pressure Differential Test described in D.O.T., 49 CFR 173.159(d), and IMO/IMDG, and ICAO/IATA packing instruction 872 and note A67. Batteries having met the related conditions are EXEMPT from hazardous goods regulations for the purpose of transportation by DOT, and IATA/ICAO, and therefore are unrestricted for transportation by any means. For all modes of transportation, each battery outer package is labeled "NON-SPILLABLE". All our Batteries are marked non-spillable.

Updated: Nov. 20, 2012

Frequently Asked Questions (FAQ)