

HAL-EMG-EXT-3L-10W

10W Explosion Proof LED Emergency Exit Sign w/ Halogen Bug Eyes - C1D2 - 120/277VAC - Self Testing

Product ID: 147274



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-EMG-EXT-3L-10W Explosion Proof LED Emergency Exit Sign

Device Type: Emergency Lighting System

Lamp Types: LED (Exit Sign), MR16 Halogen Bug Eyes

Dimensions: 14.5" x 12.7" x 3.5"

Weight: 20 lbs

Input Voltage: 120/277V AC @ 60Hz

Lamp Voltage: 12V DC

Watts: 10W (Max 29W) [Unit]; 12W (Max 24W) [Lamps]

Current: 0.30/0.08A (Max), 0.13/0.05A (Standby)

Temperature Rating/Max Temp: T3A/180 C

Battery Type: Sealed, Maintenance-free Nickel Cadmium

Battery Runtime: 90 Minutes

Lamp Material: Cast Aluminum Housing w/ Polycarbonate Cover

Exit Sign Material: PVC Body, Polycarbonate Cover w/ Stainless Steel, Tamper-Resistant Screws

Frame Material: Polyvinyl Chloride w/ Built-in Gasket

Mount: Wall Mount via 1/2" Electrical Conduit Entry (Both Sides and Top of Unit)

Quick Summary

Class I, Division 2 Groups A, B, C, D

CSA/cUL evaluated to UL Standards 924, 844 and 1598

Advanced Diagnostics (Non-Audible)

Self Testing

Short Circuit Proof

Brownout Protection

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-214-616-6180

Toll Free: 1-800-369-6671

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics HAL-EMG-EXT-3L-10W explosion proof LED emergency exit sign w/ halogen bug eyes features reliable illumination and notification in Class I, Division 2 hazardous locations. This unit supports 120-277V AC input voltages (29W max) and 12V DC output (24W max). The bug eye lamps are equipped with MR16 halogen bulbs. In the event of power outage, this unit will continue to function for 90 minutes via a sealed, maintenance-free nickel cadmium battery. A self-

testing mechanism automates monitoring of critical functions within the unit.

This hazardous area LED emergency exit sign is suitable for Class I, Division 2 rated facilities. During operation, the unit features 120-227V AC input voltages (12V DC output for the lamp). The unit consumes 10 watts (max 29W), while the lamp consumes 12 watts (max 24W). Should power outage occur, the unit may revert to a nickel cadmium battery for power, which offers a runtime of 90 minutes. A low voltage battery disconnect built into the device preserves the solid-state battery and charger. This unit is constructed of cast aluminum with a sturdy polycarbonate cover and stainless steel, tamper-resistant screws.

Advanced Diagnostic circuitry is available in the HAL-EMG-EXT-3L-10W. This circuitry is programmed to ensure the combination unit's readiness and reliability by continuously monitoring every critical function of the unit. If a problem occurs, a single "Service Required" indicator illuminates immediately. A detailed diagnostic display that will further indicate the nature of the fault is located on the inside of the exit sign, out of sight from the general public. The self test will test the unit for a minimum of 30 seconds every 30 days, 30 minutes every 60 days and 90 minutes annually.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Mount: This unit is designed for wall mounts via a 1/2" electrical conduit entry on both sides and at the top.

Applications: Manufacturing plants, chemical plants, paint shops, oil refineries, gas stations, industrial facilities, warehouses, processing plants and other Class I, Division 2 hazardous locations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Input Max: 120/277Vac, 50/60, 30/80A, 200W
Output: 12Vdc, 20W / 80 Min.
EMERGENCY LIGHTING EQUIPMENT FOR HAZARDOUS LOCATIONS
UL Listed, Group A, B, C, D
Suitable for Wet Locations 80°C Max. Amb. Temp. Code: T4A
CAUTION: See instructions for details for installation, operation and maintenance.

- WARNING -

EMERGENCY LIGHTING EQUIPMENT
UL LISTED, GROUP A, B, C, D
Suitable for Wet Locations 80°C Max. Amb. Temp. Code: T4A







Frequently Asked Questions (FAQ)