

GAU-HB-50LED-RT

50 Watt Low Bay LED Light Fixture - Outdoor Rated - IP67 - 4,333 Lumens

Product ID: 148236



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

GAU-HB-50LED-RT - C1D1 Low Bay LED Light

Listing: United States - Canada

Lamp Type: LED

Dimensions: 7.04" L x 7.04" H x 5.72" D

Weight: 7 lbs

Voltage: 100-277 Volts AC, 50/60Hz or 11-25 Volts AC/DC

Total Watts: 50W

Total Lumens: 4,333

Luminous Efficacy: 86.67 Lm/W

Lamp Life: 60,000+ Hours

Color Temp: 5600K, 4500K, 3000K

Color Rendering Index: >75 CRI

Beam Angle: 60° or 125°

Lighting Configuration: Flood Pattern

Power Efficiency: >95%

Power Factor: 0.992

Ambient Operating Temp Range: -50° C to +65°C

Operating Temp Rating: T5

Housing Material: Copper Free Cast Aluminum

Housing Finish: Epoxy Powder Coated - Grey

Lens Material: Hardened Borosilicate Glass

Gasket Material: Silicone

Mounting: 3/4" Pendant & Wall/Surface Mount - Both Ship w/ Fixture

Wiring: 10' 16/3 SOOW w/ Flying Leads

Wiring Hubs: (5) 3/4" NPT Threaded Hubs

Ratings/Approvals

Listed for United States and Canada

Certified to C22.2 No. 250.0

Certified to UL 1598

Paint Spray Booth Approved

IP67 Rated Waterproof

Single LED Driver

80% Lumen Retention after 60,000 Hours

Factory Sealed Light Fixture

Recommended 15' to 40' Mounting Height

Special Orders- Requirements

Contact us for special requirements

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics GAU-HB-50LED-RT Low Bay light fixture provides operators with a powerful and energy efficient alternative to traditional luminaries. LED technology and compact design makes this lamp an excellent replacement upgrade option for bulky and high maintenance cost older incandescent, metal halide and high pressure sodium lights.

This industrial grade light fixture provides 4,333 lumens of high quality light while drawing only 50 watts. The copper free aluminum alloy body is powder coated for added durability and an attractive aesthetic appearance. Special heat dissipating design in conjunction with LED technology helps this fixture to achieve an excellent 60,000 hour rated lifespan with 80% lumen retention. Light weight and a low profile make this unit an attractive alternative to larger and heavier older fixtures and requires less hardware to install. The GAU-HB-50LED-RT low bay LED light also offers operators convenience in the form of field serviceability.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life. LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

LED Drivers: Even in LED fixtures, heat is the single largest factor in premature light failure and color shifting. As a result, many manufacturers reduce the output of their LEDs in order to reduce the amount of heat produced. Rather than lower light output or quality, Larson Electronics addresses this problem with the addition of an electronic LED driver. This internal driver provides the ability to automatically monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. This not only reduces the energy dissipation, effectively lowering the operating temperature of the fixture, but also prevents AC over-voltage and short circuit loading making this fixture virtually maintenance free. Because the electronic driver allows the GAU-HB-50LED-RT to run at a cooler internal temperature and regulates the electrical current, energy efficiency and LED service hours are maximized while at the same time reducing operating costs and downtime incurred from the frequent servicing intervals required with other hotter running lights.

This light is universal voltage capable and can be operated with 100-277 VAC, 50/60Hz. We also offer a low voltage version of this LED fixture that operates on AC/DC voltages from 11-25 Volts. This LED light fixture is IP67 rated, dust-proof, and protected against high pressure jets and temporary submersion. The cast aluminum body and LED lamp give this light excellent durability and resistance to vibration and impacts. The housing is specially designed to dissipate heat which increases the efficiency and lifespan of the LEDs and electronics.

Wiring: The GAU-HB-50LED-RT low bay LED light fixture is equipped with 10 feet of abrasion and chemical resistant 16/3 SOOW cable with flying leads. The LED light fixture features 5 3/4" NPT threaded ports for running conduit depending on the installation location. Four of the ports are located on the corners of the unit and the fifth port is found on the rear of the industrial grade low bay LED fixture.

Energy Consumption Comparison

	<u>Metal Halide</u>	<u>LED</u>
Wattage	175 watts	50 watts

Amp Draw @ 120V AC	1.69 amps	0.42 amps
Amp Draw @ 220V AC	0.92 amps	0.23 amps
Amp Draw @ 240V AC	0.85 amps	0.21 amps
Amp Draw @ 277V AC	0.73 amps	0.18 amps
Amp Draw @ 12V DC	16.77 amps	4.17 amps
Amp Draw @ 24V DC	8.39 amps	2.08 amps
Lamp Life Expectancy	20,000 hours	60,000+ hours
Operation cost per year (12hs/day @ 12c/kWh)	\$241.78	\$26.30

Each LED light fixture has the potential to save \$150.00+ per year in electricity alone, not including maintenance costs, operational downtime, reduced productivity, HVAC loads, or carbon footprint. When retrofitting an entire facility with 100s of light fixtures, the return on investment of LED over metal halide becomes evident.

This LED light produces 4,333 lumens with a color temperature of 5600K and a color rendering index of 75 which produces colors and details much more accurately than high pressure sodium or mercury vapor luminaries. We also offer a 3000K warm white and 4500K natural white color temperature options (longer lead times may apply for non-standard temperatures). The GAU-HB-50LED-RT offers several mounting options including ceiling mounting, pendant mounting, wall mounting and cable mounting. The standard version of this LED fixture includes a pendant mount and a surface mount option.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

High Quality Features

1. Low power consumption.
2. Instant on/off operation.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy.
4. Superior color rendering compared to HPS, LPS, MH.
5. Retains 80% lumen output after 60,000 operating hours.
6. Powder coated aluminum fixture body.
7. Pendant and Swivel Bracket mount included
8. Low profile - Light weight
9. 4,333 Lumen output from 50 watts

Superior LED Benefits

1. 60,000+ hour lifespan.
 2. Can SAVE 50% or more on energy.
 3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
 4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
 5. 100% recyclable.
 6. No toxins-lead, mercury.
 7. No UV light, infrared radiation or CO2 emissions.
 8. Qualifies buildings for LED and other sustainable business certifications.
 9. Bright, even light maintains consistent color over time.
 10. Instant on/off - No flickering, delays or buzzing.
 11. Very good color rendering.
 12. Vibration/impact resistant.
 13. Significantly cooler operation.
 14. Less frequent outages, higher output improves workplace safety.
-

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364









Frequently Asked Questions (FAQ)