Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

CHICO-SPS-6OZ

Explosion Proof Seal Compound - Seal for C1D1 and C2D2 Hazardous Locations - 6oz

Product ID: 148521



Image: CHICO-SPS-6OZ

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

CHICO-SPS-6OZ Explosion Proof Sealing Compound
Size: 6 oz.
Seal Time: 5 minutes
Cure Time: 20 minutes
Shelf Life: 18 months
Storage Temperature: 10°C - 85°C
Ambient Operating Temperature: -50°C - 150°C (-50°F - +302°F)

Certifications - Compliance
Class I, Division 1 Groups C, D
Class II, Division 1 Groups E, F, G
Special Orders - Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The CHICO-SPS-6OZ Explosion Proof Sealing Compound is designed for electrical conductors in hazardous locations.

This sealing compound separates and forms an explosion proof seal around each conductor and helps to restrict the passage of gases, vapors or flames through the sealed fitting. The CHICO-SPS-6OZ creates a tight seal for electrical conductors used in Class I, Division 1 Groups c and D and Class II, Division 1 Groups E, F and G hazardous locations. Installs seal in 5 minutes and completely hardens within 20 minutes. Packaging includes a 6 oz. pre-measured cartridge and screw-on nozzle for accurate distribution.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs