Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-ISX-SS-3P-480D-30KVA-208Y.120-N1-ES

30 kVA Isolation Transformer - 480V Delta Primary - 208Y/120 Secondary - Stainless Steel - NEMA 1

Product ID: 149234



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-SS-3P-480D-30KVA-208Y.120-N1-ES Isolation Transformer

Phase: Three Phase
Frequency: 60Hz
kVA: 30
Primary Voltage: 480V Delta
Primary Connection: Delta
Primary BIL: 10kV
Primary FCAN (Std): 2 x 2.5%
Primary FCBN (Std): 4 x 2.5%
Secondary Voltage: 208Y/120
Secondary Connection: Wye-N
Secondary BIL: 10kV
Winding Material: Copper
Efficiency Regulation: DOE 2016
Impedance: 2.5 - 6.5%
Secondary Phase Angle: 30°
Insulation: 220°
Temperature Rise: 150°C
Ambient Temperature Rating: 40°
Electrostatic Shield: Yes - Dry Type
Seismic Zone: Zone 4
Primary Termination: Mechanical Lugs
Secondary Termination: Mechanical Lugs
Sound Level: Meets NEMA ST-20 Standards
Enclosure Material: NEMA 1 - Stainless Steel
Finish: Stainless Steel
Dimensions: 28.75"H x 25.75"W x 23.8"D

Approvals/Ratings

Listing: UL Listed
CSA Certified
Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Weight: 380 lbs

E-mail: sales@larsonelectronics.com

The MT-ISX-SS-3P-480D-30KVA-208Y.120-N1-ES 480D 3 Phase Energy Efficient Isolation Transformer with Stainless Steel Housing from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for indoor applications, the MT-ISX-SS-3P-480D-30KVA-208Y.120-N1-ES provides increased reliability, protection against critical equipment failures and an extra level of protection by isolating the power source from the connected device. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 30kVA, the MT-ISX-SS-3P-480D-30KVA-208Y.120-N1-ES isolation transformer is a three phase unit with a primary voltage of 480V Delta. It also provides a secondary voltage of 208Y/120 Wye-N. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology. This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type N1 enclosure makes the unit suitable for indoor applications and it can be either floor or wall mounted. The unit also features a 220° insulation with a 80°C temperature rise.

Benefits: The MT-ISX-SS-3P-480D-30KVA-208Y.120-N1-ES isolation transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-ISX-SS-3P-480D-30KVA-208Y.120-N1-ES is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-SS-3P-480D-30KVA-208Y.120-N1-ES achieves these safety features by seperating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: Power supplies for sensitive equipment such as computers, medical devices, or laboratory instruments.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


DANGER PELIGRO




M



Frequently Asked Questions (FAQ)