

XLE-ALS-4AWG

Full Tension Automatic Splice - For #4 or #2 ACSR/AAAC/AAC Cables

Product ID: 149588



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

The Larson Electronics XLE-ALS-4AWG Full Tension Automatic Splice is the fastest and safest method for permanently splicing tensioned conductors. This splice provides permanent mechanical holding and electrical current transfer.

One per purchase.

Specs:

Conductor Type - AAC, AAAC, ACSR

Conductor Diameter - (Minimum) 0.22 in

Conductor Diameter - (Maximum) 0.32 in

Automatic Conductor Range - #4-#2 ACSR#4-#2 AAAC#4-#2 AAC

Material - Aluminum

Gripper Material - Aluminum Alloy

Minimum Conductor Diameter -0.22 in

Maximum Conductor Diameter -0.32 in

Outside Diameter - 0.220 - 0.320 in (5.59 - 8.13 mm)

Dimension A - 12 in (290 mm)

Dimension B -1.0 in (25 mm)

Inhibitor Loaded -Yes

Weight / Ea. -0.343 lbs





Frequently Asked Questions (FAQ)