

RL-85-LED-36W-CPR

10 Million Candlepower Rechargeable LED Light Hunting Spotlight- 36 Watts - Pistol Style -3200 Lumen

Product ID: 149604



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

RL-85-LED-36W-CPR Handheld Spotlight

Lamp Type: Cree LED

Dimensions: 7.95"L x 2.75"W x 8.37"D

Weight: 1.5 lbs

Voltage: 120-240V AC or 12-24V DC

Total Watts: 36W

Total Lumens: 3,200

Candlepower: 10 Million

Luminous Efficacy: 88.89 Lm/W

LED Lamp Life Expectancy: 50,000+

Wiring: Detachable Charger

Cord Options: 5-10P (US Charger), Schuko (Intl 240V Charger), or Cigarette Plug (DC Charger)

Beam Type: Spot

Housing Material: ABS Polymer & Aluminum Alloy

Housing Color: Black

Lens Material: Polycarbonate

Mounting: Handheld

Quick Summary

IP67 Waterproof

Dustproof

Shockproof

Impact/Vibration Resistant Construction

Lightweight

Portable

Continual On/Off Switch

Push Once to Power On, Push Again to Power Off

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The RL-85-LED-36W-CPR super bright handheld 10 million candlepower spotlight from Larson Electronics is lightweight, ultra rugged, and features a comfortable ergonomic design. This unit uses seven high output Cree LEDs and an advanced reflector and lens configuration to generate 3,200 lumens with a beam reach of over 1,600 feet while drawing only 36 watts of power. Operating on 12-24V DC or 120V or 240V, this IP67 rated waterproof spotlight is ideal for hunting, camping,

marine and boating use as well as for first responders and emergency services. The RL-85-LED-36W-CPR features a continual on/off switch that requires one press to stay on and another press to turn off.

Light Features: The RL-85-LED-36W-CPR super bright handheld spotlight delivers an impressive 3,200 lumens while drawing only 36 watts of energy. With a combination seven high output Cree LEDs and a 5" reflector, this spotlight cuts through the darkness with a beam length of over 1,600 feet. The Cree LED units in this light have been chosen for their high lumen per watt ratio and extreme longevity.

This IP65 rated spotlight features an ultra-durable ABS shockproof polymer body, an aluminum alloy light head housing, and an impact resistant polycarbonate lens. While the RL-85-LED-36W-CPR is built to withstand rugged use and harsh outdoor conditions, comfort and ease of operation haven't been sacrificed. This unit is ergonomically designed for balanced and comfortable handling. The nylon handle has a no-slip textured surface that ensures a firm grip even in wet conditions. The booted push button is conveniently placed to allow operators easy forefinger access to the switch for quick on/off action.

Larson Electronics offers additional options for the RL-85-LED-36W-CPR spotlight, including red and green lenses. For more information, contact sales@larsonelectronics.com.



[Click Photo to Enlarge](#)

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life. LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Cree Specific: This lamp uses Cree LED units that have been chosen for their high lumen per watt ratio and extreme longevity. These Cree LEDs generate a robust 80 lumens per watt effective lumen output and have a 70% lumen retention at 50,000 hours, giving them better efficiency and operational life than traditional light sources.



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)

Power: The rechargeable RL-85-LED-36W-CPR spotlight comes equipped with a

7.4V 2600MA lithium battery and is recharged using an included AC charger. A 120V or 240V wall charger comes standard, or an optional vehicle charger that operates on 12-24V DC. This light has a work time of 2.5-3 hours on a single charge. Recharging from a fully discharged state takes 3 hours.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

High Quality Features

1. Low power consumption.
2. Instant on/off operation.
3. Nylon and aluminum alloy body.
4. Durable polycarbonate lens.
5. Retains 70% lumen output after 50,000 operating hours.
6. Ergonomic nylon handle.
7. Built for Toughness and Durability
8. Low profile - Lightweight
9. 2,000 Lumen output from only 25 watts.

Superior LED Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off - No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.







LARSON
ELECTRONICS
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com



MATERIAL SAFETY DATA SHEET**Model ICR18650S3 Lithium Ion Rechargeable Battery****LG CHEMICAL LTD****1. Chemical Product and Company Identification****Product Identification**

LG CHEM ICR18650S3 Lithium-Ion Battery

Manufacturer

LG Chemical Ltd.

Twin Tower

Youido-Dong 120, Youngdeungpo-Ku

Seoul, Korea

Emergency Telephone Number

82-2-3773-7256

2. Composition Information

Hazardous Ingredients	%	CAS Number
Aluminum Foil	2-10	7429-90-5
Metal Oxide (proprietary)	20-50	
Polyvinylidene Fluoride (PVDF)	<5	24937-79-9
Copper Foil	2-10	7440-50-8
Carbon (proprietary)	10-30	7440-44-0
Electrolyte (proprietary)	10-20	
Stainless steel, Nickel and inert materials	Remainder	N/A

* Equivalent Lithium Content: 0.66g, Electric Power Capacity: 7.92Wh

3. Hazards Identification

Emergency Overview

May explode in a fire, which could release hydrogen fluoride gas.

Use extinguishing media suitable for materials burning in fire.

Primary routes of entry

Skin contact	:	NO
Skin absorption	:	NO
Eye contact	:	NO
Inhalation	:	NO
Ingestion	:	NO

Symptoms of exposure

Skin contact

No effect under routine handling and use.

Skin absorption

No effect under routine handling and use.

Eye contact

No effect under routine handling and use.

Inhalation

No effect under routine handling and use.

Reported as carcinogen

Not applicable

4. First Aid Measures

Inhalation

Not a health hazard.

Eye contact

Not a health hazard.

Skin contact

Not a health hazard.

Ingestion

If swallowed, obtain medical attention immediately.

**IF EXPOSURE TO INTERNAL MATERIALS WITHIN CELL DUE TO
DAMAGED OUTER CASING, THE FOLLOWING ACTIONS ARE
RECOMMENDED ;**

Inhalation

Leave area immediately and seek medical attention.

Eye contact

Rinse eyes with water for 15 minutes and seek medical attention.

Skin contact

Wash area thoroughly with soap and water and seek medical attention.

Ingestion

Drink milk/water and induce vomiting; seek medical attention.

5. Fire Fighting Measures

General Hazard

Cell is not flammable. Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

Extinguishing Media

Use extinguishing media suitable for the materials that are burning.

Special Firefighting Instructions

If possible, remove cell(s) from fire fighting area. If heated above 160°C, cell(s) may explode/vent.

Firefighting Equipment

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

6. Accidental Release Measures

On Land

Place material into suitable containers and call local fire/police department.

In Water

If possible, remove from water and call local fire/police department.

7. Handling and Storage

Handling

No special protective clothing required for handling individual cells.

Storage

Store in a cool, dry place.

8. Exposure Controls / Personal Protection

Engineering controls

Keep away from heat and open flame. Store in a cool dry place.

Personal Protection

Respirator

Not required during normal operations. SCBA required in the event of a fire.

Eye/face protection

Not required beyond safety practices of employer.

Gloves

Not required for handling of cells.

Foot protection

Steel toed shoes recommended for large container handling.

9. Physical and Chemical Properties

State	Solid
Odor	N/A
PH	N/A
Vapor pressure	N/A
Vapor density	N/A
Boiling point	N/A
Solubility in water	Insoluble
Specific gravity	N/A
Density	N/A

10. Stability and Reactivity

Reactivity

None

Incompatibilities

None during normal operation. Avoid exposure to heat, open flame, and corrosives.

Hazardous Decomposition Products

None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

Conditions To Avoid

Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

11. Toxicological Information

This product does not elicit toxicological properties during routine handling and use.

Sensitization	Teratogenicity	Reproductive toxicity	Acute toxicity
NO	NO	NO	NO

If the cells are opened through misuse or damage, discard immediately. Internal components of cell are irritants and sensitizers.

12. Ecological Information

Some materials within the cell are bioaccumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

13. Disposal Considerations

California regulated debris

RCRA Waste Code : Nonregulated

Dispose of according to all federal, state, and local regulations.

14. Transport Information

Lithium Ion batteries are considered to be "Rechargeable batteries" and meet the requirements of transportation by the U.S. Department of Transportation(DOT), International Civil Aviation Administration(ICAO), The 50th edition of International Air Transportation Association(IATA, 2009) special provision A45/A154 and belong to non-dangerous goods.

15. Regulatory Information

OSHA hazard communication standard (29 CFR 1910.1200)

_____Hazardous

_____✓_____Non-hazardous

Frequently Asked Questions (FAQ)