Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-ISX-1P-208V-75KVA-120.240V-N3R

75 kVA Isolation Transformer - 208V Primary - 120/240V Secondary - Single Phase - NEMA 3R

Product ID: 149825



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-1P-208V-75KVA-120.240V-N3R Isolation Transformer

Phase: Single Phase
Frequency: 60Hz
kVA: 75
Primary Voltage: 208V
Taps: (2) 2.5% FCAN Above, (4) 2.5% FCBN Below
Secondary Voltage: 120/240V
Winding Material: Aluminum
Insulation: 220°C
Temperature Rise: 150°C
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated
Finish: ANSI 61 Grey, UL50 Finish
Dimensions: -
Weight: -

Approvals/Ratings

Listing: UL Listed
CSA Certified
Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-ISX-1P-208V-75KVA-120.240V-N3R 208V 1 Phase Energy Efficient Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-1P-208V-75KVA-120.240V-N3R provides increased reliablity, protection against critical equipment failures and an extra level of protection by isolating the power source from the connected device. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a

wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 75kVA, the MT-ISX-1P-208V-75KVA-120.240V-N3R isolation transformer is a single phase unit with a primary voltage of 208V. It also provides a secondary voltage of 120/240V. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be either floor or wall mounted. The unit also features a 220° insulation with a 150°C temperature rise and is rated IP24.

Benefits: The MT-ISX-1P-208V-75KVA-120.240V-N3R isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electricallybalanced to minimize axial forces during short circuit situations.

This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-ISX-1P-208V-75KVA-120.240V-N3R is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-1P-208V-75KVA-120.240V-N3R achieves these safety features by seperating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.


Applications: Power supplies for sensitive equipment such as computers, medical devices, or laboratory instruments.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


Wiring Diagram

WARNING: *DO NOT SERVICE WHILE ENERGIZED!*

MT-ISX-1P-208V-75KVA-120.240V-N3R



COIL TAP ARRANGEMENT



Primary Volts	Connect Lines To	TAP
252	H1-H2	2 TO 3
240	H1-H2	4 TO 5
228	H1-H2	6 TO 7
218	H1-H2	8 TO 9
208	H1-H2	9 TO 10
197	H1-H2	10 TO 11

Secondary Volts	Connect Lines To	Inter-connect
240	X1-X4	X2-X3
120	X1-X4	X1-X3, X2-X4
240/120	X1-X2-X4	X2-X3

LARSON ELECTRONICS LLC • 9419 E US HWY 175 • KEMP, TX 75143
p: 1-800-369-6671 • intl: 903-498-3363 • f: 903-498-3364 • sales@larsonelectronics.com


DANGER PELIGRO




M



Frequently Asked Questions (FAQ)