Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPP-30A-DA-3P-3W4P

30A Explosion Proof Plug - C1D1/2 - 115/230V 3PH 60 Hz - 4P3W - Pin/Sleeve - NEMA 7

Product ID: 153669



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPP-30A-DA-3P-3W4P Explosion Proof Plug
Amp Rating: 30
Dimensions: 4.75"L x 1.6875"D
Configuration: 3-wire, 4-pole
Grommet Range: .875" - 1.125"
Compatibility: EPO-30A-BM-3P-3W4P
Materials: Copper-free Aluminum
Plug Type: Pin and Sleeve
Voltage: 115-230V AC 3PH, 60 Hz
Horsepower: 3HP

Ratings
Class I, Division 1, Groups C, D
Class I, Zones 1 & 2, IIB, IIA
NEMA 7 (C, D)
Special Orders- Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The Larson Electronics EPP-30A-DA-3P-3W4P Explosion Proof Plug ensures secure electrical connections in combustible facilities. This 30-amp pin and sleeve unit is compatible with 115-230V AC three phase 60 Hz. Constructed of copeer-free aluminum, the explosion proof accessory is equipped with a 3-wire, 4-pole configuration.
The EPP-30A-DA-3P-3W4P pin and sleeve plug is compatible with our EPO-30A-BM-3P-3W4P receptacles. This 30-amp unit is approved for Class I, Division 1 and 2, Groups C, D. The explosion proof plug features copper-free aluminum construction and compatibility with 115-230V AC three phase 60 Hz. This 3-wire, 4-pole plug features safety time delay and an extra long grounding pole.
Inter-Compatibility: These plugs are are cross-interchangeable with Appleton Powertite, Crouse Hinds Arktite, and Hubbell-Killark KR series plugs and receptacles. Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Motor-Generator Sets, Compressors, Wet areas or Locations Where Combustible Dust is Present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.


MISTER


MISTRAL
LEGRAND


LARSON
ELECTRONICS
VOLTS
115
230
460
FOR USE WITH COPPER WIRE ONLY
FOR USE WITH KILLARK TYPE
KRJ OR KRS RECEPTACLES
CIR-
CUIT
W
P
CAT
NO.


MISTER

Frequently Asked Questions (FAQ)