Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPSLED-80-110VDC

15W Explosion Proof LED Strobe Light - High Voltage DC - 110V DC - 4Hz Flash Rate - CIDI - IP67

Product ID: 223978



Image: EPSLED-80-110VDC

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPSLED-80-110VDC Explosion Proof LED Strobe Light

Lamp Type: LED
Dimensions: from specs
Weight: 9lbs
Voltage: 110V DC
Total Watts: 15W
Lumens: 2400
Luminous Efficacy: 105 lm/w
Lamp Life Expectancy: 50,000+ Hours
Color: Red, Blue, Green, Amber, Purple or White
Beam Angle: 110º
Lighting Configuration: Strobing Flash
Strobe Count: from specs
Power Efficacy: >95%
Power Factor: >0.9
Amp Draw: 0.08A @ 120V, 0.04A @ 240V, 0.8A @ 12V, 0.4A @ 24V
Ambient Operating Temp Range: -50°C to +65°C
Operating Temp Rating: T3C
Housing Material: Copper Free Cast Aluminum
Housing Finish: Epoxy Powder Coated
Lens Material: Hardened Borosilicate Glass
Mounting: Wall, Pendant, Ceiling, or Stanchion
Wiring Hub: 3/4" NPT (1-1/4" NPT Stanchion)

Ratings/Features

Class I, Divisions 1 & 2, Groups C,D
Class I, Zones 1 & 2, Groups IIB, IIA
Class II, Divisions 1 & 2, Groups E,F,G
Class III, Divisions 1 & 2
NRTL Certified to UL-844
NRTL Certified to UL-1598
NRTL Certified to UL Marine Type
Certified to CSA C22.2 no. 137-M1981
NEMA 3, 4, 4X, 7CD, 9EFG
Suitable for wet locations
Factory Sealed Light Fixture

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Made in Texas

The EPSLED-80-110VDC Explosion Proof LED Strobe Light from Larson Electronics is rated Class 1 Division 1, Groups C, D, paint spray both approved, and produces 4 flashes per second. Water proof and IP67 rated , this LED equipped light is pendant, ceiling, or wall mounted, and available with several color and voltage options.

The powerful and durable EPSLED-80-110VDC explosion proof LED strobe light from Larson Electronics is approved for use in paint spray booths and is ideal for industrial applications, hazardous work spaces, and areas where gases, vapors and dusts may be present and a powerful and durable strobe light solution is needed. The lamp housing is waterproof, constructed of heavy cast aluminum, and NRTL Certified to UL tested to withstand 1490 lbs. per square inch of hydrostatic pressure. Factory sealed and finished in a durable polyester powder coating, this lamp can be ordered with red, blue, green, amber, purple and white flash colors and operates on 110V DC.



Click Photo to Enlarge

This hazardous area strobe light carries a T3C temperature rating and is NRTL Certified to UL Listed Class 1, Groups C and D, Class 2, Groups E and F, and Class III, Groups E, F and G. This strobe light is IP67 rated waterproof and suitable for use in paint spray booths and areas where flammable gases, vapors and chemicals may be encountered as well as approved for exposure to combustible dusts. The cast aluminum housing is fully factory sealed and includes an integrated inspection hole for easy access to the splice compartment. Wiring is through or 3/4" hub.



Bulb Included



Click Photo to Enlarge



Amber Bulb Configuration

The 15 watt LED lamp in this unit offers exceptional power and a 50,000+ hour life span and is energized by leads which pass through sealing compound that separates the lamp chamber from the wiring compartment. The LED lamp assembly is protected by an impact and heat resistant clear prismatic globe with heavy gauge aluminum reflector that affords excellent light control. The LED lamp in this strobe light offers a 50,000+ hour lifespan. The unit shown is pendant mount, and we offer ceiling and wall mount versions as well for added installation versatility.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Wall Mount



Ceiling Mount



Pendant Mount



Stanchion Mount

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Certification

Manufacturer: Larson Electronics LLC
Address: 9419 US-HWY 175
Kemp, Texas 75143

Declare the following equipment conforms to the standard(s) as listed:

Model: EPSL-80-XX-YY
Description: Explosion Proof Jelly Jar Light

Evaluated Listings:

UL: E10514, E91793 – NEC / United States standards
UL: E10514 – CEC / Canada standards
CSA: LR11716 – CEC / Canada standards
ETL: UL 508A, UL 1203 – NEC / United States standards
ETL: CSA C22.2 No. 14, No. 25, No. 30 – CEC / Canada standards

The EPSL-80-XX-YY is certified to NEC and CEC standards for hazardous locations for:

- NEC: Class I, Divisions 1 & 2, Groups C & D; Class II, Divisions 1 & 2, Groups E, F, G
- NEC: Class I, Zones 1 & 2, Groups IIB, IIA
- CEC: Class I, Divisions 1 & 2, Groups C & D; Class II, Divisions 1 & 2, Groups E, F, G
- CEC: Class I, Zones 1 & 2, Groups IIB, IIA

The EPSL-80-XX-YY comprised of a Killark EMI series device enclosure. This device enclosure may contain an incandescent, compact fluorescent, or LED lamp and custom mounting of the lamp assembly to prevent damage. This assembly is built to NEC and CEC standards for hazardous locations and quality checked per ISO 9001:2015 standards.

Signed for and on behalf of: Larson Electronics, LLC
Place of issue: Kemp, TX

Signature: James Thomas

Name: James Thomas
Position: Operations Manager

LARSON ELECTRONICS LLC • 9419 E US HWY 175 • KEMP, TX 75143
p: 1-800-369-6671 • intl: 903-498-3363 • f: 903-498-3364 • sales@larsonelectronics.com

UL Product iQ™

IGIV.E10514 - Luminaire Fittings for Use in Hazardous Locations

Luminaire Fittings for Use in Hazardous Locations

See General Information for Luminaire Fittings for Use in Hazardous Locations

KILLARK, DIV OF HUBBELL INC (DELAWARE) E10514
2112 FENTON LOGISTICS PARK BLVD
FENTON, MO 63026 USA

Trademark and/or Tradename: "E10514" , "Killark/Chalmit"

Class I, Groups A, B, C and D; Class II, Groups E, F and G.

Flexible luminaire fittings: Series EKH, Types EKJH, EKHH, EKGH. Series EKJ, Cat. No. EKJ-1 followed by 4 to 36 incl.; Cat. No. EKJ-2 followed by 4 to 36 incl.

Class I, Groups C and D; Class II, Groups E, F and G.

Luminaire fittings: Series GEC, Cat. Nos. GECCAT, GECCT, GECCTF, GECEAT, GECET, GECLAT, GECLBT, GECLT, GECLTF, GECNT, GECTAT, GECTT, GECTTF, GECUET, GECUWT, GECXAT, GECXT, GECXTF followed by -11, -12, -21, or -22, may be followed by M; Series GEC, Cat. Nos. GECCAT, GECCT, GECCTF, GECEAT, GECET, GECLAT, GECLBT, GECLT, GECLTF, GECNT, GECTAT, GECTT, GECTTF, GECXT, GECXTF followed by -31 or -32, may be followed by M; Series GRCD, Cat. Nos. GRCDC, GRCDE, GRCDL, GRCDT, GRCDX followed by -11, -12, -21, -22, -31, or -32.

Series HXB, Cat. Nos. HXB-11, -12, -21, -22, -31, -32; Series JL, Cat. Nos. JLC, JLE, JLL, JLT,JLX-11, -12, -21, -22; Series JAL, Cat. Nos. JALC, JALE, JALL, JALT, JALX-11, -12, -21, -22, -31, -32; Cat. Nos. SPM, SPH, SPJ or SPI followed by 000001 to 999999 incl., followed by A to Z incl.

Series XFH, Cat. Nos. XFH-21, -22, -31, -32.

Flexible luminaire: Type EKJ, Cat. No. EKJ-3.

Series EZ, Cat. Nos. EZM10, EZS05, EZS07 or EZS10 followed by 0, 1, 2, 3, 4, 5, 6 or 7, followed by A2, A3, B2, B3, X2, X3, followed by G or O, followed by PS.

Class I, Group D; Class II, Groups E, F and G.

Luminaire fittings: Series JAL, Cat. Nos. JALC, JALE, JALL, JALT, JALX-4, -5 with suffixes: SU1, SU2, SU3, SU8, SUP, SU10, SU12, SU14, SU46, L, WL, P or Y.

Cat. No. EZH, EZM or EZS followed by 05, 07, 10, 15, 17, 20, 25 or 40, followed by 0, 1, 2, 3, 4, 5, 6, 7 or 8, followed by D4 or D5, followed by G or O, may be followed by Q, may be followed by BP or R.

Series EZ, Cat. No. EZM10, EZS05, -07 or -10 followed by 0, 1, 2, 3, 4, 5, 6 or 7, followed by D4 or D5, followed by G or O, followed by PS.

Class I, Groups C and D; Class II, Groups E, F and G; Class III.

EZ Series Luminaire Fittings: (+)

Ballast housing assemblies: Cat. No. EZ, followed by M, S or H, followed by 05, 07, 10, 15, 17, 20, 25 or 40, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8 or 9, may be followed by Q, R, BP, PS and/or F#, followed by 1 to 7.

Ballast housing assemblies: Cat. No. EZ followed by P followed by 05, 07, 10, 12, 15, 17, 20, 25, 32, 35 or 40, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8 or 9, may be followed by Q, R, BP, PS and/or F#, followed by 1 to 7 incl.

Luminaire Fitting	Cat. No.
Ballast housing assemblies	Series EZH, EZP, EZM or EZS
Optic assembly	EZGS1 or -2
Splice boxes	EZA2, -3, EZB2, -3, EZX2, -3
Optional accessories	
Angle reflector	VMPA-40
Deep dome reflector	HDR-400
Guards	EZG1, VMAG-40
Standard dome reflector	VMPSD-40

(+) Also Complementary Listed as Miscellaneous Marine Luminaires Fittings (IGZR)

Luminaire fittings: Series EMI followed by 15 or 20, may or may not be followed by ML.

Luminaire Fitting	Cat. No.
Lampholder housings	Series EMI
Optic assembly	EMGS1
Splice boxes	
Ceiling, 3/4 in. conduit	EZX2
Ceiling, 1 in. conduit	EZX3
Pendant, 3/4 in. conduit	EZA2
Pendant, 1 in. conduit	EZA3
Wall mount, 3/4 in. conduit	EZB2
Wall mount, 1 in. conduit	EZB3
Optional accessories	
Angle reflector	ERA-15
Guard	EMG1
Shallow dome reflector	ERSD-15
Angle stanchion, 1-1/4 in. conduit	EZD4
Angle stanchion, 1-1/2 in. conduit	EZD5
Optional accessories	

Angle reflector	ERA-15
Guard	EMG1
Shallow dome reflector	ERSD-15

Luminaire fittings: Series EBF followed by 13 or 26, followed by 1, 4 or 7, may or may not be followed by ML.

Luminaire Fitting	Cat. No.
Lampholder housings	Series EBF
Optic assembly	EMGS1
Splice boxes	
Ceiling, 3/4 in. conduit	EZX2
Ceiling, 1 in. conduit	EZX3
Pendant, 3/4 in. conduit	EZA2
Pendant, 1 in. conduit	EZA3
Wall mount, 3/4 in. conduit	EZB2
Wall mount, 1 in. conduit	EZB3
Optional accessories	
Angle reflector	ERA-15
Guard	EMG1
Shallow dome reflector	ERSD-15
Angle stanchion, 1-1/4 in. conduit	EZD4
Angle stanchion, 1-1/2 in. conduit	EZD5
Optional accessories	
Angle reflector	ERA-15
Guard	EMG1
Shallow dome reflector	ERSD-15

Luminaire fittings: Series EMH, EMI, EMM, EMS followed by 5, 7, 10, 15, 20, 30, 35, 75, may or may not be followed by 0, 1, 2, 3, 4, 5 or 7, may or may not be followed by ML.

Luminaire Fitting	Cat. No.
Luminaire housings	Series EMH, EMI, EMM, EMS
Optic assembly	EMGS3

Splice boxes	
Ceiling, 3/4 in. conduit	EZX2
Ceiling, 1 in. conduit	EZX3
Pendant, 3/4 in. conduit	EZA2
Pendant, 1 in. conduit	EZA3
Wall mount, 3/4 in. conduit	EZB2
Wall mount, 1 in. conduit	EZB3
Optional accessories	
Angle reflector	ERA30
Guard	EMG2
Shallow dome reflector	ERSD30

Luminaire Fitting	Cat. No.
Luminaire housings	Series EMH, EMI, EMM, EMS
Optic assembly	EMGS3
Splice boxes	
Angle stanchion, 1-1/4 in. conduit	EZD4
Angle stanchion, 1-1/2 in. conduit	EZD5
Optional accessories	
Angle reflector	ERA30
Guard	EMG2
Shallow dome reflector	ERSD30

Luminaire fittings: Series EQF followed by 26, 32, 42, 52, 64 or 84 , followed by 30, may be followed by N4, D or A.

Luminaire Fitting	Cat. No.
Lampholder housings	Series EQF
Optic assembly	EMGS1, EMGS3
Splice boxes	
Ceiling, 3/4 in. conduit	EZX2
Ceiling, 1 in. conduit	EZX3

Pendant, 3/4 in. conduit	EZA2
Pendant, 1 in. conduit	EZA3
Wall mount, 3/4 in. conduit	EZB2
Wall mount, 1 in. conduit	EZB3
Optional accessories	
Angle reflector	ERA-15, ERA30
Guard	EMG1
Shallow dome reflector	ERSD-15, ERSD30
Angle stanchion, 1-1/4 in. conduit	EZD4
Angle stanchion, 1-1/2 in. conduit	EZD5
Optional accessories	
Angle reflector	ERA-15
Guard	EMG1, EMG2
Shallow dome reflector	ERSD-15

Class I, Groups C and D.

EZ Series Luminaire Fittings: (+)

Ballast housing assemblies: Cat. No. EZ followed by M, S, or H, followed by 05, 07, 10, 15, 17, 20, 25 or 40, followed by 0 to 9, may be followed by T, R, BP and/or PS.

Ballast housing assemblies: Cat. No. EZ followed by P followed by 05, 07, 10, 12, 15, 17, 20, 25, 32, 35 or 40, followed by 0 to 9, may be followed by T, R, BP and/or PS.

Splice boxes: Cat. Nos. EZD4 or EZD5.

(+) Also Complementary Listed as Miscillaneous Marine Luminaires Fittings (IGZR)

Class I, Division 2, Groups A, B, C and D; Class II, Groups E, F and G.

Ballast tank assemblies: Series VM (E, F, P or V)-0-0-(2, 3, 7, 8, 9, 32 or 35)-(0, 1, 2, 3, 4, 5, 7 or 8)-00, may be followed by NR for use with the following fittings:

Optics: VMER40,VMG-40, VZRG-4050.

Guard: VMAG-40.

Mounting splice boxes: VMA-2, -3, -24, -34, VMB-2, -3, VMC-2, -3, VMX-2, -3.

Reflectors: HRA-500, HRD-400, HRS-500, HRSD-500, VMPA-40, VMPSD-40.

Ballast tank assemblies: Series VMKO, VMLO, VMMO followed by -0, followed by 1, 4, 5, 6, 7 or 9, followed by 00, 10, 20, 30, 40, 50, 60, 70*or 80, may be followed by 1, may be followed by IR, NR, QTZ (Class II) and/or BP and/or KIT followed by 134, 135, 136, 137, 138, 139, 140, 141, 142, 143 or 144 for the use with the following fittings. (Not all combinations are covered for Class II).

Optics - VMG-17, VZRG-1550, VZRG-2550.

Gruards - VMAG-17, VMRWG-8, VMRWG.

Mounting splice boxes - VMA-2, -3, -24 and -34, VMX-2 and -3, VMB-2 and-3, VMC-2 and -3, VMD-4 and -5 (Class I, Div. 2 only with no reflectors), VMDS-5.

Reflectors - VMPA-17 and VMPSD-17.

Ballast tank assembly: Series VBF followed by 13, 26 or 39, followed by 1 or 4. May be followed by F or N4.

Ballast tank assembly: Series VQF followed by 26, 32, 39, 42, 52, 64 or 84, followed by 30. May be followed by F or N4.

Mounting splice boxes: VMA-2, -3, -24 and -34, VMX-2 and -3, VMB-2 and -3, VMC-2 and -3, VMD-4 and -5 (Class I, Div.2 only with no reflectors), VMDS-5.

Optics - Globe: VMG-17.

Guard: VMAG-17.

Reflectors: VMPA-17 and VMPSD-17.

Ballast tank assembly: Series MB for use with the following fittings

Mounting splice boxes: Cat. Nos. MBA-2, -3, MBB-2, -3, MBD-4, -5, MBX-2, -3.

Optics: MBG, VZRG-1550.

Guard: MBAG, VMRGW-8.

Reflectors: VMPA-17, VMPSD-17.

Class I, Groups A, B, C and D, Division 2.

	Cat. No.
Luminaire LED Modules	VTL-1
	VTL-2
Luminaire bodies	VXFC-100-N34
	VXFC-200-N34
Splice boxes	VB-1 or -2
	VBC-1 or -2
	VD-4
	VGA-1 or -2
	VGC-1 or -2
	VGH-1 or -2
	VGX-1 or -2
	VXA-1 or -2
Globes	VAMG-100, -200
	VBG-100 or -200
	VCG-100 or -200
	VCGP-100 or -200
	VGG-100 or -200

	VRG-100 or -200
	VRSG-100
Optional accessories	
Guard	VAG-100 or -200
Reflector	VPRSD-100 or -200
Bracket Mounting Adapter	VFL

Cat. No. VM5S; followed by 60; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, P# (# = 1, 2 or 3), TB, Q# (# = 1 thru 8) or F# (1 thru 8).

Cat. No. VM5H; followed by 25, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, P# (# = 1, 2 or 3), TB, Q# (# = 1 thru 8) or F# (# = 1 thru 8).

Cat. Nos. VM5P or VM5E; followed by 17, 25, 32, 35, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, P# (# = 1, 2 or 3), TB, Q# (# = 1 thru 8) or F# (# = 1 thru 8).

Cat. No. VM5M; followed by 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, P# (# = 1, 2 or 3), TB, Q# (# = 1 thru 8) or F# (# = 1 thru 8).

The VM5 series ballast tank assemblies are intended for use with the following Listed Luminaire Fittings for hazardous locations. Not all combinations are covered.

Optics , Cat. Nos: VMG40, VZRG4050, VZRG4020, VMER40.

External guards , Cat. Nos: VMAG40S, VMRWG, VMERG.

External reflectors, Cat. Nos: VMPSD40, VMPA40, HRD400, HRD400ALZ.

Mounting splice boxes, Cat. Nos: VMA2B, VMA3B, VMF2B, VMF3B, VMX2B, VMX3B, VMX6B, VMX7B, VMX8B, VMX9B, VMB2B, VMB3B, VMC2B, VMC3B, VMD4B, VMD5B, VMS4B, VMS5B, VMB10B, VMB8B, VMB810B.

VM series Luminaire fittings for use in hazardous locations, Class I, Divisions 2, Groups A, B, C and D; Class II, Groups E, F, and G; Class III.

Luminaire fittings:

Optics: VMG17, VMG-17, VMR175, VMR171, VMG25, VMR255, VMR251, VMR253, VZRG1550, VZRG2520, VZRG2550, VMER40, VMEP40.

Guards: VMAG17, VMAG25S, VMRWG, VMRWGS, VMRWG8, VMERG.

Reflectors: VMPSD40, VMPA40.

Mounting Splice Boxes: VMA2B, VMA3B, VMF2B, VMF3B, VMX2B, VMX3B, VMX6B, VMX7B, VMX8B, VMX9B, VMB2B, VMB3B, VMC2B, VMC3B, VMD4B, VMD5B, VMS4B, VMS5B.

Ballast Tank Assemblies: VM1H, VM1P, VM1S, VM2H, VM2P or VM2S followed by 03, 05, 07, 10, 12, 15 or 17, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15, may be followed by IR, NR, BP, P# (1, 2 or 3), TBX (X = 1 thru 9), Q# (1 thru 8) or F# (1 thru 8).

Series VM3S followed by 05, 07, 10 or 15, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM3H followed by 07, 10, 15, 17, or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM3P followed by 12, 15, 17 or 20, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM3M followed by 10, 17, or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM4S followed by 05, 07, 10, or 15, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM4H followed by 07, 10, 15, 17 or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM4P followed by 12, 15, 17, or 20, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM4M followed by 10, 17, or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Ballast Tank Assemblies: Cat. No. VM5S; followed by 25, or 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by NR, BP, TB, Q# (# = 1 thru 8) or F# (1 thru 8).

Cat. No. VM5H; followed by 25, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by NR, BP, TB, Q# (# = 1 thru 8) or F# (# = 1 thru 8).

Cat. Nos. VM5P or VM5E; followed by 17, 25, 32, 35, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by NR, BP, TB, Q# (# = 1 thru 8) or F# (# = 1 thru 8).

Cat. No. VM5M; followed by 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by NR, BP, TB, Q# (# = 1 thru 8) or F# (# = 1 thru 8) + Note:

The VM5 series ballast tank assemblies are intended for use with the following Listed Luminaire Fittings for hazardous locations. Not all combinations are covered.

Optics , Cat. Nos: VMG40, VZRG4050, VZRG4020, VMER40.

External guards , Cat. Nos: VMAG40S, VMRWG, VMERG.

External reflectors , Cat. Nos: VMPSD40, VMPA40, HRD400, HRD400ALZ.

Mounting splice boxes, Cat. Nos: VMA2B, VMA3B, VMF2B, VMF3B, VMX2B, VMX3B, VMX6B, VMX7B, VMX8B, VMX9B, VMB2B, VMB3B, VMC2B, VMC3B, VMD4B, VMD5B, VMS4B, VMS5B, VMB10B, VMB8B, VMB810B.

(Mailing address: P. O. Box 5325, St. Louis, MO 63115)

Last Updated on 2019-09-17

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

UL Product iQ™

IGZR.E91793 - Luminaires, Miscellaneous, Marine

Note: We are enhancing our systems and you may notice missing/outdated data. During this interim period, please refer to your Certificate of Compliance or contact our Customer Service at https://www.ul.com/about/locations.

Luminaires, Miscellaneous, Marine

See General Information for Luminaires, Miscellaneous, Marine

KILLARK, DIV OF HUBBELL INC (DELAWARE) E91793
2112 FENTON LOGISTICS PARK BLVD
FENTON, MO 63026 USA

EBF fluorescent or EMI incandescent Series, Complete unit consists of an assembly of components. The complete unit Cat. No. is as follows: E, followed by MI or BF, followed by 13, 15, 20 or 26, followed by 1, 4, or 7 or a blank followed by ML.

Splice box, Cat. No. EZ followed by A2, A3, X2, X3, B2, B3, D4, D5.

External reflectors, Cat. Nos. ERSD15, ERA15.

Guard, Cat. No. EMG1.

Optic assembly, Cat. No. EMGS1.

EMI incandescent, EMS high pressure sodium, EMM mercury vapor or EMH metal halide series, Complete unit consists of an assembly of components. The complete unit Cat. No. is as follows: E, followed by MI, MS, MM or MH, followed by 35, 05, 07, 75, 10, 15 or 30, followed by 0, 1, 2, 3, 4, 5, or 7 or a blank followed by ML.

Splice box, Cat. No. EZ followed by A2, A3, X2, X3, B2, B3, D4 or D5.

External reflectors, Cat. Nos. ERSD30, ERA30.

Guard, Cat. No. EMG2.

Optic assembly, Cat. No. EMGS3.

VM series Luminaire fittings. +

Optics: VMG17, VMG-17, VMR175, VMR171, VMG25, VMR255, VMR251, VMR253, VZRG1550, VZRG2520, VZRG2550, VMER40, VMEP40.

Guards: VMAG17, VMAG25S, VMRWG, VMRWGS, VMRWG8, VMERG.

Reflectors: VMPSD40, VMPA40.

Mounting Splice Boxes: VMA2B, VMA3B, VMF2B, VMF3B, VMX2B, VMX3B, VMX6B, VMX7B, VMX8B, VMX9B, VMB2B, VMB3B, VMC2B, VMC3B, VMD4B, VMD5B, VMS4B, VMS5B.

Ballast Tank Assemblies: VM1H, VM1P, VM1S, VM2H, VM2P or VM2S followed by 03, 05, 07, 10, 12, 15 or 17, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15, may be followed by IR, NR, BP, P# (1, 2 or 3), TBX (X = 1 thru 9) or Q# (1 thru 8).

Series VM3S followed by 05, 07, 10 or 15, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or3), TB, Q# (1 thru 8), or QA.

Series VM3H followed by 07, 10, 15, 17 or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or3), TB, Q# (1 thru 8), or QA.

Series VM3P followed by 12, 15, 17 or 20, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), or QA.

Series VM3M followed by 10, 17 or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB,

Q# (1 thru 8), or QA.

Series VM4S followed by 05, 07, 10 or 15, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), or QA.

Series VM4H followed by 07, 10, 15, 17 or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), or QA.

Series VM4P followed by 12, 15, 17 or 20, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), or QA.

Series VM4M followed by 10, 17 or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), or QA.

Ballast tank assemblies , Cat. No. VM5S followed by 25, 40 or 60, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by NR, BP, TB or Q.

Cat. No. VM5H followed by 25, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by NR, BP, TB or Q.

Cat. No. VM5P or VM5E followed by 17, 25, 32, 35, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by NR, BP, TB or Q.

Cat. No. VM5M followed by 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by NR, BP, TB or Q.

The ballast tank assemblies are intended for use with the following Listed Fixture Fittings for hazardous locations. Not all combinations are covered.

Optics , Cat. Nos: VMG40, VZRG4050, VZRG4020, VMER40.

External guards , Cat. Nos. VMAG40S, VMRWG, VMERG.

External reflectors , Cat. Nos. VMPSD40, VMPA40, HRD400, HRD400ALZ.

Mounting splice boxes , Cat. Nos. VMA2B, VMA3B, VMF2B, VMF3B, VMX2B, VMX3B, VMX6B, VMX7B, VMX8B, VMX9B, VMB2B, VMB3B, VMC2B, VMC3B, VMD4B, VMD5B, VMS4B, VMS5B.

VM (Old Style) series Luminaire fittings. +

Ballast tank assemblies , Cat. Nos. VMKO, VMLO, VMMO followed by -0, followed by 1, 4, 5, 6, 7, or 9; followed by 00, 10, 20, 30, 40, 50, 60, 70 or 80; may be followed by 1; may be followed by IR, NR, QTZ, and/or BP and/or KIT# followed by 134, 135, 136, 137, 138, 139, 140, 141, 142, 143 or 144.

Optics , Cat. Nos.VMG-17+, VZRG-1550+, VZRG-2550.

External guards , Cat. Nos. VMAG-17+, VMRWG-8+, VMRWG.

External reflectors , Cat. Nos. VMPA-17+, VMPSD-17.

Mounting splice boxes , Cat. Nos. VMA-2, -3, -24, -34, VMX-2, -3, VMB-2, -3, VMC-2, -3, VMD-4, -5, VMDS-5.

MB series Luminaire fittings +

Ballast housings , Series MB, MBF.

Optics , Cat. Nos. MBG, VZRG-1550.

External guards , Cat. Nos. MBAG, VMRWG-8.

External reflectors , Cat. Nos. VMPSD-17, VMPA-17.

Mounting splice boxes , Cat. Nos. MBA-2, MBA-3, MBX-2, MBX-3, MBB-2, MBB-3, MBD-4, MBD-5.

EZ Series Fixture Fittings: (+)

Series EZ followed by M, S, H or P; followed by 05, 07, 10, 12, 15, 17, 20, 25, 32, 35 or 40; followed by 0 to 9; may be followed by Q, PS, R, T and/or BP.

Optic assemblies , Cat. Nos. EZGS1+, EZGS2.

Reflectors , Cat. Nos. VMPSD-40+, VMPA-40+ or HRD-400.

Guards , Cat Nos. EZG1+ or VMAG-40.

+ - Complementary Listing under "Luminaires For Hazardous Locations" (IGIV).

Last Updated on 2012-10-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

UL Product iQ™

IHSN.E10514 - Luminaire Fittings for Use in Zone Classified Hazardous Locations

Luminaire Fittings for Use in Zone Classified Hazardous Locations

See General Information for Luminaire Fittings for Use in Zone Classified Hazardous Locations

KILLARK, DIV OF HUBBELL INC (DELAWARE) E10514
2112 FENTON LOGISTICS PARK BLVD
FENTON, MO 63026 USA
Class I, Zone 1, AEx d IIB.

Series EZM, EZH or EZS followed by 10, 15, 17, 25, 40, 50 or 70, followed by 0, 1, 2, 3, 4, 5, 6, 7 or 8, followed by A2, A3, B2, B3, D4, D5, X2or X3, may be followed by G, PS, BP or R.

Series EMI or EBF followed by 13, 15, 20, 26 or 30, followed by A2, 3, B2, B3, D4, D5, X2 or X3, may be followed by G.

Series EMS, EMM or EMH followed by 35, 05, 07, 75, 10, 15, 13, 26, followed by, followed by 0, 1, 2, 3, 4, 5, 6, 7 or 8, followed by A2, A3, B2, B3, D4, D5, X2 or X3, may be followed by G.

Trademark and/or Tradename: "E10514", "Killark/Chalmit"

Last Updated on 2015-10-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

UL Product iQ™

IGIV7.E10514 - Luminaire Fittings for Use in Hazardous Locations Certified for Canada

Luminaire Fittings for Use in Hazardous Locations Certified for Canada

See General Information for Luminaire Fittings for Use in Hazardous Locations Certified for Canada

KILLARK, DIV OF HUBBELL INC (DELAWARE) E10514
2112 FENTON LOGISTICS PARK BLVD
FENTON, MO 63026 USA
VM series Luminaire fittings for use in hazardous locations, Class I, Divisions 2, Groups A, B, C and D; Class II, Groups E, F, and G; Class III.

Fixture fittings:

Optics: VMG17, VMG-17, VMR175, VMR171, VMG25, VMR255, VMR251, VMR253, VZRG1550, VZRG2520, VZRG2550, VMER40, VMEP40.

Guards: VMAG17, VMAG25S, VMRWG, VMRWGS, VMRWG8, VMERG.

Reflectors: VMPSD40, VMPA40.

Mounting Splice Boxes: VMA2B, VMA3B, VMF2B, VMF3B, VMX2B, VMX3B, VMX6B, VMX7B, VMX8B, VMX9B, VMB2B, VMB3B, VMC2B, VMC3B, VMD4B, VMD5B, VMS4B, VMS5B, VMB10B, VMB8B, VMB810B

Ballast Tank Assemblies: VM1H, VM1P, VM1S, VM2H, VM2P or VM2S followed by 03, 05, 07, 10, 12, 15 or 17, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15, may be followed by IR, NR, BP, P# (1, 2 or 3), TBX (X = 1 thru 9), Q# (1 thru 8) or F# (1 thru 8).

Series VM3S followed by 05, 07, 10 or 15, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM3H followed by 07, 10, 15, 17 or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM3P followed by 12, 15, 17 or 20, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM3M followed by 10, 17 or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM4S followed by 05, 07, 10 or 15, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM4H followed by 07, 10, 15, 17 or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM4P followed by 12, 15, 17 or 20, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Series VM4M followed by 10, 17 or 25, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by IR, NR, BP, P # (1, 2 or 3), TB, Q# (1 thru 8), QA or F# (1 thru 8).

Ballast Tank Assemblies: Cat. No. VM5S; followed by 25, or 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, TB, or Q# (# = 1 thru 8).

Cat. No. VM5H; followed by 25, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, TB, or Q# (# = 1 thru 8).

Cat. Nos. VM5P or VM5E; followed by 17, 25, 32, 35, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, TB, or Q#

(# = 1 thru 8).

Cat. No. VM5M; followed by 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, TB, or Q# (# = 1 thru 8).

The VM5 series ballast tank assemblies are intended for use with the following Listed Fixture Fittings for hazardous locations. Not all combinations are covered.

Optics , Cat. Nos: VMG40, VZRG4050, VZRG4020, VMER40.

External guards , Cat. Nos: VMAG40S, VMRWG, VMERG.

External reflectors , Cat. Nos: VMPSD40, VMPA40, HRD400, HRD400ALZ.

Mounting splice boxes, Cat. Nos: VMA2B, VMA3B, VMF2B, VMF3B, VMX2B, VMX3B, VMX6B, VMX7B, VMX8B, VMX9B, VMB2B, VMB3B, VMC2B, VMC3B, VMD4B, VMD5B, VMS4B, VMS5B, VMB10B, VMB8B, VMB810B.

Class I, Divisions 2, Groups A, B, C and D.

Cat. No. VM5S; followed by 25, 40 or 60; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, P# (# = 1, 2 or 3), TB, or Q# (# = 1 thru 8).

Cat. No. VM5H; followed by 25, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, P# (# = 1, 2 or 3), TB, Q# (# = 1 thru 8).

Cat. Nos. VM5P or VM5E; followed by 17, 25, 32, 35, 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, P# (# = 1, 2 or 3), TB, Q# (# = 1 thru 8).

Cat. No. VM5M; followed by 40; followed by 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 15. May be followed by BP, P# (# = 1, 2 or 3), TB, Q# (# = 1 thru 8).

The VM5 series ballast tank assemblies are intended for use with the following Listed Fixture Fittings for hazardous locations. Not all combinations are covered.

Optics , Cat. Nos: VMG40, VZRG4050, VZRG4020, VMER40.

External guards , Cat. Nos: VMAG40S, VMRWG, VMERG.

External reflectors , Cat. Nos: VMPSD40, VMPA40, HRD400, HRD400ALZ.

Mounting splice boxes, Cat. Nos: VMA2B, VMA3B, VMF2B, VMF3B, VMX2B, VMX3B, VMX6B, VMX7B, VMX8B, VMX9B, VMB2B, VMB3B, VMC2B, VMC3B, VMD4B, VMD5B, VMS4B, VMS5B, VMB10B, VMB8B, VMB810B.

Trademark and/or Tradename: "E10514", "Killark/Chalmit"

Last Updated on 2016-05-31

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Certification Record

Contact an Expert (https://www.csagroup.org/contact/)

CUSTOMER	CLASS	FILE NUMBER
Killark, Div of Hubbell Inc. (Delaware) 2112 Fenton Logistics Park Blvd, Fenton Missouri United States 63026	3428-03 (../class/?class=3428-03) FIXTURES AND FITTINGS-For Hazardous Locations	011713_C_000

Conduction Expert (https://www.csagroup.org/contact/)

Class I, Groups C and D; Class II, Groups E, F and G; Class III;
(Temperature Coded), CSA Encl. 3 and 4 (component packaged):

- Series "HZ" integral ballast with or without aux. quartz lamp 100 or 150W, (for Div 1 only) 480V max, 60Hz, pendent ceiling, bracket, bulk-head or stanchion mount, max 400W high pressure sodium; 250 and 400W mercury vapour or metal halide. Suffix letters and digits following Series "HZ" denote lamp type, wattage, voltage, guard option, mounting, conduit , globe and aux. lamp options.
- Temperature coded as follows: HPS without quartz lamp (T3C), with quartz lamp (T2D). 200 and 400W, MH and MV, without quartz lamp (T3A), with quartz lamp (T2D).

Class I, Groups C and D; Class II, Groups E, F and G; Class III; (Temperature Coded); CSA Encl 3, 4, 4X:
Class I, Division 2, Groups B, C and D; Class II, Division 2, Groups E, F and G; Class III; CSA Encl 3, 4, 4X:

- Series EZ luminaires, mercury vapour (MV), metal halide (MH) or high pressure sodium (HPS) and EZL - LED, 190W max; 50/60 Hz, 480 VAC max or 250VDC max; lamp wattage 400 W max; 60 Hz, 600 V max.

Note: Suffixes letters/numerals denote Lamp Type, Lamp Ratings, Voltage, Mounting and Options.
Temperature coded as follows:

Cat No	Lamp W	Type+	Rated Ambient C	Class I Div. 1 Groups	Suitable For Simultaneous Use In Class Groups C, D and Class II, Groups
*EZS50	50	HPS	40	C,D 120(T4A)	E,F,G 160 (T3C)
EZS50	50	HPS	55	C,D 120(T4A)	E,F,G 160 (T3C)
EZS50	50	HPS	65	C,D 120(T4A)	E,F,G 165 (T3B)
*EZS07	70	HPS	40	C,D 120(T4A)	E,F,G 160 (T3C)
EZS07	70	HPS	55	C,D 120(T4A)	E,F,G 160 (T3C)
EZS07	70	HPS	65	C,D 120(T4A)	E,F,G 165 (T3B)
*EZS10	100	HPS	40	C,D 120(T4A)	E,F,G 160 (T3C)
EZS10	100	HPS	55	C,D 120(T4A)	E,F,G 160 (T3C)
EZS10	100	HPS	65	C,D 120(T4A)	E,F,G 165 (T3B)
EZS15	150	HPS	40	C,D 120(T4A)	E,F,G 160 (T3C)
EZS15	150	HPS	55	C,D 120(T4A)	E,F,G 160 (T3C)

(https://www.csagroup.org/) Testing & Certification Standards About Careers Store Contact English

Contact an Expert

We're always here to help. Let's talk.

We're here to answer your questions and help you get started right away. Call or send us a message anytime.

Contact Us (https://www.csagroup.org/contact)

Contact an Expert (https://www.csagroup.org/contact/)

(https://www.csagroup.org)

FAQs (/faq/)

CSA OnDemand™ (http://store.csagroup.org/ondemand/s/?language=en_US)

Informs & Notices (/informs-notices/)

Submit an Incident Report (/submit-a-report)

Agreement on Acceptance of Components (/agreement-acceptance-components/)

CSA Communities (http://community.csagroup.org/login.jspa?referer=%252Findex.jspa)

Product Alerts & Recalls (/product-alerts-recalls/)

Report Suspect Counterfeit Marks (/testing-certification/marks-labels/brand-protection/reporting-suspect-counterfeit-marks)

Resources & Insights (/resources-insights/)

Standards Research (/standards/standards-research/)

CSA Group Product Listing (/testing-certification/product-listing/)

Sign up for our Newsletter (https://www.csagroup.org/newsletter/)

(http://www.facebook.com/CSAGroup/) (http://www.linkedin.com/company/csa-group/) (http://www.youtube.com/timelines/) (https://www.csagroup.org/standards/)

Legal (https://www.csagroup.org/legal/) Privacy Policy (https://www.csagroup.org/legal/privacy-policy/)

Evidence of Insurance (https://www.csagroup.org/legal/evidence-of-insurance/) HSSE Policy (https://www.csagroup.org/hsse-policy/)

Accreditation (https://www.csagroup.org/accreditation/) Annual Report (https://www.csagroup.org/annual-report/)

© 2020 CSA Group (https://www.csagroup.org)

Certification

Manufacturer: Larson Electronics LLC
Address: 9419 US-HWY 175
Kemp, Texas 75143

Declare the following equipment conforms to the standard(s) as listed:

Model: EPSL-80-XX-YY
Description: Explosion Proof Jellyjar Light

Evaluated Listings:

CE: EN 60598-2-5:2015
CE: EN 62560:2012/AC:2015

The EPSL-80-XX-YY Series complies with the essential protection requirements of the European Parliament of the Council Directive 2014/34/EU on the approximation of the laws of the Member States relating to electrical apparatuses operating within the range of 50-1000 volts AC or 75-1500 volts DC. This certification applies to all specimens manufactured in accordance to the manufactures drawings.

Signed for and on behalf of: Larson Electronics, LLC
Place of issue: Kemp, TX

Signature: James Thomas

Name: James Thomas
Position: Operations Manager

LARSON ELECTRONICS LLC • 9419 E US HWY 175 • KEMP, TX 75143
p: 1-800-369-6671 • intl: 903-498-3363 • f: 903-498-3364 • sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs