

EPS-PB20-2P

20A Explosion Proof Mushroom Push Button Switch - Class I/ II, Division 1 & 2 - 120V AC - 2P

Product ID: 243867



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPS-PB20-2P Explosion Proof Switch

Listing: NRTL Listed for United States and Canada

Dimensions: -

Weight: -

Voltage: 120V AC, 60Hz

Poles: 2P

Amps: 20A

Switch Configuration: NO or NC

Operating Temperature: -20° to 40°C

Materials: Copper-free Aluminum, Stainless Steel Screws

Finish: Aluminum Acrylic Paint

Mount: Surface

Wiring Configuration: Dead End or Feed Thru

Hub Size Options: 1/2" or 3/4"

Ratings

Class I, Divisions 1&2 Groups C,D

Class II, Divisions 1&2 Groups E,F,G

Class III

NEMA 3, 7

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics EPS-PB20-2P Explosion Proof Push Button Switch is designed for use in hazardous work areas, such as chemical plants, oil refineries and settings where combustible gases or dust may be present. This 20-amp device features the following explosion proof ratings: Class I, Division 1 & 2, Class II, Division 1 & 2 and Class III. In industrial and commercial settings, the front-operated push button switch may be used to support basic features of machines lacking electrical circuits for control. When ordering this 2-pole unit, buyers may choose from 1/2" and 3/4", dead-end and feed-thru options.

The EPS-PB20-2P is rated for 20 amps at 120V AC, 60 Hz. This explosion proof push button comes in a switch configuration of normally open or normally closed. The 2-pole device supports operating temperatures between -20° to 40°C. It is enclosed in a separate sealing chamber, and the sealing chamber has smooth, double flanges that mate both to the cover and the mounting enclosure to provide flame tight joints.



[Click Photo to Enlarge](#)




[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



On this unit, the screws consist of stainless steel captive screws and attach the sealing chamber to cover and mounting enclosure. The side rocker arm push button has lockout holes, and the switch is supplied with an internal ground screw. Its housing is constructed of copper-free aluminum, finished with aluminum acrylic paint. With the robust protruding button design, workers using thick gloves may find the device easier to activate, compared to a traditional push button switch design.



Hubs: This device features 1/2" and 3/4", as well as dead-end and feed-thru options. Both options come with Class I, Divisions 1 & 2 (Groups C and D), Class II, Divisions 1 & 2 (Groups E, F and G) and Class III explosion proof ratings.

Mounting: The EPS-PB20-2P is compatible with surface mounting requirements. Two mounting holes at the back of the unit can be used to secure the switch during installation.


At Larson Electronics, we do more than meet your lighting needs. We also provide

replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.









LARSON
ELECTRONICS®
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com

Frequently Asked Questions (FAQ)