

XLE-PA-IP67-309.NA-3PH-20A-480Y.277-4P5W-B

IEC 60309 Waterproof Inlet, 20 Amps 3P+N+E, 480/277V 3PH 4P5W, Pin & Sleeve, IP67

Product ID: 263536



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

XLE-PA-IP67-309.NA-3PH-20A-480Y.277-4P5W-B Water Tight Pin and Sleeve Connector

Device Series: IEC 60309 (North American Standard)

Device Type: Inlet

Dimensions: -

Weight: -

Amperage Rating: 20A

Voltage: 480/277

Frequency: 50/60 Hz

Phase: 3-Phase Wye

Configuration: 4P5W (3P+N+E)

of Poles: 4-Pole

of Wires: 5-Wire

Max Voltage Rating: 480V 3PH

Clock Hour: 7H

Cord Range: .350 - .860

Dielectric Voltage: 2000V for 1 min

of Operations: > 5000 connects/disconnects under load, at full rated current and voltage

Minimum Withdrawal Force: 5lbs

Temperature Rise: Max +30°C at full-rated current after 50 cycles of OL at 150% rated current

Operating Temperature Range: -25°C to +65°C

Waterproof Rating: IP67, IP69K, NEMA 4X

Shock Resistance: IK09

Flammability: V-2 Rated

Certifications - Compliance

Certified for United States & Canada

NRTL Certified to UL 1682, UL 1686

NRTL Certified to CAN/CSA C22.2 No 182.1

CE Certified, Low Voltage Directive 73/23/EEC

CE Certified, Low Voltage Directive 93/68/EEC

NRTL Certified to 60309-1, 60309-2

RoHS Certified

Compatible with IEC 60309 Compliant Products

IP67/IP69K Rated Weatherproof

IK07 Rated Drop Resistant

Flame Retardant (UL94 V2)

Certified for Full Load Interrupting

Current Interrupting: Certified for current interrupting at full rated current

Corrosion Resistance: Ferrous parts immersed in 20°C, 10 percent ammonium chloride solution for 10 min

Flammability: Rated V-2 per UL 94

Ingress Protection Rating: IP67/IP69K

Moisture Resistance: Immersed for 24 hours in 5cm of 25°C water per UL 1682

Crush Test: 250lbs for 1 min after -25°C for 6 hrs

Impact Resistance: Drop from 30" 8 times after conditioning to -25°C for 6 hrs

Cross Compatible: 520B7W

Mating Plug: XLE-PA-IP67-309.NA-3PH-20A-480Y.277-4P5W-P

Mating Receptacle: XLE-PA-IP67-309.NA-3PH-20A-

Insulation Resistance: 500V for 1 min; $\geq 5M$

Cable Secureness: "Force: 30lb; Torque: 0.4 ft-lb; Max Disp: $\leq 3/32$ "

Seals: Neoprene

Material, Housing Body: Toughened PVC

Material, Housing Cover: Toughened PVC

Material, Contacts: Brass

Material, Contact Carrier: Nylon

Material, External Screws: Acid-Proof Stainless Steel

Material, Internal Screws: Zinc-plated steel

Material, Phase/Ground Sleeves: Brass

Material, Sleeve Spring: Stainless Steel

Material, Terminal Screws: Steel

Color: Red

Shipping Dimensions: -

Shipping Weight: -

480Y.277-4P5W-R

Mating Connector: XLE-PA-IP67-309.NA-3PH-20A-480Y.277-4P5W-C

Mating Inlet: XLE-PA-IP67-309.NA-3PH-20A-480Y.277-4P5W-B

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics XLE-PA-IP67-309.NA-3PH-20A-480Y.277-4P5W-B is an IEC 60309 standard industrial use waterproof Inlet for industrial work sites. The 20-amp pin/sleeve Inlet is configured to operate on 3-Phase Wye 480/277V AC power and features an IP67 waterproof rating. Designed for rugged facilities, the %Pole%-pole %Wire%-wire unit can be disconnected under load up to 5000? times.

The XLE-PA-IP67-309.NA-3PH-20A-480Y.277-4P5W-B is an industrial grade Inlet with waterproof properties. This pin/sleeve unit is compatible with 3-Phase Wye 480/277V and holds a 20-amp rating. The IP67-rated Inlet is constructed of toughened PVC, reinforced thermoplastic polyester and stainless steel.

The XLE-PA-IP67-309.NA series from Larson Electronics complies with the IEC 60309 standard for North American equipment, is a direct cross for 520B7W , and is cross compatible with other equipment designed to the same standard. The XLE-PA-IP67-309.NA-3PH-20A-480Y.277-4P5W-B is a Red Inlet with a grounding pin located at clock hour 7.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)