

EXPCMR-IP-POE-DPTZ-24V

6MP Explosion Proof Digital Pan Tilt Zoom Security Camera - 360° Coverage - PTZ - Day/Night - C1D1

Product ID: 265055



Image: EXPCMR-IP-POE-DPTZ-24V

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXPCMR-IP-POE-DPTZ-24V Explosion Proof Digital PTZ

Unit Type: Explosion Proof Camera

Dimensions: 7.44"D x 11"W x 14.53"H

Camera Weight: 27 lbs

Total Watts: 12W Max

Voltage: 24V DC

PoE: 802.3af

Image Sensor: Progressive Scan CMOS

Camera Resolution: 3072 x 2048

Megapixel: 6

Compression Type: H.264, MJPEG

Frame Rate: High-frame Mode- 1 Fisheye 25fps @ 2048 x 1536, 30fps @ 2048 x 2048, 4x

ePTZ 30fps @ 1024 x 768; Multi-channel Mode- 1 x Fisheye 15fps @ 1280 x 1280, 1x

Panoramic 15fps @ 2048 x 1536, 3x ePTZ 15fps @ 1024 x 768

Day/Night Function: True D/N w/Mechanical Cut Filter

IR Wavelength/Range: 850 nm/49 Feet

Relative Aperture (F-stop): 2.8

FOV (Degrees): 360

Audio Compression: 64Kbps (G.711)/16Kbps (G.726)/MP2L2

Audio Streaming: Two-way Audio Streaming w/ Built-in Mic

Ethernet Interface: RJ-45

Ethernet Ports/Speed: 1, 10/100

Networking Protocols: TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP

Recording: Email Notification, Event Log, Event Notification, Event Search, Motion Detection, Pre/Post Alarm Recording, Privacy Video Block, Video Analytics Capable

Storage Capacity: 64 GB max via SD card slot

Quick Summary

Class I, Div. 1 & 2, Groups B, C, D

Class I, Zones 1 & 2, Groups IIB+H2, IIA

Class II, Div. 1 & 2, Groups E, F, G

Class III, Div. 1 & 2

NEMA 3, 4, 4X, 7 (B, C, D), 9 (E, F, G)

ATEX/IEC Ex

Ex d IIC T6 or T5

64 GB Storage

Day/Night Operation

Connectors: Sensor Inputs (1), Alarm Output (1), Audio In (1), Audio Out (1)

Ambient Temperature Range: -22°F ~ 140°F

Material: Copper-free Aluminum

Finish: Electrostatically Applied Powder Epoxy/Polyester Finish

Lens Cover Material: Tempered Soda Lime Glass

Wiring Hub: (2) 3/4" - 14 NPT Drilled and Tapped Conduit Openings

Mount: Flat Surface/Trunnion Mount

Shipping Weight: 30 lbs

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

The EXPCMR-IP-POE-DPTZ-24V Explosion Proof Digital Pan Tilt Zoom Camera from Larson Electronics is designed for security and remote observation in both indoor and outdoor hazardous environments. This high resolution day/night camera features 64GB internal storage. The security device comes with the following explosion proof ratings: Class I, Div. 1 & 2, Groups B, C, D; Class I, Zone 1 and Class II, Div. 1 & 2, Groups E, F, G. Constructed of heavy duty aluminum, the unit supports 360° fisheye panoramic surround views and up to five independent camera views at once on-screen.

Camera Features: The EXPCMR-IP-POE-DPTZ-24V digital PTZ camera provides operators in hazardous areas with crisp high resolution images. Equipped with a 1.27 mm optical lens, this 12W unit produces up to 6.0 megapixel (3072 x 2048) resolution while operating at 24V DC. Operators may choose from the following viewing modes: fisheye, horizontal panoramic and ePTZ quad view. A 360° fisheye panoramic surround view offers wider coverage and eliminates blind spots, while a 180° panoramic view provides end-to-end horizontal coverage.

This device features two-way audio using a built-in speaker and microphone. The EXPCMR-IP-POE-DPTZ-24V security camera is designed to perform under harsh and rugged conditions. For use in extreme environments, the IP66 rated waterproof unit resists the corrosive effects of weather, dust, dirt, and humidity. With a copper-free aluminum housing, the camera is capable of operating in hazardous locations with temperatures ranging between -22°F and 140°F, as well as 0% to 95% non-condensing, humid environments.

Mounting/Wiring: The EXPCMR-IP-POE-DPTZ-24V can be mounted on flat surfaces via an adjustable trunnion mount. This unit is designed to operate on 24V DC, consuming a maximum of 12W per system. Two 3/4" - 14 NPT drilled and tapped conduit openings (one top and one bottom) are available for wiring.

Our explosion proof cameras with Power over Ethernet (PoE) features enable data transfers and power to be passed through a single Ethernet cable that is usually a Cat 3/Cat 5 cable or better. There are several types of PoE, which come with their own respective standard and maximum power to port capabilities. The IEEE 802.3af PoE standard, with a voltage range of 44.0 - 57.0V, offers 15.4W of DC power for each port. The IEEE 802.3at PoE standard, with a voltage range of 50.0 - 57.0V, provides up to 30W of DC power per port, which is ideal for surveillance cameras, antennas and network access points. The IEEE 802.3bt PoE standard, with a voltage range of 50.0 - 57.0V, provides 60W of DC power for each port. In order to utilize PoE properly, the components, such as the receiving unit and sending device, must be PoE compliant.

Applications: Vessel, tank and reactor monitoring, remote observation of external facilities, offshore and land based rigs, indoor and outdoor security, commercial buildings, service garages, oil refineries and other applicable hazardous locations.




At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

	8	7	6	5	4	3	2	1
	REV	DESCRIPTION						DATE
	A	PRODUCTION RELEASE						12/28/2021
EXPCMR-IP-POE-DPTZ-24V 								
	8	7	6	5	4	3	2	1

EXPCMR-IP-POE-DPTZ-24V






TAGS	QTY	CATALOG	DESCRIPTION
DV1-101.06A	1	UNV00004231	6.0 MP IR Panoramic Fisheye Vandal
DV1-101.06	1	UNV00002067	24V TO 12V 10A POWER SUPPLY



**LARSON
ELECTRONICS**

9419 E US HWY 175,
KEMP, TX 75143

TITLE EXPCMR-IP-POE-DPTZ-24V		
DRAWN BY R.BLACK	DATE 12/28/2021	REV A
CHECKED BY A. CIBISOVS	SHEET # 1 OF 1	DRAWING # 101



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
LARSON ELECTRONICS LLC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
LARSON ELECTRONICS LLC IS
PROHIBITED.

DIMENSIONS ARE IN INCHES		DATE		7/3/2026		SCALE: NTS		SHEET 1 OF 1	
DO NOT SCALE DRAWING		DATE		7/3/2026		SCALE: NTS		SHEET 1 OF 1	



PART NUMBER:
**EXPCMR-IP-POE-
DPTZ-24V**

SIZE
A

REV
1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Frequently Asked Questions (FAQ)

There are no Faqs