

EPCS-PB10-2XPL.GR-1XMPB-N4X-M1

10A Explosion Proof Push Button w/ LED Pilot Lights - Class I, II, III - (2) 10A LED PLs - Momentary PB

Product ID: 265683



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPCS-PB10-2XPL.GR-1XMPB-N4X-M1 Explosion Proof Control Station

Listing: NRTL Listed for United States, Canada

Unit Type: Explosion Proof Push Button w/ LED Pilot Lights

Dimensions: 13.08" x 8.14" x 9.82"

Weight: -

LED Pilot Lights: (1) Red, (1) Green

Pilot Light Voltage: 120V, 240V, 12V or 24V

Push Button Type: Momentary, Black

PB Contacts: (1) NO, (1) NC- 10A Rated

Material: Copper Free Aluminum

Mount: Surface

Configuration: Dead End or Feed Through

Hub Size: 1/2" NPT or 3/4" NPT

Ratings/Approvals

Class I, Divisions 1 & 2, Groups C, D

Class II, Division 1, Groups E, F & G

Class III

NEMA 3R, 4, 4X, 7 (C, D), 9 (E, F, G)

NRTL Listed to UL 508A, UL 1203

NRTL Listed to CSA C22.2 No 14, 25, 30

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics EPCS-PB10-2XPL.GR-1XMPB-N4X-M1 Explosion Proof Control Station is suitable for use in Class I, II and III rated combustible sites. This weatherproof unit contains three operators: (2) pilot lights and (1) push button. Protected by a copper-free aluminum enclosure, the control device is offered with 1/2" or 3/4" hub size.

The EPCS-PB10-2XPL.GR-1XMPB-N4X-M1 is recommended for motor or equipment control in flammable facilities. The unit contains two LED pilot lights (green and red) and one push button. Voltage options for the pilot lights include: 120V, 240V, 12V or 24V. The momentary, black push button is equipped with one NO and one NC contacts, which are rated at 10 amps. The NEMA-rated device is constructed of copper-free aluminum. The EPCS-PB10-2XPL.GR-1XMPB-N4X-M1 comes with

stainless steel captive screws for the cover assembly.

Hubs: The explosion proof device is offered with 1/2" NPT or 3/4" NPT hub size and in dead end or feed through configuration for completing wiring connections.

Mount: The EPCS-PB10-2XPL.GR-1XMPB-N4X-M1 is compatible with surface mounting applications.

Applications: Starters, remote control of motors, chemical processing plants, food processing facilities, oil refineries and other hazardous locations applicable to the unit's classified ratings.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)