Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EXP-CTR-3P-12A-480V-120VC-2X0.75NS

12A Explosion Proof Contactor - C1D1, C2D1 - 3P - (2) 3/4" NPT Hubs, N/S - 480V - ATEX/IECEX Rated - 120VDC Coil

Product ID: 267142



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXP-CTR-3P-12A-480V-120VC-2X0.75NS Explosion Proof Contactor
Device Type: Explosion Proof Contactor
External Dimensions: 9.13" x 9.63" x 7.18"
Weight: -
Voltage: 480V AC 50/60 Hz
Coil Voltage: 120V DC
Amps: 12A
Poles: 3
Configuration: NO or NC
Material: Copper-free Aluminum
Enclosure Finish: Electrostatically Applied Powder Epoxy/Polyester Finish
Mount: Surface
Wiring: Contactors - Lugs
Hubs: (2) 3/4" NPT Hubs - (1) North, (1) South
Access Hole OD: 5.38"

Ratings/Approvals
Listed for United States, Canada, Europe, Asia
Class I, Div. 1 & 2, Groups B, C, D
Class I, Zones 1 & 2, Groups IIB+H2, IIA
Class II, Div. 1 & 2, Groups E, F, G
Class III, Div. 1 & 2
ATEX/IEC Ex
Ex d IIC T6 or T5
Ex tD A21 IP66 T80°C or T90°C IP66
Ta = -20°C to +60°C
NEMA Type 3, 4, 4X, 7 (B,C,D), 9 (E,F,G)

Special Orders- Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The EXP-CTR-3P-12A-480V-120VC-2X0.75NS from Larson Electronics is an Explosion Proof Contactor for secure connections to circuits and motors in ATEX-rated and combustible sites. This 12-amp device is compatible with 480V AC 50/60 Hz and features an NO configuration. Operators are provided access to two 3/4" NPT hubs at the north and south sides of the explosion proof, 3-pole unit. This unit has a 120 VDC

coil.
The EXP-CTR-3P-12A-480V-120VC-2X0.75NS faciliates electrical connections in flammable environments. This 12-amp, 3-pole unit operates on 480V AC 50/60 Hz and is activated via a 120V control coil. Equipped with an NO configuration, the explosion proof contactor features lugs for secure connections.Two, 3/4" NPT hubs are available on the north and south sides (1 per side) of the ATEX rated device. Constructed of copper-free aluminum with an electrostatically applied powder epoxy/polyester finish, this explosion proof contactor is rated NEMA Type 3, 4, 4X, 7 (B,C,D) and 9 (E,F,G) and designed to withstand the rigors of demanding environmental and operating conditions while remaining robust and easy to use.
Applications: Hazardous locations, HVAC systems, industrial motors, compressors, chemical processing, welding, heating equipment, manufacturing sites and more.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.






CAUTION
LARSEN


LARSON
ELECTRONICS
LARSONELECTRONICS.COM
877-875-2747
sales@larsonelectronics.com
EXP-CTR-3P-30A-230V-230.75NS-NC

Frequently Asked Questions (FAQ)