Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

HAL-12-IPS-LED-UVA-DP

10 Watt Low Profile Ultraviolet LED Light - Low Voltage UVA Linear - Class 1 Division 2 - 1' Strip - Line-In Deutsch Connector

Product ID: 268874



Image: HAL-12-IPS-LED-UVA-DP

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-12-IPS-LED-UVA-DP Hazardous Location LED Lighting
Lamp Type: UV LED
Dimensions: 13.9"L x 2.69"W x 1.84"D
Weight: 0.7 lb
Voltage: 11-25 Volts AC/DC
Watts: 10
Voltage: 12 or 24 V DC
Total Intensity: 3,500 mW/cm2
Radiant Efficacy: 350 mW/w
Lamp Life Expectancy: 50,000 Hours
Amps: 3.34 A @12 V DC - 1.67 A @ 24 V DC
Light Color: 365NM - Ultraviolet
Beam Angle: 100°
Lighting Configuration: Flood Pattern
Power Efficiency: >95%
Power Factor: 0.992
Amperage: 3.34 A @ 12 V DC - 1.67 A @ 24 V DC
Ambient Operating Temp Range:-40°C to +65°C
Operating Temp Rating: T3
Housing Material: Extruded Aluminum
Housing Finish: Powder Coated - Black
Lens Material: Polycarbonate
Gasket Material: Silicone
Mounting: Adjustable Swivel Mount Surface Bracket
Wiring: 6' 16/2 SOOW w/ Male Deutsch Connector

Listings/Ratings
NRTL Listed for United States and Canada
Class I, Division 2, Groups A, B, C, D
NRTL Certified to UL 844
NRTL Certified to UL 1598
IP65 Ingress Protection
T3 Temperature Rating
70% Radiant Retention after 50,000 Hours
Factory Sealed Light Fixture

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

Buy American Compliant

The Larson Electronics HAL-12-IPS-LED-UVA-DP is a low voltage ultraviolet hazardous location lighting solution approved for Class I Division 2 environments and UL 1598 listed for use in wet locations. This powerful 13.90" long LED strip light produces 3,500 mW radiant intensity, operates on 12 or 24 V DC, and is suitable for hazardous locations where UV lamps are used in paint and adhesive curing, food inspection, or for non-destructive testing, as well as food processing, vision systems, and automation systems.

The HAL-12-IPS-LED-UVA-DP is designed to provide a high output and ruggedly durable lighting solution for applications where ultraviolet light is needed and Class I Division 2 compliance is required. This low voltage hazardous location UV light emits light in the ultraviolet spectrum. This 365NM strip light can be operated on either 12 or 24 volt DC current and includes 6 feet of connecting lead terminated with a DT06-2S male Deutsch connector. The housing is constructed of powder coated extruded aluminum for excellent strength and durability and is rated IP65 for protection against exposure to splashing water and limited dust ingress. These units are configured in a 13.90" long strip or "bar" profile for installation in locations where wide dispersal and a low profile is preferred. The high output, cool running operation, and good color rendering properties of this light make it an ideal replacement for older, bulkier, and less reliable HID and halogen light fixtures.

The HAL-12-IPS-LED-UVA-DP uses LED light technology, a technology that is far better in energy saving than traditional fluorescent bulbs used for the same purposes. Traditional ultraviolet lights require a coating to block out visible light or a special composition of gases and chemicals used to create a higher concentration of ultraviolet light. This process, however, also produces many other wavelengths of light which go unused and end up as wasted energy. LED lights are unique in that they have a narrower wavelength band than traditional ultraviolet sources and therefore do not require these special coatings. As a result, LED lights do not produce unused, wasted light and therefore consume less energy than traditional UV lights on the market. LED lights have the added benefit of being capable of producing very specific wavelengths with tighter curves and are more durable and lightweight as well.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

This Class I, Division 2 LED ultraviolet light fixture can be used for non-destructive testing in aviation and manufacturing, food processing and inspection, and in paint, coating, and adhesive curing. The HAL-12-IPS-LED-UVA-DP provides operators in hazardous locations with a reliable and durable UV lighting solution that combines effective production of UV light with explosion proof protection and is applicable for leak detection, vision systems, automation systems, paint spray booths, ink, coatings, and adhesive curing, non-destructive testing, inspection, and food processing.

Ultraviolet Wavelength: Ultraviolet A Wavelength produces a longer wave between the 400nm - 315nm spectrum. This explosion proof LED light has a peak wavelength of 365NM.

Durability: The HAL-12-IPS-LED-UVA-DP hazardous location LED light is constructed of extruded aluminum with a tough powder coat finish for high strength and durability. The housing is IP65 rated, providing limited ingress protection against dusts, and basic protection against splashing water such as rain. This design is weather resistant, suitable for indoor or outdoor applications, and ideal for areas where wetness or dusty conditions are commonly encountered.

Mounting: Mounting for this unit is provided by two standard adjustable end brackets that allow operators to mount the light to flat surfaces and then adjust the light 170° vertically for the best placement. The entire assembly weighs 0.7 lbs and measures 13.9 inches in length, and 2.69 inches wide and 1.84 inches deep, making it ideal for mounting in areas where space is limited and a low profile fixture more readily installed.

Wiring/Power: This light is universal voltage capable and operates on AC/DC voltages from 11-25 Volts. Each strip light is equipped with 6 feet of 16/3 SOOW cable terminated with a DT06-2S male Deutsch connector for making power connections.

Versatility: The HAL-12-IPS-LED-UVA-DP is ETL approved for Class I Division 2 groups A, B, C and D locations. This unit carries an IP65 water resistant rating ensuring protection against limited ingress from dusts, dirt, and basic protection against light water spray landing directly on the fixture. This light is ideal for indoor or outdoor applications and industrial operations with hazardous location classification where dusty or wet conditions are commonly encountered.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs