

HALD-CLS-1X150LED

Low Profile Explosion Proof LED Light - Class I, II - Corner Mount - Paint Spray Booth Rated
Product ID: 270944



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HALD-CLS-1X150LED HAZLOC Corner Mount Light

Listing: NRTL Listed for United States and Canada

Lamp Technology: Cree LED

Dimensions: -

Weight: 40 lbs

Voltage: 100-277 Volts AC, 50/60Hz or 11-25 Volts AC/DC

Total Watts: 150W

Lumens: 21,000

Luminous Efficacy: 140 Lm/W

Lamp Life: 60,000+ Hours

Color Temp: 5600K, 5000K, 4500K, 4000K, 3500K, 3000K, 2700K, or 6500K

Color Rendering Index: >75 CRI

Lamp Type: -

Lamp Base: -

Replacement Lamp: -

Beam Angle: 60°, 125°, or 140°

Lighting Configuration: Flood Pattern

Power Efficiency: >95%

Power Factor: 0.992

Ambient Operating Temp Range: -50° C to +65°C

Operating Temp Rating: T5

Housing Material: Copper Free Cast Aluminum

Housing Finish: Powder Coated - White

Lens Material: Polycarbonate

Mounting: Wall-to-Ceiling Corner Mount

Wiring: 10` 16/3 SOOW w/ Flying Leads

Wiring Hub: 3/4" NPT

Ratings/Features

Class I, Divisions 1 & 2, Groups C and D

Class II, Divisions 1 & 2, Groups E,F,G

Certified to UL 844 Ed. 13

Certified to UL 1598

Certified to C22.2 No. 137 Rev 2009

Certified to C22.2 No. 250.0

Certified to C22.2 No. 30-M-1986 Rev 2012

T5 Temperature Rating

Paint Spray Booth Approved

IEC 60529 Tested

IP67 Rated Waterproof

LEL Approved

Multiple Driver Banks

80% Lumen Retention after 60,000 Hours

Factory Sealed Light Fixture

3.5kV Surge Protection (NTC Circuit)

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics HALD-CLS-1X150LED Hazardous Area LED Light Fixture is designed to provide operators with a powerful and energy efficient alternative to traditional hazardous location luminaries. This LED fixture is NRTL listed Class I, Divisions 1 & 2 and Class II, Divisions 1 & 2 and approved for use within paint spray booths. Cree LED technology and compact design makes this lamp an excellent replacement upgrade option for paint booths and hazardous locations where flammable chemical/petrochemical vapors are present.

*****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS HAZARDOUS LOCATION LIGHT FIXTURE*****

The HALD-CLS-1X150LED is ideal for use in paint spray booths and hazardous environments where space for lighting fixtures is limited. Designed for wall-to-ceiling corner mount applications, this fixture is T5 temperature rated and is a fully integrated LED unit. The LED assembly is protected by an aluminum framed, 3/16" thick polycarbonate lens that provides direct front access to the internal components.

This Class I, Division 1 & 2 and Class II, Division 1 & 2 explosion proof light fixture provides 21,000 lumens of high quality light while drawing only 150 watts. The copper free aluminum alloy body is powder coated for added durability and an attractive aesthetic appearance. A special heat dissipating design in conjunction with LED technology helps this fixture to achieve an excellent 60,000 hour rated lifespan with 80% lumen retention. Light weight and a low profile make this unit an attractive alternative to larger and heavier older fixtures and requires less hardware to install.

The integrated LED assembly in this unit features multiple LED drivers which helps to increase the operational life of the fixture. With traditional LED lights, in the event an LED array or driver fails, the entire fixture no longer illuminates. This new series of LED lamps contains twenty-four individual LED boards configured in a series of banks. Each bank contains two LED boards with an individual driver. In the event of a driver failure, only one bank of LEDs will be effected while the other banks will continue to operate. In the event that of an LED failure, the mating LED will continue to operate.

Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current applied and emitting light. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than traditional lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state design of light emitting diodes provides a more reliable, stable, durable, and energy efficient light source over traditional lighting.

This light is multi-voltage capable and can be operated with 100-277V AC, 50/60Hz without any need for a special ballast. The aluminum body and LED lamp give this light excellent durability and resistance to vibration and impacts. The housing is specially designed to dissipate heat which increases the efficiency and lifespan of the LED luminaries. The LED lamp produces 21,000 lumens with a color temperature of 5000K, 4000K, or 3000K and a color rendering index of 75 which produces colors and details much more accurately than high pressure sodium or mercury vapor luminaries.

Mounting: The HALD-CLS-1X150LED is compatible with wall-to-ceiling corner mounting installations. This mounting solution enables the angled lighting system to be installed in corners without a compatible angled ceiling. When properly mounted, the explosion proof light provides a 45-degree angle from the ground.


Applications: Paint spray booths and enclosed spaces where flammable chemical/petrochemical vapors are present.

At Larson Electronics, we do more than meet your lighting needs. We also provide



replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

	8	7	6	5	4	3	2	1
	REV	DESCRIPTION						DATE
	A	PRODUCTION RELEASE						1/20/2025
HALD-CLS-1X150LED-1227-125B-56K 								
	8	7	6	5	4	3	2	1




TAGS	QTY	CATALOG	DESCRIPTION
LT1-101.14	1	UNV00007989	150W 120-277V 125DB 5K HIGH BAY LED LIGHT SPONGEBOB
CBL1-101.10	1	UNV00009083	CORD 16/3 SOOW UL 90C BLK CABLE

 LARSON ELECTRONICS 9419 E US HWY 175, KEMP, TX 75143	TITLE HALD-CLS-1X150LED-1227-125B-56K		
	DRAWN BY S.DESAI	DATE 1/20/2025	REV A
	CHECKED BY	SHEET # 1 OF 1	DRAWING # 101









Frequently Asked Questions (FAQ)