Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EXPCMR-IP-POE-OZ-6MP-27D-88D

6MP Explosion Proof HD Security Camera - C1D1, C2D1 - 27° to 88° FOV - PoE/IP67

Product ID: 278389



Image: EXPCMR-IP-POE-OZ-6MP-27D-88D

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXPCMR-IP-POE-OZ-6MP-27D-88D Explosion Proof Remote Observation Camera

Listing: NRTL Listed for United States & Canada
Dimensions: 12.34"L x 3.96"W x 4.22"H
Camera Weight: -
Total Watts: 17W PoE (802.3at), max. 19W
Voltage: 12V DC ± 25%
Image Sensor: Progressive Scan CMOS
Imager Size: 1/2.9
Color: Yes
Effective Pixels/Resolution: 3072(H) * 2048(V)
Megapixels: 6MP
Lux: 0 (B/W), 0.01 (Color)
AGC Control: OSD Selectable
Relative Aperture (F-stop): F1.2
FOV: 88° ~ 27°
Focus: Auto
Lens Type: Motorized Varifocal
Lens: 2.8-12mm Focal Length
Day/Night: True D/N w/Mechanical Cut Filter
Infrared Light: Built-in - 850nm
Infrared Light Distance: 170'
Digital Noise Reduction: 3D DNR
Dynamic Range: 120 dB
Frame Rate: Selectable
Video Output: (1)
Ethernet Ports/Speed: 1; 10/100

Ratings / Features

Class I, Divisions 1 & 2, Groups B, C, D
Class I, Zones 1 & 2, Groups IIB+H2, IIA
Class II, Divisions 1 & 2, Groups E, F, G
Class III, Divisions 1 & 2
NEMA 3R, 4, 7 (B, C, D), 9 (E, F, G)
NRTL Listed to UL 508A
NRTL Listed to UL 1203
NRTL Listed to CSA C22.2 No 14, 25, 30
Seamless Power (PoE)

Audio: Yes
Protocols: TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more
Bit Rate: 32 Kbps - 16 Mbps
Compression: H.265+, H.265, H.264, H.264+
Settings: Remote Configuration, Remote Viewable, Email Notification, Event Log, Event Notification, Selectable Frame Rate, Privacy Video Block, Video Analytics Capable
Card Reader Type: Micro SD Card (Not Included)
Storage: Up to 128GB
Language: English

Mobile App Support: Yes - iOS, Android

Ambient Temperature Range: -40°C to +60°C
Operating Humidity: Up to 95% (Non-condensing)
Housing Materials: Aluminum
Lens Material: Tempered Glass
Mounting: Adjustable Bracket
Wiring Hub: (2) 3/4" NPT

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The EXPCMR-IP-POE-OZ-6MP-27D-88D from Larson Electronics is an Explosion Proof Camera that is designed for security and remote observation in both indoor and outdoor hazardous environments. This 6.0MP HD high resolution security camera features auto focus and 3072 × 2048 @ 20 fps resolution. Equipped with built-in infrared, the monitoring device supports Power over Ethernet (PoE) from data cables (no power cord needed).

Camera Features: The EXPCMR-IP-POE-OZ-6MP-27D-88D security camera provides operators in hazardous areas with crisp 6.0MP high resolution images. A 2.8-12mm motorized lens automatically adjusts focus, providing operators with a precise 88° ~ 27° field of view. This camera measures a compact 12.34" x 3.96" x 4.22" and the mounting base allows for precise aiming with 90° of vertical adjustment. Compatible with storage up to 128GB (micro SD card not included), the remote inspection camera utilizes a true day/night with mechanical cut filter to produce clear images in variable and low light conditions. This infrared light offers a distance of 170 feet during use.

The explosion proof unit comes with built-in infrared lights. For additional infrared illumination, an external infrared light can be used with the explosion proof device (not included). For 12-24V DC applications, we recommend the Larson Electronics 12-watt explosion surface-mount infrared LED light (EXHL-TRN-LE3-IR-1224). As an alternative, we also offer the EXHL-TRN-LE3-IR-1227 for 120-240V AC applications.

The EXPCMR-IP-POE-OZ-6MP-27D-88D security camera is built to perform under harsh and rugged conditions. This IP67 rated waterproof unit resists the corrosive effects of weather, dust, dirt, and humidity. This Class I, Divisions 1 & 2; Class II, Divisions 1 & 2 and Class III, Divisions 1 & 2 rated camera provides property and product security while also protecting operators with its safe and reliable explosion proof and weatherproof design.

Power/Wiring: This unit is designed to operate on PoE, allowing the device to receive power directly from the data cable. Link-up with the camera is achieved via a customer provided, standard stranded cable, such as a CAT6 ethernet cable. The cable can be routed either through the mounting surface or through a cable guide at the edge of the mounting base.

Our explosion proof cameras with Power over Ethernet (PoE) features enable data transfers and power to be passed through a single Ethernet cable that is usually a Cat 3/Cat 5 cable or

better. There are several types of PoE, which come with their own respective standard and maximum power to port capabilities. The IEEE 802.3af PoE standard, with a voltage range of 44.0 - 57.0V, offers 15.4W of DC power for each port. The IEEE 802.3at PoE standard, with a voltage range of 50.0 – 57.0V, provides up to 30W of DC power per port, which is ideal for surveillance cameras, antennas and network access points. The IEEE 802.3bt PoE standard, with a voltage range of 50.0 – 57.0V, provides 60W of DC power for each port. In order to utilize PoE properly, the components, such as the receiving unit and sending device, must be PoE compliant.

Mounting: The EXPCMR-IP-POE-OZ-6MP-27D-88D explosion proof security camera is secured to flat surfaces, such as a ceiling or wall, using an adjustable reverse pedestal style bracket. The included mounting bracket allows 90° vertical adjustment and 360° of swivel for precision aiming.

Applications: Vessel, tank and reactor monitoring, remote observation of external facilities, offshore and land based rigs, indoor and outdoor security, commercial buildings and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs