

**MT-DOE16-3P-480D-3KVA-690Y.400-N3R**

**3 kVA Isolation Transformer - 480V Delta Primary - 690Y/400 Wye-N Secondary - NEMA 3R**

**Product ID: 278909**



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

**MT-DOE16-3P-480D-3KVA-690Y.400-N3R Isolation Transformer**

Phase: Three Phase  
Frequency: 60 Hz  
kVA: 3  
Primary Voltage: 480 V Delta  
Taps: TBD  
Secondary Voltage: 690Y/400 V Wye-N  
Winding Material: Aluminum  
Insulation: 400°C  
Temperature Rise: 150°C  
Impedance (Std): -  
Seismic: Yes  
Sound Level: Meets NEMA ST-20 Standards  
Primary Termination: -  
Secondary Termination: -  
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated  
Finish: ANSI 61 Grey, UL50 Finish  
Dimensions: 14"-L x 6"-D x 20"-H  
Weight: 100 lbs  
Mounting: Floor or Wall Mount

**Ratings**

Listed for United States and Canada  
ANN Cooling  
IP24 Rated  
Isolation Transformer

**Special Orders- Requirements**

Contact us for special requirements  
Fax: 1-903-498-3364  
Toll Free: 1-800-369-6671  
Intl: 1-214-616-6180  
E-mail: [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

**The MT-DOE16-3P-480D-3KVA-690Y.400-N3R 480 V Delta 3 Phase Energy Efficient Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-3P-480D-3KVA-690Y.400-N3R provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of**

---

**applications and businesses.**

**\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS\***

**Transformer Features:** With a transformer rating of 3 kVA, the MT-DOE16-3P-480D-3KVA-690Y.400-N3R isolation transformer is a three phase unit with a primary voltage of 480 V Delta. It also provides a secondary voltage of 690Y/400 V Wye-N. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology. This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor or wall mounted. The unit also features 400°C insulation with a 150°C temperature rise and is rated IP24.

**Benefits:** The MT-DOE16-3P-480D-3KVA-690Y.400-N3R isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

**Safety:** The MT-DOE16-3P-480D-3KVA-690Y.400-N3R is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-3P-480D-3KVA-690Y.400-N3R achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.


**Applications:** General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) to discuss your specific requirements.

## Wiring Diagram

**WARNING: DO NOT SERVICE WHILE ENERGIZED!**

### MT-DOE16-3P-480D-3KVA-690Y.400-N3R



| PRIMARY VOLTS               |         |
|-----------------------------|---------|
| CONNECT LINES TO H1, H2, H3 |         |
| CONNECT "A" TO TAP          | VOLTAGE |
| 1                           | 456     |
| 2                           | 480     |
| 3                           | 504     |
| SECONDARY VOLTS             |         |
| CONNECT LINES               | VOLTAGE |
| X1, X2, X3                  | 690     |
| X0-X1, X0-X2, X0-X3         | 400     |









MT-ATX-1P-208V-3KVA-120V  
Uninsulated Dry Type Transformer


Phase: Single Phase  
KVA: 3  
Volts: 120V  
Insulation: 150°C  
Weight: 100lb  
Wdg. Mat: AA

Outdoor Type 2R



Low Voltage: 208

High Voltage: 120



Low Voltage Connections

| 1    | 2    |
|------|------|
| 120V | 208V |
| 240V | 480V |

High Voltage Connections

| 1    | 2    |
|------|------|
| 120V | 240V |
| 480V | 600V |

LARSONELECTRONICS.COM

1-800-369-6671

sales@larsonelectronics.com



## **Frequently Asked Questions (FAQ)**