

MPD-EB47-T.400AB-SZ0-V-1.R29-8.R26-24.R10-M1

Power Distribution Panel - 240V AC, 1-phase - 400A MB Panel - (33) Breakers - Left Side Hinged Door - NEMA 1

Product ID: 279371



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-EB47-T.400AB-SZ0-V-1.R29-8.R26-24.R10-M1 Power Distribution Panel

Line-in Cord: Not Included - Requires Minimum Use Wiring 400A Rated Cu @ [600 V]
(**Customer Provided**)

Line-in Cord Cap: Not Included - Requires Minimum Use Device 400A @ [120/240 V]
(**Customer Provided**)

Primary Voltage: 240 V AC

Primary Phase: 1-Phase

Primary Frequency: 60 Hz

Panel Type: Main Breaker

Panel: 120/240V 1PH 400A MCCB 42 Space Hinged N1

Primary Breakers: (1) 40A 2P MCB [250V]; (8) 20A 2P MCB [250V]; (24) 20A 1P MCB [125V]

Primary Protection: MCCB Circuit Breaker; MCB Circuit Breakers

Transformer: N/A

Circuits: 42

Feed Type: Bottom

Top Entry: -

Interrupting Rating: 14

Operating Temperature: 40°C

Materials: Steel, Copper

Bus Material: Copper

Ground Bar Material: Aluminum (Bolted)

Panel Finish: High-Strength TGIC Polyester Powder Coated Blue

Form Factor: Blue Powder Coated N1 Hinged Enclosure - Left Side Hinged Door

Input Wire Size: -

Internal Dimensions: -

Weight: -

Ratings

Max Primary OCP: 400A @ 240 V

NEMA 1

Left Side Hinged Door

Made in the USA

Powder Coat Finish Standards:

Complies with ASTM D-522

Complies with ASTM D-3363

Complies with ASTM D-2794

Complies with ASTM D-523

Complies with ASTM D-3359

Special Orders - Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

Mounting: Surface Mount

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

The MPD-EB47-T.400AB-SZ0-V-1.R29-8.R26-24.R10-M1 from Larson Electronics is a Power Distribution Panel that is designed for reliable, safe, and convenient power distribution at industrial work sites. This 400-amp unit provides single-phase 240 V AC via a main circuit breaker panel. The power distribution panel provides operators the ability to safely tap into and distribute 240 V AC power from a variety of sources including generators and direct grid power. The MPD-EB47-T.400AB-SZ0-V-1.R29-8.R26-24.R10-M1 has a left side hinged panel.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

The MPD-EB47-T.400AB-SZ0-V-1.R29-8.R26-24.R10-M1 power distribution panel provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. The MPD series of power distribution panels require operators to provide their own line-in cables for use. Knockouts located at the bottom of the unit are provided for convenient installation of operator-provided input and output cables.

The panel is designed to operate with single-phase 240 V AC voltage. Power distribution for this panel runs 240 V AC through a 400-amp, 42 circuit main circuit breaker panel. The NEMA 1 400-amp 120/240 V 1-phase main circuit breaker panel is protected by three 40-amp 2P din rail mounted MCB breaker, eight 20-amp 2P din rail mounted MCB breakers, and twenty-four 20-amp 1P din rail mounted MCB breakers.

Enclosure Design: This power distribution system is housed in a space-saving enclosure and carries a NEMA 1 rating for protection against falling dirt and incidental contact in indoor locations. A left side hinged door offers access to internal system components.

The power distribution system is constructed of steel with a polyester powder coated blue finish for durability against dirt, moisture and mild corrosion. This special coating creates a high-strength barrier for protection from accidental bumps and scratches. The TGIC polyester powder coat finish offers reliable resistance against chemicals, UV light (sun light) and degrading elements in outdoor locations. Our powder coating solution ensures robust color retention for many years without fading. Custom colors, such as blue (standard), black, desert tan or forest green, and galvanized finishes are available upon request. Non-standard powder coat colors or galvanized finishes may increase price and lead times.

We also offer similar power distribution panels on dolly carts with wheels, powder coated cube frames with lifting eyelets/skid pockets or stand-alone with handles for faster turnarounds and completion of temporary tasks.

Certification: All units are built in accordance to NFPA 70 (National Electric Code). All equipment is NEMA 1 rated for indoor use and provide a degree of protection against falling dirt and incidental contact. NEMA 4 and NEMA 4X equipment can be equipped upon request.


Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth ground.


~Please check all motor loads for dual rated motors that will work 208 or 240.~


Applications: This power distribution system is NEMA 3R rated and ideal for indoor/outdoor use and applications including but not limited to; construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.


At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to

honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.









Frequently Asked Questions (FAQ)