Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14

30 kva 3PH Isolation Transformer, 220V Delta Primary, 230Y/133 Wye-N Secondary, N3R, Ventilated, 50/60 Hz

Product ID: 280041



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14 Isolation Transformer

Transformer Type: Isolation Transformer
Transformer Configuration: Dry Type
Phase: Three Phase
Frequency: 50/60 Hz ± 3%
Primary Voltage: 220V AC
Primary Configuration: 3, 3-wire plus ground, ±5%, Delta
Capacity: 30 kva
Secondary Voltage: 230Y/133 V Wye
Secondary Configuration: 3, 4-wire Wye
Knockouts: Sides
FCAN (Above) Taps: 2
FCBN (Below) Taps: 2
Tap %: 2.5
Impedance: 3 - 5% Typical
Efficiency @ 35% Load: ~98%
Winding Material: Aluminum
Primary Termination (Std): Terminal Lugs
Secondary Termination (Std): Terminal Lugs
Termination Access: Front Access Cover
Mounting: Floor
Cooling: Air/Dry
Insulation: 220°C
Temperature Rise: 150°C
Ambient Temperature Range: 0°C - 50°C
Sound Level: Not to Exceed 60 dBA @ 1 Meter Under Zero to Full Load Conditions
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated - Steel
Finish: ANSI 61 Grey

Approvals/Ratings

NRTL Listed for United States
NRTL Listed for Canada
NEMA 3R Indoor/Outdoor Steel Enclosure
Meets or Exceeds NEMA ST-20 Standards
DOE Efficiency Isolation Transformer
Distribution Type Transformer
Built to UL-50 Standards
Seismic Qualified for Earthquake Loads
RoHS
CE Certified

Special Orders - Requirements

Dimensions: 19.37"L x 24.39"W x 25.5"H
Weight: 325 lbs
Shipping Method: Pallet Freight - LTL
Shipping Weight: 390 lbs
Shipping Dimensions: 48"L x 40"W x 34"H

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14 from Larson Electronics is a Three Phase 220 V to 230Y/133 Isolation Transformer that is powerful, reliable, and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14 provides increased reliability and protection against critical equipment failures. This 30 kva isolation transformer is designed for distribution loads and potential seismic activity. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: The MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14 Isolation transformer is a three phase transformer with an 30 kva capacity rating. This isolation transformer is configured with an input voltage of 220 V Delta 3-Phase AC on the primary side and an output voltage of 230Y/133 Wye-Neutral 3-Phase AC on the secondary side. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and is designed to be floor mounted. Wall mount brackets or additional mounting accessories can be purchased separately. This 30 kva isolation transformer features 220°C insulation with a 150°C temperature rise.

Benefits: The MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14 220V to 230Y/133 general purpose transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

Overload Capacity: When normally operating at 90% of its rated load, the permissible daily overloads above rating are:

- 160% - 1/2 hour
- 140% - 1 hour
- 125% - 2 hours
- 110% - 4 hours
- 105% - 8 hours

Short Circuit Strength: The MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14 is designed to be capable of withstanding, without injury; stresses caused by short circuits on the secondary with rated voltage applied to the transformer provided the short circuit duration does not exceed time limits as specified by NEMA.

Mounting: The MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14 can be floor mounted. Integrated floor brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access. It includes compression-style lugs size appropriate for amperage where used on primary and secondary terminals. The chassis lug on this unit is connected to neutral and (Xo) and ports are provided for three external connections.

This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the

transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership.
Safety: The MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14 is an isolation transformer which means that it provides operators with an increased level of protection against electric shock and injury. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-3P-220D-30KVA-230Y.133-GD1-4500-14 achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.
Applications: Converting 220V local grid power to 230Y/133 for on-site equipment. This 30 kva power transformer is ideal for sensitive equipment such as CNC equipment, computers, medical devices, ovens, or laboratory instruments. Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


LARSON ELECTRONICS
MADE IN USA
LARSONELECTRONICS.COM / 1-800-369-6671
WARNING
LARSON ELECTRONICS
A14


LARSON ELECTRONICS
LARSONELECTRONICS.COM / 1-800-369-6671
WARNING
LARSON ELECTRONICS
A14


X1
H1
X2
H2
X3
H3
H4
X0

Frequently Asked Questions (FAQ)