

## **MPD-DS-FS-FDS-3P-4W-208V-900A-EF-BM-N3R-TD**

**Fused Disconnect Switch, 900 Amp, 208V 3PH AC, 3-Pole 4-Wire, (3) Class L Time Delay Fuses, NEMA 3R**

**Product ID: 285289**



Image: MPD-DS-FS-FDS-3P-4W-208V-900A-EF-BM-N3R-TD

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

### **MPD-DS-FS-FDS-3P-4W-208V-900A-EF-BM-N3R-TD Disconnect Switch - Fused Disconnect**

**Unit Type:** Service Entrance Fused Disconnect Switch

**Line-In:** N/A (customer provided)

**Line-In Cord Cap:** N/A (customer provided)

**Line-In Connections:** Terminal Lugs, Accepts 750MCM-1/0

**Line-In Orientation:** Bottom Feed

**Voltage (V):** 208V AC Delta or Wye

**Phase (PH):** 3-Phase

**Frequency (Hz):** 60 Hz (60-Cycles)

**Protection Method:** Fused, Class L Type Fuse

**Protection Type:** Time Delay Fuse

**Protection Fuses:** (3) Fuses, Included

**Protection Ampacity:** 900A

**Mains Rating (Amps):** 900A

**Interrupting Rating:** 200 kA @ 208V AC

**Disconnect Means:** Manual via Handle

**Neutral Connection:** Insulated Groundable Neutral Kit with Bonding Strap

**Line-Out:** N/A (customer provided)

**Line-Out Cord Cap:** N/A (customer provided)

**Line-Out Connection:** Terminal Lugs, Accepts 750MCM-1/0

### **Ratings**

NRTL Listed Service Equipment

NRTL Listed to UL 891 Dead Front Switch Boards

NEMA 3R Rated for Indoor and Outdoor Use

Made in the USA

**Line-Out Orientation:** Bottom Feed

**Form Factor:** Rectangular, Slim-profile Enclosure w/ Lockable Door

**Door:** (1) Left Hinged Door w/ Pad Lockable Handle

**Enclosure Material:** 11GA Sheet Steel

**Enclosure Finish:** ANSI 49 Grey

**Enclosure Type:** NEMA 3R Ventilated

**Dimensions:** 36"-W x 52"-H x 24"-D

**Weight:** 800 lbs

**Shipping Dimensions:** 58"-W x 44"-L x 98"-H

**Shipping Weight:** 850 lbs

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

**Special Orders - Special Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Intl:** 1-903-270-1187

**Fax:** 1-903-765-7664

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

\*All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250\*

**Made in the USA**

**The Larson Electronics MPD-DS-FS-FDS-3P-4W-208V-900A-EF-BM-N3R-TD Power Distribution Disconnect Switch is designed for reliable, safe and convenient power distribution at industrial work sites. This fused disconnect includes three 900-amp 208V rated Class L fuses. Designed for floor mounting installations, the bottom feed disconnect switch is protected by a NEMA 3R rated, steel enclosure with a ventilated design.**

***\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS\****

The MPD-DS-FS-FDS-3P-4W-208V-900A-EF-BM-N3R-TD service entrance disconnect switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with three-phase 208V AC Delta or Wye, the disconnect switch features a manual operating handle. This bottom feed disconnect carries a 200 kA at 208V AC interrupt rating. The switchgear comes with and accepts three 900-amp 208V rated Class L time delay fuses. An insulated groundable neutral kit with bond strap is included for neutral connections.

**Operation:** The dead front disconnect switch features a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power. A dead front cover protects operators from the fuses for safety. Operators can inspect the fuses through the dead front via a vented cover. Removing the dead front allows access to the fuses.

**Time Delay vs. Fast Acting Fuses** Two of the most common types of fuses found in power distribution equipment are time delay and fast acting fuses.

**Time Delay:** Time delay fuses are tripped once overcurrent heat builds up enough to melt the fuse element over a period of time. That period of time varies between different time delay fuses depending on the application. Time delay fuses decrease the chances of false tripping. During startup, many components require a large current for a very short amount of time. In other words, a time delay fuse disconnects the circuit only when the overcurrent persists in the line.

**Fast Acting:** Fast acting fuses are tripped immediately upon sensing an overcurrent or short circuit in the line. They are ideal for electronics, components, or systems that

cannot withstand sudden changes in current. A fast acting fuse will not withstand a temporary overload such as one that occurs during the startup process.

**Enclosure Design:** The disconnect switch is protected by an 11GA sheet steel enclosure with ANSI 49 grey finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated for protection against water, moisture and debris. This rating allows the fused disconnect to be used in indoor and outdoor areas.

**Certification:** This disconnect switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.

**Mount:** Operators can mount the service entrance disconnect on floors and flat surfaces.

**Customization:** The MPD-DS-FS-FDS-3P-4W-208V-900A-EF-BM-N3R-TD can be customized to meet specific operating and power requirements. Example of customizations include:


- Making the fused disconnect portable and certified to NRTL UL 1640 for portable equipment
- Adding single pole camlock connectors for quick connections
- Adding heaters for cold environments
- Aiding alarm relays for trip notification down stream
- Adding powering meters

**Applications:** This switchgear is suitable for indoor/outdoor use and applications including, but not limited to, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) for more information about our custom options tailored to meet your specific industry needs.

---

|                                                                                     |                    |   |   |   |   |   |            |
|-------------------------------------------------------------------------------------|--------------------|---|---|---|---|---|------------|
| 8                                                                                   | 7                  | 6 | 5 | 4 | 3 | 2 | 1          |
| REV                                                                                 | DESCRIPTION        |   |   |   |   |   | DATE       |
| A                                                                                   | PRODUCTION RELEASE |   |   |   |   |   | 08/16/2022 |
| MPD-DS-FS-<br>FDS-3P-4W-208V-900A-<br>EF-BM-N3R-TD                                  |                    |   |   |   |   |   |            |
|  |                    |   |   |   |   |   |            |
| 8                                                                                   | 7                  | 6 | 5 | 4 | 3 | 2 | 1          |




| TAGS                                   | QTY | CATALOG | DESCRIPTION                       |
|----------------------------------------|-----|---------|-----------------------------------|
| DS1-101.12<br>DS1-101.18<br>DS1-101.23 | 3   |         | 900A FUSE 200kA AT 600VAC CALSS L |

|                                                                                                                                                        |                                                         |                    |                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|--------------------|------------------|
| <br>LARSON<br>ELECTRONICS<br>9419 E US HWY 175,<br>KEMP, TX 75143 | TITLE<br>MPD-DS-FS-FDS-3P-4W-208V-900A-<br>EF-BM-N3R-TD |                    |                  |
|                                                                                                                                                        | DRAWN BY<br>A. CIBISOVS                                 | DATE<br>08/16/2022 | REV<br>A         |
|                                                                                                                                                        | CHECKED BY<br>S. DESAI                                  | SHEET #<br>1 OF 1  | DRAWING #<br>101 |

Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.765.7664



Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.765.7664



Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.765.7664



Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.765.7664





---

## Frequently Asked Questions (FAQ)

There are no Faqs