Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14

25 kVA Isolation Transformer - 400V Delta Primary - 230Y/133 Wye-N Secondary - NEMA 3R - Fully Potted/Encapsulated - 304 Stainless Steel Enclosure

Product ID: 292928



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14 Encapsulated Isolation Transformer

Phase: Three Phase
Frequency: 50/60 Hz +/- 3%
kVA: 25
Primary Voltage: 400 V Delta
Primary Connection: Delta
Primary FCAN: 2 x 2.5%
Primary FCBN: 2 x 2.5%
Secondary Voltage: 230Y/133 V Wye-N
Secondary Connection: Wye-N
Winding Material: Aluminum
Efficiency: No Efficiency Specification
Insulation: 180°C
Temperature Rise: 115°C
Ambient Operating Temperature Range: -40°C to 50°C (-40°F to 122°F)
Ambient Storage Temperature Range: -40°C to 70°C (-40°F to 158°F)
Operating Altitude: 3000 Meters
Storage Altitude: 10,000 Meters
Impedance (Std): 1.7-2.5% (Typical)
Seismic Resistance: Earthquakes Up to Intensity VIII on the Modified Mercalli Scale
Sound Level: 60 dBA @ 1 Meter Under Zero to Full Load
Primary Termination: Wire Leads
Secondary Termination: Wire Leads
Enclosure Material: NEMA Type 3R Heavy Duty - Fully Potted / Encapsulated
Finish: 304 Stainless Steel
Dimensions: 30.00"-H (76.2 cm) x 25.50"-W (64.77 cm) x 12.50"-D (31.75 cm), (*Please note that dimensions are approximate and subject to change*)

Ratings

NRTL Listed for United States and Canada
ANN Cooling
IP14 Rated
Fully Potted / Encapsulated
Isolation Transformer

Special Orders - Requirements

Weight: 500 lb (*Please note that weight is approximate and subject to change*)
Shipping: Pallet Freight
Shipping Dims: 48" x 48" x 36"
Shipping Weight: 550 lb
Mounting: Floor

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14 from Larson Electronics is a 400 V Delta 3 Phase Energy Efficient Fully Potted Isolation Transformer that is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14 provides increased reliablity, protection against critical equipment failures and an extra level of protection by isolating the power source from the connected device. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 25 kVA, the MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14 isolation transformer is a three phase unit with a primary voltage of 400 V Delta that can operate at +/- 5% of the rated input voltage. It also provides a secondary voltage of 230Y/133 V Wye-N.
Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.
This fully potted unit boasts a low cost of ownership and is highly energy efficient. It is potted in flame retardant, thermally conductive, high voltage insulating epoxy with silica filling. Lower heat emissions mean less cooling is needed as well. The NEMA Standard Type 3R 304 stainless steel enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 180°C insulation with a 115°C temperature rise and is rated IP14.
Benefits: The MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14 encapsulated isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. A double-barrel compression lug (sized per NEC) is included with this unit for ground cables. The compression lug is mounted to existing core and coil frame bolts.
This fully potted transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor mounting brackets make installation fast and easy.
Safety: The MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14 is a fully potted isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14 achieves these safety features by seperating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.
When normally operating at 90% of its rated load, the permissible daily overloads above rating are:

- 160% - ½ hour
- 140% - 1 hour
- 125% - 2 hours
- 110% - 4 hours

- 105% - 8 hours

Humidity: For operation purposes, the MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14 has an acceptable humidity range of 0 to 100%. This includes condensation, rain from 0 to 10 cm/hr (4in/hr), radial ice from 0 to 2.5 cm (1 inch), 15.0 cm (5.9 inches) of snow and direct exposure to sunlight. For storage purposes, this unit has an acceptable humidity range of 0 - 100% including condensation.
Seismic: The MT-ISX-SS-FP-3P-400D-25KVA-230Y.133-GD1-4504-14 is designed to withstand seismic forces produced by an earthquake of Intensity VIII on the modified Mercalli Scale.
Environmental Exposure: This fully potted transformer will continue to meet all specified ratings when exposed to salt fog and to sunlight or solar radiation of 1110 W/M2.
Applications: Power supplies for sensitive equipment such as computers, medical devices, or laboratory instruments.
Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


H1
H2
7 5 3 1
2 4 6 8
X4
X2
X3
X1
LARSON
ELECTRONICS
MT-ATX-5S-FP-1P-480V-25KVA-120.240V-N4X
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com



Frequently Asked Questions (FAQ)