

EXP-RT-SPST-MIN.720

Explosion Proof Timer Switch - Class I, II, III - 12-Hour Timer, SPST Switch - NEMA - 120-277V AC
Product ID: 293389



Image: EXP-RT-SPST-MIN.720

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXP-RT-SPST-MIN.720 Explosion Proof Timer Switch

Listing: NRTL Listed for United States, Canada

Unit Type: Explosion Proof Timer Switch

Dimensions: 5.1"-L x 3.625"-W x 6.663"-H

Minutes: Up to 720 Minutes

Configuration: SPST

Voltage: 120-277V AC, 50/60 Hz

Timer Control: Mechanical Spring

Amperage: 20A @ 125V AC (7A for Tungsten loads), 10A @ 250 VAC, 10A @ 277V AC

Horsepower: 1HP @ 120V AC, 2HP @ 240V AC

Ambient Operating Temp: -40°F to 104°F (-40°C to 40°C)

Unit Materials: Copper-Free Cast Aluminum

Mounting: External Mounting Lugs on Body

Hub Quantity: (2) Feed Through or (1) Dead End

Hub Size: 1/2" or 3/4"

Ratings/Approvals

Class I, Divisions 1 & 2 Groups C,D

Class II, Divisions 1 & 2 Groups E,F,G

Class III, Divisions 1 & 2

NEMA 3,7(BCD),9(EFG),12

No Power Input Required for Timer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

Made in Texas

The EXP-RT-SPST-MIN.720 from Larson Electronics is an Explosion Proof Timer Switch that provides timed controls for equipment in combustible work sites and locations. The 12-hour timer can be configured using a SPST switch. Constructed of copper-free aluminum, the unit is NEMA-rated for durability in rugged environments.

The EXP-RT-SPST-MIN.720 offers robust timing control of equipment. This unit is equipped

with a single pole single throw switch, which allows operators to set the timer to 12 hours. The explosion proof timer switch is designed for Class I, Divisions 1 and 2, Class II, Divisions 1 and 2, and Class III hazardous environments and operates on 120-277 V AC 50/60 Hz; 20A @ 125V AC (7A for Tungsten loads), 10A @ 250 VAC, 10A @ 277V AC. It uses 1HP @ 120V AC and 2HP @ 240V AC.

The EXP-RT-SPST-MIN.720 is constructed of copper-free cast aluminum for superior performance and durability. These switches are not factory sealed and require external sealing fittings. Two external mounting lugs provide simple and secure mounting of the unit to walls and flat surfaces. This explosion proof unit is available with either 1/2" or 3/4" NPT tapped hubs. The conduit openings are provided on the top and bottom of the unit in feed through versions, while dead-end versions have a single conduit hub, providing easy and secure connection to main power line supplies. Operating temperature is -40°F to 104°F (-40°C to 40°C).


Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Lighting, Wet areas or Locations Where Combustible Dust is Present. This switch can be used with fans, motors, heaters, and lighting (including incandescent, halogen, compact fluorescent, tungsten, and LED lighting loads).

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

	8	7	6	5	4	3	2	1
	REV	DESCRIPTION						DATE
	A	PRODUCTION RELEASE						05-09-2023
EXP-RT-SPDT-MIN.720-XX-XX 								
	8	7	6	5	4	3	2	1

EXP-RT-SPDT-MIN.720-XX-XX





TAGS	QTY	CATALOG	DESCRIPTION
1-101.12	1	UNV00019209	Spring Wound Countdown Timer, Commercial, 125-277 VAC, 50/60 Hz, SPDT, 12 Hour Max, w/ Hold, Silver

 LARSON ELECTRONICS 9419 E US HWY 175, KEMP, TX 75143	TITLE EXP-RT-SPDT-MIN.720-XX-XX		
	DRAWN BY J.Maldonado	DATE 05-09-2023	REV A
	CHECKED BY S.Desai	SHEET # 1 OF 1	DRAWING # 101





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Frequently Asked Questions (FAQ)

There are no Faqs