Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU

0.75 KVA (750 VA) DOE Efficiency Transformer - 240/480V Primary - 120/240V Secondary - NEMA 4X - Stainless Steel - Fully Potted

Product ID: 294880



Image: MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU DOE Efficiency Transformer

Transformer Type: Fully Potted / Encapsulated Distribution
Phase: Single Phase
Frequency: 60 Hz
kVA: 0.75
Primary Voltage: 240/480V
Taps: -
Secondary Voltage: 120/240V
Winding Material: copper
Efficiency: DOE 2016 / NRCAN 2019 (Also Meets ON Reg. 404/12)
Insulation: 180°C
Temperature Rise: 115°C
Impedance (Std): -
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Termination: -
Secondary Termination: -
Enclosure Material: NEMA Type 4X Heavy Duty Resin Encapsulated - Stainless Steel
Finish: Natural Finish
Dimensions: 11.62"H x 5.50"W x 5.13"D
Weight: 30 lb
Mounting: Wall Mount

Ratings

NRTL Listed for United States and Canada
ANN Cooling
IP66 Rated
Fully Potted / Encapsulated
Distribution Transformer
NRTL Certified to C22.2 No. 47
NRTL Certified to UL 506

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU 240/480V 1 Phase Energy Efficient Fully Potted Distribution Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU provides increased reliablity and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 0.75 KVA (750 VA), the MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU fully potted distribution transformer is a single phase unit with a primary voltage of 240/480V. It also provides a secondary voltage of 120/240V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 4X stainless steel enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features 180°C insulation with a 115°C temperature rise and is rated IP66.

Benefits: The MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU fully potted distribution transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This encapsulated distribution transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated mounting brackets make installation fast and easy and the offset outward facing installation holes allow for easy power tool access.

Safety: The MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU is a distribution transformer which means that it provides operators with an increased level of protection against electric shock. A distribution transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.


Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or

sales@larsonelectronics.com to discuss your specific requirements.

Wiring Diagram

WARNING: *DO NOT SERVICE WHILE ENERGIZED!*

MT-DOE16-SS-FP-1P-240.480V-0.75KVA-120.240V-N4X-CU



Primary Volts	Connect Lines To	Jumpers
480	H1-H4	H2-H3
240	H1-H4	H1-H3, H2-H4

Secondary Volts	Connect Lines To	Jumpers
240	X1-X4	X2-X3
120	X1-X4	X2-X4, X1-X3

LARSON ELECTRONICS LLC • 9419 E US HWY 175 • KEMP, TX 75143
p: 1-800-369-6671 • intl: 903-498-3363 • f: 903-498-3364 • sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs