Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-UPM-R11-1P-GMQ-25KVA-SZ-A6-BF-CZ-2ZZ-M1

25 KVA Overhead Distribution Transformer, Pole Mount, 13200Y/7620 Grounded Wye Pri., 120/240V Sec., Mineral Oil, Copper, ONAN, Tap Changer - AES Part # - 10.523.682

Product ID: 296460



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-UPM-R11-1P-GMQ-25KVA-SZ-A6-BF-CZ-2ZZ-M1 Pole Mount Overhead Transformer

Transformer Type: Overhead Distribution Transformer, Conventional Type
Transformer Configuration: Liquid Filled Pole Mounted
Transformer Polarity Type: Subtractive
Phase: Single Phase
Capacity: 25 KVA
Primary Voltage: 13200GrdY/7620
Primary Voltage Switch: N/A
Primary Voltage Class: 15 kV Class
Primary Phasor: Grounded Wye
Primary BIL: 95 kV
Secondary Voltage: 120/240V (L-N-L)
Secondary Voltage Class: 1.2 kV Class
Secondary Phasor: Dual Winding Single Phase
Secondary BIL: 30 KV
Frequency: 60 Hz
Temperature Rise: 65°C
Insulation Rating: Class E Insulation - 120°C, 248°F
Forced Air (Fans): None
Cooling Class: ONAN; Self-Cooled
Tap Changer: 5-Position Tap Changer w/ External Operating Handle
Tap Qty: (2) FCAN Above, (2) FCBN Below
Tap %: 2.5%
Tap Changer Switch Location: Middle of Tank Body, Left of Mounting Provisions
Impedance: 1.0-2.2% Typical
Primary Connection Type: Live Bushing Lug
Primary Termination: Porcelain High Voltage Bushing
Primary Connection Qty: (1)

Ratings

Meets/Exceeds DOE 2016 Efficiency Ratings
Complies with ANSI / IEEE C57 12.00
Complies with ANSI / IEEE C57 12.20
Complies with ANSI / IEEE C57 12.28
Complies with ANSI / IEEE C57 12.31
Complies with ANSI / IEEE C57 12.70
Complies with ANSI / IEEE C57 12.80
Complies with ASTM D3487

Features:

Non-PCB Insulating Fluid
Lifting Lugs Included
Corrosion Resistant Cover Band

Efficiency: 98.70%

Primary Lightning Arrestors: (1) Bolt-on High Voltage MCOV Lightning Arrestor, w/ Bird Guard, Side Mounted to Tank
Primary Lightning Mounting Provision: Mounting Provisions for Installing Lightning Arrestor on H1 & H2 Primary Terminals
Primary Lightning Arrestors Voltage Rating: 15 kV
Primary Lightning Arrestors MCOV Rating: 12.7 kVrms
Secondary Connection Type: Live Bushing Lug
Secondary Connections: Threaded Stud Terminals
Secondary Connection Qty: (3)
Secondary Neutral Connection: Secondary X2 Neutral Grounded to Tank via 1/2"-13 UNC Tapped Hole, 7/16" Deep Bung & Copper Ground Strap
Terminals: Tin Plated Primary and Secondary - Accepts Copper or Aluminum Connections
Grounding Provisions: (1) Lug w/ Grounding Strap, Tank Grounding Lug
Transformer Protection: N/A
Load Break Switch: N/A
Efficiency Standard(s): Meets DOE 2016 Standards, Meets CSA Standards Meets ANSI/IEEE Standards
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Pulse Drive Rating: N/A
Insulation Fluid: FR3 Oil
Fluid Capacity*: 19 Gallons
Fluid Weight*: 148 lb
Liquid Level Indicator: Internal In-Tank Oil Level Line
Temperature Indicator: N/A
Pressure/Vacuum Indicator: N/A
Pressure Relief Device: Included, Automatic Action
Fault Indicator: N/A
Oil Level Marking: Internal
Fill Valve: N/A (Tank Filled via Removable Lid)
Drain Valve: 1/2" NPT Port w/ Removable Bolt
Winding Material: Copper
Ambient Temperature Rating: 40°C
Ambient Operating Temperature Range: -40°C to +40°C (-50°F to +104°F)
Sound Level: 48 dBA
Elevation Level: N/A
Core Material: Grain Oriented Steel
Tank Material: Coated Steel
Housing Material: Coated Steel w/ Corrosion Resistant Cover Band, Removable Top Cover
Hardware Material: Stainless Steel Hardware
Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating
Finish Color: White
Mounting: Double Hanger Bracket
Mounting: Pole Mount via Hangar Brackets
Lifting Lugs: Included
Dimensions*: 22.40"-W x 23.10"-D x 36.00"-H
Tank Diameter*: 17.72"-OD
Dry Weight*: 198.41 lb
Total Weight (Liquid Filled)*: 434 lb
*Please note that numbers are approximate and subject to change

Based on transformer operating at 50% of nameplate base kVA.

Load Losses Based on 85°C Reference Temp.
No Load Loss (in watts): +/- 104W
Full Load Loss (in watts): +/- 377W
Total Load Loss (in watts): +/- 481W

Note: Losses offered are typical only, not guaranteed

Labeling:
Externally Stencilled (Painted) KVA Rating
Externally Stencilled (Painted) Voltage Rating
External Non-PCB Label
External Barcode Label
Stainless Steel Riveted Nameplate

Factory Tests:
Winding Resistance Test
Insulation Resistance Test
Voltage Ratio Error Test
Short-circuit Impedance Test
No-load Loss (Wattage) Test
Load Loss (Wattage) Test
Induced Voltage Withstand Test
Separate Source Voltage Withstand Test
Pressure Integrity Test Test

Shipping:
Shipped on pallet on open flatbed
Palletized on Wooden Pallet w/ Skid Pockets
Pallet Skid Facing Outward Sides of Truck
Note: For low quantity purchases, enclosed truck can be requested
Note: Crated shipping in lieu of palletizing can be done upon request for an additional fee

Special Orders - Requirements
Contact us for special requirements
Toll Free:1-800-369-6671
Intl:1-214-616-6180
Fax:1-903-498-3364
E-mail:sales@larsonelectronics.com

The MT-UPM-R11-1P-GMQ-25KVA-SZ-A6-BF-CZ-2ZZ-M1 from Larson Electronics is an Overhead Distribution Pole Mounted Transformer that offers powerful, reliable, and efficient power distribution in outdoor and public locations. The low operating costs, low heat emissions, and low cost of ownership makes this transformer ideal for a wide range of applications and businesses. This power distribution system is designed for overhead, pole mount installations and use.

AES Part # - 10.523.682

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 25 kVA, the industrial transformer features a primary voltage of 13200Y/7620 Grounded Wye and a secondary voltage of single-phase 120/240V (L-N-L). This transformer connects to a three phase electrical grid system to provide single phase low voltage power for

indoor distribution. This pole mount transformer features porcelain high-voltage, dual bushings on the primary side and three bushings on the secondary side. Equipped with copper windings and a grain oriented steel core, this overhead distribution transformer consists of one coil and two core loops. Tin plated terminals on the primary and secondary side accepts copper or aluminum connections.

The MT-UPM-R11-1P-GMQ-25KVA-SZ-A6-BF-CZ-2ZZ-M1 is air cooled and does not have fans or mounting provision for fans. This unit features a 65°C temperature rise for reduced heat waste, increased reliability and longer life. The combination of low temperature rise and high efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations, in addition to outdoor areas.

Insulation Fluid: The MT-UPM-R7-1P-GNF-75KVA-SZ-BF-A6-BM-CZ-2ZZ-M1 features FR-3 oil insulation fluid. Internal marking is available for proper oil level monitoring. We offer transformers with mineral oil fluid, if needed.

Gauges: This transformer is equipped with a liquid level gauge. We can add temperature and pressure/vacuum gauges at an additional cost. Standard liquid level, temperature, and pressure/vacuum gauges are analog, manual reading types.

Pressure Relief Device: An automatic pressure relief device is included with this transformer.

Rapid Rise Relay: There are no rapid rise relays on the unit. This safety component is designed for protection when a rapid increase in tank pressure occurs. The relay is suitable for detecting sudden pressure fluctuations above predetermined safe limits.

Surge Arrestors: This system is equipped with one lightning arrestor with bird guard. Mounting provisions for installing customer provided lightning arrestor on the H1 and H2 primary terminal are included for installing arrestors in-field.

Valves: The MT-UPM-R11-1P-GMQ-25KVA-SZ-A6-BF-CZ-2ZZ-M1 is not equipped with a fill valve. The transformer can be filled via removing the top lid. A 1/2" NPT drain port w/ removable bolt plug is equipped.


Protection Fuses: This transformer does not contain fuses or circuit breakers. For units without protection fuses, up stream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.


Mount: The heavy-duty enclosure makes the unit suitable for outdoor applications. Equipped with hangar brackets and lifting lugs, this overhead power distribution system can be mounted on poles.


Benefits: The MT-UPM-R11-1P-GMQ-25KVA-SZ-A6-BF-CZ-2ZZ-M1 heavy-duty transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

We offer completely self protected (CSP) pole mount overhead transformers at an additional cost.

Applications: General purposes, industrial sites, electrical rooms, public locations, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities, public locations, and more. Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



90
100
80
SINGLE PHASE POLE MOUNTED TRANSFORMER
MT-UPM-R11-1P-GMR-25KVA-SZ-A6-BF-CZ-2ZZ-M1
Phase: 1PH
25
KVA
Impedence
1.0~2.2
%
BIL
95/30
KV
HV
13200GrdY/7620
V
LV
120/240
V
Freq.
60
Hz
Phasor
II0
Serial NO.
833D25-C1
Product ID
Vol of Oil
19
Gal
Total Mass
434
LBS
HV/LV Con.
Copper
Cooling
ONAN
Temp.Rise:
65°C
Tank must be solidly grounded-NON-PCB Biodegradable Oil
Subtractive Polarity
% HV
TAPS
8001
1/A
7811
2/B
7620
3/C
7430
4/D
7239
5/E
H1
X1
X2
X3
H1
A
C
B
D
X1
X2
X3
LV
LV
2
2
LV
ANSI C57.12.20-DOE 2016 Compliant-Manufactured 2023.08
LARSON MAGNETICS
Larson Magnetics LLC
Kemp, TX USA






Approx Weight: 434 Lbs
Non-PCB Containing Oil

No.	Name	Remarks
23	Paint spec	
22	Lifting lug	
21	Core & coil	
20	Insulation oil	
19	Tank	
18	Drain valve	
17	Tap changer	
16	Pressure relief valve	
15	Grounding strap	
14	Washer 12	
13	Bolt M12x25	
12	LV bushing	
11	Sealing gasket	
10	Cover	
9	Washer 12	
8	Bolt M12x30	
7	Screw M4x6	
6	Nameplate	
5	Hold down gear	
4	Ground strap	
3	Washer 12	
2	Bolt M12 x 20	
1	HV Bushing	



wiring diagram



All dimensions are in inches

For approval / preliminary design only. Not for order build specific

Designed by:	Checked by:	Approved by:	k.V.A:	Votage:	Date:	Scale:	Note! Do not scale copies

LARSON ELECTRONICS

13200GrdY/7620V Pri - 240/120V Sec,
25kVA Pole Mounted Transformer

Drg. No. :	Code:	Paper:	Rev.	Sheet:


MISTER




100
LARSON
ELECTRONICS


WARNING

Frequently Asked Questions (FAQ)