Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-GPU-3P-566D-106KVA-235D-N3R-AL-M1

106 kVA 3PH Inverter Transformer for Ground Power Units, 566V Delta Primary, 235V Wye Secondary, 260-A, Aluminum, NEMA 3R, 400 Hz

Product ID: 301888



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-MT-ISX-3P-480D-150KVA-480D-N3R-EB-M1 Inverter Transformer for Ground Power Units

Transformer Type: Inverter Transformer
Transformer Configuration: Dry Type
Phase: Three Phase
Frequency: 400 Hz
Primary Voltage: 566V AC @ 3 x 36A
Primary Connection: Delta
Capacity: 106 KVA
Secondary Voltage: 235 AC @ 260.4A
Secondary Connection: Wye
Vector Group: DDDyn1
No-load Transformer Tolerance: +/- 0.5%
Short Circuit Impedance: 1.20 +/- 10% base 106KVA
Protection:
FCAN (Above) Taps: 2
FCAN (Above) Taps: 4
Tap %: 2.5%
Impedance: 2.5-6.5% Typical
Efficiency @ 35% Load: ~98%
Core Material: Grain Oriented
Winding Material: Aluminum
Protection of Windings: Resin Impregnation & Final Black Paint Coating
Primary Termination (Std): Bus Bars, (3 x 3) AL Busbars 15x3 mm with 1 hole 7mm
Secondary Termination (Std): Bus Bars, (3+1) AL Busbars 25x5 with 1 hole 9mm
Termination Access: Front Access Cover
Mounting: Floor

Approvals/Ratings

NRTL Listed for United States
NRTL Listed for Canada
NEMA 3R Indoor/Outdoor Steel Enclosure
Meets or Exceeds NEMA ST-20 Standards
Isolation Transformer
Distribution Type Transformer
Built to UL-50 Standards
Seismic Qualified for Earthquake Loads
RoHS

CE Certified

Cooling: Air/Dry
Insulation: 220°C
Temperature Rise: 150°C
Sound Level: 60dB,at 1m
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated - Steel
Finish: ANSI 61 Grey
Dimensions: (510up/495Low) x 235 x (428core/445bars) in mm
Weight: 970 lb
Shipping Method: Pallet Freight - LTL
Shipping Weight: 1080 lb
Shipping Dimensions: 48"-L x 60"-W x 50"-H

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-GPU-3P-566D-106KVA-235D-N3R-AL-M1 Three Phase 566 to 235 106 KVA Inverter Transformer for Ground Power Units from Larson Electronics is powerful, reliable, and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-GPU-3P-566D-106KVA-235D-N3R-AL-M1 provides increased reliability and protection against critical equipment failures.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: The MT-GPU-3P-566D-106KVA-235D-N3R-AL-M1 Inverter transformer is a three phase transformer with a 106 KVA capacity rating. This inverter transformer is configured with an input voltage of 566V Delta 3-Phase AC on the primary side and an output voltage of 235V Wye 3-Phase AC on the secondary side. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and is designed to be floor mounted. Wall mount brackets or additional mounting accessories can be purchased separately. This 106 KVA distribution transformer features 220°C insulation with a 150°C temperature rise.

Benefits: The MT-GPU-3P-566D-106KVA-235D-N3R-AL-M1 566V to 235 general purpose transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

The MT-ISX series of isolation transformers from Larson Electronics meet or exceed efficiency standards for United States and Canada. This results is overall lower cost of ownership throughout the life of the transformer.

Safety: The MT-GPU-3P-566D-106KVA-235D-N3R-AL-M1 is an isolation transformer which means that it provides operators with an increased level of protection against electric shock and injury. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-GPU-3P-566D-106KVA-235D-N3R-AL-M1 achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: Converting 566V local grid power to 235 for on-site equipment. This 106 KVA power transformer is ideal for sensitive equipment such as CNC equipment, computers, medical devices, ovens, or laboratory instruments. Larson Electronics is a manufacturer and as such can build stationary and portable

transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.




Larson Electronics
1-800-369-6671



Frequently Asked Questions (FAQ)