Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

## MT-PSTH-R7-3P-DRC-7.5MVA-YMS-HNS-LNS-A6-AB-CZ-2ZZ-M1

# 7.5 MVA (7500 KVA) Hermetically Sealed Substation - 44000V Delta Primary, 27600Y/15936 Wye Secondary - Biodegradable Fluid, KNAN/KNAF, Fan Cooled

**Product ID: 302612**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

| MT-PSTH-R7-3P-DRC-7.5MVA-YMS-HNS-LNS-A6-AB-CZ-2ZZ-M1 Hermetically Sealed Transformer | Ratings |
|---|---|
| **Transformer Type: Substation Power Transformer, Hermetically Sealed** | Meets/Exceeds DOE 2016 Efficiency Ratings |
| **Transformer Configuration: Liquid Filled Pad Mounted** | Meets/Exceeds CSA Efficiency Ratings |
| **Transformer Feed Type: Radial Feed** | Complies with ANSI / IEEE C57.12.00 |
| **Operation: Approved for Step-Up and Step-Down Operations** | Complies with ANSI / IEEE C57 12.28 |
| **Phase: Three Phase** | Complies with ANSI / IEEE C57 12.29 |
| **Capacity (w/o Fan): 7.5 MVA (7500 KVA)** | Complies with ANSI / IEEE C57 12.34 |
| **Capacity (w/ Fan): 10 MVA (10000 KVA)** | Complies with ANSI / IEEE C37.47 |
| **Vector Group: DYN11** | Complies with ANSI / IEEE C57 12.35 |
| **Primary Voltage: 44000V** | Complies with ANSI / IEEE C57.12.70 |
| **Primary Voltage Switch: N/A** | Complies with ANSI / IEEE C57.12.110 |
| **Primary Voltage Class: 46 kV Class** | Complies with ANSI / IEEE C57.12.131 |
| **Primary Phasor: Delta** | Complies with ANSI / IEEE C62.11 |
| **Primary BIL: 250 kV** | Complies with ANSI / IEEE C62.22 |
| **Secondary Voltage: 27600Y/15936** | Complies with ANSI / IEEE 386 |
| **Secondary Voltage Class: 35 kV Class** | Complies with ANSI / IEEE C2 |
| **Secondary Phasor: Wye-N** | Complies with ANSI Z535.4 |
| **Secondary BIL: 150 kV** | Complies with 10 CFR Part 431 |
| **Frequency: 60 HZ** | Complies with ASTM D3487 |
| **Temperature Rise: 55°C** | Complies with ASTM D6871 |
| **Insulation Rating: Class E Insulation - 120°C, 248°F** | Complies with NEMA 260-1996 |
| **Cooling Class: KNAN; Self-Cooled** | Complies with CSA C802.1 |
| **Forced Air (Fans): Included** | Complies with CSA C2.1-06 |
| **Tap Changer: 5-Position Off-Load Tap Changer** | Complies with CSA C50 |
| **Tap Qty: (2) FCAN Above Taps, (2) FCBN Below Taps** | Complies with CSA C88 |
| **Tap %: 2.5% Taps** | Complies with CSA C88.1 |
| **Tap Changer Switch Rating: 46 kV, On-Load Rated** | Complies with CSA C88-16 |
| **Tap Changer Switch Location: High Voltage (HV) [Left Side]** | Complies with CSA C227.4 |

**Impedance (Typical): 7.5%**
**Primary Connection Type: Live Front**
**Primary Termination Arrangement: Side Mounted Terminals w/ Air Terminal Chamber to Ground**
**Primary Termination: Porcelain Bushings**
**Primary Connection Qty: (3) Primary Connections**
**Primary Bushing Rating: 46 kV Class, 250 kV BIL**
**Primary Neutral Connection: N/A**
**Primary Surge Arrestors: Included**
**Primary Surge Arrestor Voltage Rating: 39kV**
**Primary Surge Arrestor MCOV Rating: 39kV, MCOV Rating**
**Primary Over Current Protection (OCP): N/A**
**Primary Over Current Protection Method: N/A**
**Primary Over Current Protection Holder: N/A**

**Primary Grounding Provisions: N/A**

**Secondary Connection Type: Live Front**
**Secondary Termination Arrangement: Side Mounted Terminals w/ Air Terminal Chamber to Ground**
**Secondary Connections: Porcelain Bushings**
**Secondary Connection Qty: (4)**
**Secondary Connection Supports: N/A**
**Secondary Over Current Protection (OCP): N/A**
**Secondary Neutral Connection: N/A**
**Secondary Grounding Provisions: (1) NEMA Ground Bar Attached to Tank via (2) Welded Ground Bungs**
**Metering Current Transformer (CT): N/A**
**Metering Panel: N/A**
**Auxiliary Control Panel : N/A**
**Load Break Switch: N/A**
**Load Break Switch Qty: N/A**
**Load Break Switch Rating: N/A**
**Load Break Switch Location: N/A**
**Efficiency Standard(s): Meets ANSI/IEEE Standards**
**K-Factor Rating (Harmonic Mitigation): K-1 (Standard)**
**Pulse Drive Rating: Appropriate For Use With 6-Pulse Drive Equipment On Secondary Side**
**Insulation Fluid: Biodegradable Fluid Oil**
**Fluid (Oil) Capacity*: TBD**
**Fluid (Oil) Weight*: TBD**
**Oil Level Indicator: Analog Dial Gauge**
**Oil Temperature Indicator: Analog Dial Gauge**
**Pressure/Vacuum Indicator: Analog Dial Gauge**
**Pressure Relief Device: Included, Automatic Action**
**Fault Indicator: N/A**
**Gas Sampler Valve: N/A**
**Fill Valve: N/A**
**Fill Valve Location: N/A**
**Oil Drain Valve: 1" NPT Port w/ 5/8" NPT Sampler Valve**
**Drain Valve Location: Front Compartment**
**Winding Material: Copper**
**Ambient Temperature Rating: 40°C**
**Ambient Operating Temperature Range: -40°C to +40°C (-50°F to +104°F)**

**Sound Level: 67 dBA**

**Elevation (Altitude): 3300ft (1000 meters) Above Sea Level**
**Core Material: Grain Oriented Steel**
**Tank Material: Coated Steel**
**Cabinet Material: Coated Steel**
**Base Platform Material: Coated Steel**
**Portability: Lifting Lugs, Provisions for Jacking Under Base, w/ Base Construction Suitable for Using Rollers or Skidding**
**Housing Type: Metal Casing Liquid Filled Transformer**
**Enclosure Rating: NEMA 3R Weatherproof Wiring Cabinet, Sealed Tank**
**Seismic Rating: Yes**
**Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating**
**Finish Color: White**
**Mounting: Skid Type Base w/ Lifting Lugs**
**Conduit Opening: N/A**
**Tank Cover Access Handhole: N/A**
**Dimensions*: -**

Complies with CSA C227.5
Complies with CSA C802-3

**Features**
Hot Stick Included, HV Door Mount
Pentahead Bolt Entry Assembly
High-Fire Point Insulating Fluid
Non-PCB Insulating Fluid
Tamper Proof Housing
Hinged Front Compartment Doors, Pad Lockable
NEMA 3R Wiring Compartment

**Efficiency %: 98.00%**
*Based on transformer operating at 50% of nameplate base kVA.*

**Load Losses Based on 85°C Reference Temp.**

**No Load Loss (in watts): TBD**
**Full Load Loss (in watts) at 100%: TBD**
**Total Load Loss (in watts) at 100%: TBD**

**Total Losses at 55°C LL Temp.& 20°C NL Temp.**

**Total Load Loss (in watts) at 50%: TBD**

***Note: Losses offered are typical only, not guaranteed***

**Labeling:**
Externally Stencilled (Painted) KVA Rating
Externally Stencilled (Painted) Voltage Rating
External Non-PCB Label
External Warning & Danger Label
External Barcode Label
Internal Busing & Accessory Labeling

Stainless Steel Riveted Nameplate

**Factory Tests:**
Winding Resistance Test
Insulation Resistance Test
Voltage Ratio Error Test
Short-circuit Impedance Test
No-load Loss (Wattage) Test
Load Loss (Wattage) Test
Induced Voltage Withstand Test
Separate Source Voltage Withstand Test
Pressure Integrity Test Test

**Shipping:**
Shipped on pallet on open flatbed
Palletized on Wooden Pallet w/ Skid Pockets
Pallet Skid Facing Outward Sides of Truck
***Note: Crated shipping in lieu of palletizing can be done upon request for an additional fee***

**Special Orders - Special Requirements**
Contact us for special requirements
**Toll Free: 1-800-369-6671**

**Dry Weight (w/o Oil)*: -**
**Total Weight (Liquid Filled)*: -**
*Please note that numbers are approximate and subject to change

**Intl: 1-903-270-1187**
**Fax: 1-903-498-3364**
**E-mail: sales@larsonelectronics.com**

**The MT-PSTH-R7-3P-DRC-7.5MVA-YMS-HNS-LNS-A6-AB-CZ-2ZZ-M1 Hermetically Sealed Transformer from Larson Electronics offers powerful, reliable, and efficient power distribution in indoor or outdoor locations. The low operating costs, low heat emissions, and low cost of ownership makes this transformer ideal for a wide range of applications and businesses. This air tight transformer does not have doors and must be installed in a contained or protected area away from public access.**
***PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****
**Transformer Features:** The industrial transformer features a primary voltage of three-phase 44000V Delta and a secondary voltage of three-phase 27600Y/15936 Wye-N. This system carries the following ratings: 7.5 MVA (7500 KVA) with fan cooled capacity: 10MVA (10000 KVA). The unit has a primary radial feed and live front primary connections. We also offer systems with loop feed and dead front primary connections. This transformer features a 5-position tap changer with two, +/- 2.5% taps above and two, +/- 2.5% taps below to allow small changes for voltage. There are no load break switches, rapid rise relays, or protection fuses present on the system.
The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of rectangular coil and five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).
The MT-PSTH-R7-3P-DRC-7.5MVA-YMS-HNS-LNS-A6-AB-CZ-2ZZ-M1 is completely sealed and features air tight construction. Designed for long-term performance, the transformer is maintenance free.
**Temperature Rise:** This unit features a 55°C ambient temperature rating and a 55°C temperature rise for reduced heat waste, increased reliability, and longer life. At 55°C temperature rise, the transformer offers 7.5 MVA (7500 KVA). The transformer meets standard efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations, in addition to outdoor areas.
**Insulation Fluid:** The MT-PSTH-R7-3P-DRC-7.5MVA-YMS-HNS-LNS-A6-AB-CZ-2ZZ-M1 transformer features biodegradable fluid (KNAN).
**Gauges:** The following gauges are included with the system: oil level indicator, oil thermometer, and pressure/vacuum gauge. Standard oil level indicator, oil thermometer, and pressure/vacuum gauges are analog, manual reading types. These gauges do not have alarm contacts.
**Fault Pressure Devices:** There are no fault pressure devices on the unit. Fault pressure devices are used to detect high rates of pressure rise within the tank.
**Rapid Rise Relay:** There are no rapid rise relays on the unit. This safety component is designed for protection when a rapid increase in tank pressure occurs. The relay is suitable for detecting sudden pressure fluctuations above predetermined safe limits.
**Surge arresters:** This system comes with surge arresters on the primary and secondary side. Designed for over-voltage and transient voltage protection, the components prevent damage caused by lightning, internal switching or voltage surges. We can offer models without high elbow surge arresters that have mounting provisions for customer-provided surge arresters.
**Load Breaker Switch:** The transformer is not equipped with a load breaker switch.
**Valves:** The MT-PSTH-R7-3P-DRC-7.5MVA-YMS-HNS-LNS-A6-AB-CZ-2ZZ-M1 is equipped with an oil drain valve, an oil sampling valve, and a pressure relief valve.
**Protection Fuses:** This transformer does not have bayonet protection fuses on the primary side. For units without protection fuses, up stream protection is provided. We recommend provisions for protection fuses when possible, as blown

fuses may require more frequent oil changes.
**Terminal Connections:** The primary and secondary terminal connections are located on the top of the transformer. We can configure the location to be top located or side located for both the high voltage and low voltage sides.
**Mount:** This hermetically sealed transformer is equipped with a skid type base with lifting lugs.
**Benefits:** The MT-PSTH-R7-3P-DRC-7.5MVA-YMS-HNS-LNS-A6-AB-CZ-2ZZ-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.
**Applications:** General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities, and more.
Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

# Frequently Asked Questions (FAQ)