Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-PDT-VPM-R7-1P-GRH-37.5KVA-SZ-A6-BZ-CZ-1Z-ZZ-Z-M1

37.5 KVA Vacuum Pressure Impregnated Transformer - 25565Y/14760 Grounded Wye Primary, 240/120V 1P Secondary - ANN/Class H, Hermetically Sealed Tank

Product ID: 304420

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PDT-VPM-R7-1P-GRH-37.5KVA-SZ-A6-BZ-CZ-1Z-ZZ-Z-N3R-M1 Vacuum Pressure Impregnated Transformer

Transformer Type: Vacuum Pressure Impregnated (VPI) Transformer, Hermetically Sealed
Transformer Configuration: Dry Type
Phase: Single Phase
Capacity: 37.5 KVA
Vector Group: -
Primary Voltage: 25565GrdY/14760
Primary Voltage Class: 25 kV Class
Primary Phasor: Grounded Wye
Primary BIL: 95 kV
Secondary Voltage: 240V/120 L-N-L
Secondary Voltage Class: 1.2 kV Class
Secondary Phasor: Single Phase
Secondary BIL: 30 KV
Frequency: 60 Hz
Temperature Rise: 65°C
Cooling: ANN
Forced Air (Fans): N/A
Insulation Class: Class H
Tap Changer: Included
Tap Qty: (5) 2.5% Taps - (2) FCAN Above, (2) FCBN Below
Tap %: 2.5%
Tap Changer Switch Location: Side of Tank
Impedance (at 120°C): N/A
Primary Connection Type: Dead Front Bushing
Primary Termination: Top Mounted Terminal, Well in Air Bushing
Primary Connection Qty: (2) Primary Connections, Dead Break
Primary Surge Arrestors: N/A
Primary Surge Arrestor Voltage Rating: N/A
Primary Surge Arrestor MCOV Rating: N/A
Primary Over Current Protection (OCP): N/A
Primary Over Current Protection Method: N/A
Primary Over Current Protection Holder: N/A
Primary Grounding Provisions: N/A
Secondary Connection Type: Live Bushing Lugs
Secondary Connections: Top Mounted Terminal, NEMA 4-Hole Spade
Secondary Connection Qty: (3)
Secondary Over Current Protection (OCP): Overcurrent / Undercurrent Relay (N/O)
Secondary Grounding Provisions: (1) NEMA Ground Bar Attached to Tank via (2) Welded Ground Bungs
Metering Current Transformer (CT): N/A
Metering Panel: N/A

Ratings

Listed for United States and Canada

NEMA 3R Enclosure

Efficiency %: N/A
Based on transformer operating at 50% of nameplate base kVA.

Load Losses at 145°C Reference Temp.
Fixed Load Loss (in watts): +/- N/A
Full Load Loss(in watts): +/- N/A
Total Load Loss (in watts): +/- N/A

Note: ***Losses offered are typical only, not guaranteed***

Auxiliary Control Panel : N/A
Load Break Switch: N/A
Load Break Switch Qty: N/A
Load Break Switch Location: N/A
Efficiency Standard(s): N/A
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Temperature Sensors in Coil: Included
Temperature Gauge: Included with normally open contact
Seismic Bracing: N/A
Weather Shield: N/A
Cabinet Space Heaters: N/A
Winding Material: Copper
Ambient Temperature Rating: N/A
Sound Level: N/A
Elevation Rating: N/A
Housing Type: Metal Casing Dry Type Transformer,
Enclosure Material: Coated Steel
Enclosure Rating: N/A
System Form Factor: N/A
Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating
Finish: ANSI 61 Grey Finish Color
Mount: Skid Mount
Dimensions: N/A
Weight: N/A
*Please note that numbers are approximate and subject to change

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-PDT-VPM-R7-1P-GRH-37.5KVA-SZ-A6-BZ-CZ-1Z-ZZ-Z-N3R-M1 Vacuum Pressure Impregnated Transformer from Larson Electronics converts three-phase 25565Y/14760 Grounded Wye electrical current to single-phase 240/120V L-N-L. This power distribution unit provides operators the ability to safely tap into and distribute 600V AC power from a variety of sources, such as direct grid power. The entire system is secured to a skid mount platform.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 37.5 KVA, the industrial dry type transformer features a primary voltage of three-phase 25565Y/14760 Grounded Wye and a secondary voltage of single-phase 240/120V L-N-L. This transformer is equipped with a tap changer with five, +/- 2.5% taps (two FCAN above and two FCBN below) to allow small changes for voltage. The system has copper windings for high strength and electrical conductivity. This VPI transformer features minimized air gaps and voids in the insulation, leading to increased durability and thermal stability.

The MT-PDT-VPM-R7-1P-GRH-37.5KVA-SZ-A6-BZ-CZ-1Z-ZZ-Z-N3R-M1 does not have fans or mounting provision for fans.

Transformer Efficiency: The Class H transformer meets standard efficiency requirements. High efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations, in addition to outdoor areas.

Temperature Sensor: The MT-PDT-VPM-R7-1P-GRH-37.5KVA-SZ-A6-BZ-CZ-1Z-ZZ-Z-N3R-M1 is equipped with temperature sensors inside the system for controls and monitoring. A monitoring service is not included with the transformer.

Temperature Gauge: This transformer comes with a temperature gauge.

Load Break Switch: This VPI transformer does not include a load break switch. We can add a load break switch at an additional cost.

Surge Arresters: This transformer does not include surge arresters. Designed for over-voltage and transient voltage protection, the components prevent damage caused by lightning, internal switching or voltage surges. We can offer models without surge arresters that have mounting provisions for customer-provided surge arresters.

Control Transformer: This VPI transformer does not include a control transformer. We can add a control transformer for operating equipment at an additional cost.
Seismic Bracing: This system does not include seismic bracing. We can add seismic bracing for added protection in areas prone to earthquakes at an additional cost.
Weather Shield: This transformer does not include a weather shield. We can add a weather shield for protection in outdoor areas, humid environments and rodents at an additional cost.
Space Heaters: This system does not include a space heater. We can add a space heater for preventing condensation during extended shutdown at an additional cost.
Enclosure Design: This VPI transformer is protected by a steel housing. The enclosure carries a NEMA 3R rating for protection from exposure to moisture, rain, dust and debris.
Mount: The power distribution unit is mounted atop a skid plate base that allows this transformer to easily be moved from one location to another using a forklift. The skid platform is designed for serious use and is ruggedly constructed to withstand demanding conditions and heavy duty industrial applications. The industrial grade skid platform can be modified to meet the needs of job-site requirements.
Benefits: The MT-PDT-VPM-R7-1P-GRH-37.5KVA-SZ-A6-BZ-CZ-1Z-ZZ-Z-N3R-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.
Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities, public locations and more. Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Frequently Asked Questions (FAQ)